



Pentaplex touch-screen standalone DVR (SA-2608)

- Aluminum alloy draw-bench panels
- H.264 compression
- 3G connectivity
- Simultaneous live recording/playback
- PTZ camera control in remote areas
- CD-RW/DVD-RW/USB 2.0/Internet backup
- 4.3" LCD monitor
- Mouse/remote/touch screen control
- Date/time, event, schedule and alarm management
- 720 x 480 (NTSC) and 704 x 576 (PAL) real-time D1 display
- Motion detection and e-mail notification functions



Source from a one-stop

200 models to choose from

We provide one-stop solutions to your security needs. Our catalog boasts 200 models, including DVRs, monitors and other related items, as well as IP, IR day/night, waterproof, dual CCD, PTZ and box cameras. In addition to developing three new products monthly, our 45 R&D engineers can create custom samples within two weeks.

Two-year guarantees for every camera

We never compromise on quality. That's why our five inspectors subject our cameras to a strict five-step QC regimen, using frequency

and age testing machines, as well as signal generators. As such, we can confidently back our CE-, FCC- and RoHS-marked devices with two-year warranties.

Value-added services

In the event that you find defective units in your order, we offer technical support and provide replacements up to three months after your purchase. To start reaping the benefits that we offer, speak to our sales staff in English, Spanish, Portuguese, German or French today.

security solutions provider



sanan Shenzhen Sanan Technology Co. Ltd

Units 23L-N, Block A, Fortune Plaza, 7002 Shennan Rd.,
Futian, Shenzhen, Guangdong 518040, China
Tel: (86-755) 8202 8688/8988 • Fax: (86-755) 8385 0555
E-mail: sanancctv@globalsources.com • sanan@sanan-cctv.com
Website: www.globalsources.com/sanancctv.co • www.sanan-cctv.com



Waterproof IR camera (SA-1590)

- IP66-rated
- 1/3" Sony Super HAD CCD II
- 420-700TVL models available
- 4-9mm varifocal lens, 2.8-12mm types available
- 36 x 5mm IR LEDs, 35-40m viewing distance



H.264 DVR (SA-2203G)

- D1 resolution
- 2.5" HDD
- GPS and 3G connectivity
- 4-ch. input, 1-ch. output



IR LED camera (SA-1545)

- IP66-rated
- 1/3" Sony Super HAD CCD II
- 72 x 5mm IR LEDs, 60m viewing distance
- 4-9mm manual lens, 9-22mm adjustable external types available
- 3-axis bracket
- 420-700TVL models available



Waterproof IR camera (SA-1553)

- IP66-rated
- 1/3" Sony Super HAD CCD II
- 420-700TVL models available
- 4-9mm manual lens, adjustable external types available
- 36 x 5mm IR LEDs, 30m viewing distance
- Built-in cable bracket



IR dome camera (SA-1811)

- IP66-rated
- 1/3" Sony Super HAD CCD II
- 72 x 5mm IR LEDs, 60m viewing distance
- 4-9mm manual lens, 9-22mm adjustable external types available
- 420-700TVL models available
- 3-axis bracket