A QC regimen Ford and UPS trust

ISO/TS 16949:2009-certified facilities to ensure consistent quality Just as Ford and UPS do, you too can source from one of the first car rearview system manufacturers in mainland China. These big-name buyers appreciate our comprehensive QC processes that are overseen by 25 technicians. They conduct a gamut of inspections in our ISO/TS 16949:2009-certified factory, including salt spray, fog resistance, plating adhesion, high- and low-temperature, and waterproofing tests. With such a commitment to quality, it should come as no surprise that we count 70 percent of bus manufacturers in mainland China among our clients.

25% of profits invested in R&D annually

Thanks to the work of our 18 R&D engineers, and the cooperation of the Hong Kong Polytechnic University and the China Automotive Engineering Research Institute, we have gained six domestic patents for our products. And we invest 25 percent of our annual profits in R&D to offer you comprehensive OEM/ODM services.

Components from Sony, Sharp and Samsung

We test all the materials we source to an AQL of 0.65. This includes ICs from National Semiconductor, panels and sensors from Sony and Sharp, and capacitors and resistors from Samsung. Alternatively, by using components procured locally, we can offer you cost savings of up to 60 percent. To find out more, contact us today. Digital wireless IR camera system (MS-708RSW)

ISO 9001:2008 FC CE 😨 🖉

Shenzhen Mingshang Industrial Co. Ltd

No. 1, Mingshang Industrial Area, Shiao, Dalang, Longhua, Shenzhen, Guangdong 518033, China Tel: (86-755) 2807 8528/8538 • Fax: (86-755) 2807 8755 E-mail: mingshang@mingshang.com

Website: www.globalsources.com/mingshang.co www.mingshang.com





- Side-view camera (MS-780) • IP67-rated
- 10m IR viewing distance
- Built to withstand the shock and vibration associated with industrial use



- Mini 360° rotation dome camera (MS-772) • IP67-rated
- 10m IR viewing distance



- IR camera with audio recording function (MS-750)
- IP68-rated and dust-resistant
- 10m IR viewing distance
- Can withstand 20G vibrations and 100G impacts
- Auto-heating function (optional)



global

Verified supplier

- Digital wireless IR camera system (MS-643RSW)
- 4.3" monitor
- Digital signal with no interference
- Two bracket options
 - Low-glare mirror