



EN IEC 62680-1-3 Test Report

24B01N000775-001-COM

For

Type-C Receptacle Connector

Company Name: Guangdong Jinshengxin Industry Share Co., Ltd.

Product Name: USB TYPE C FEMALE 16PIN 180° TYPE

Model Name: JSX-CF-009

Hardware Version: A

Issued Date: 2024-04-12

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SACT.

Test Laboratory:

SACT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen,
Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email:yewu@sact.ac.cn, www.sact.ac.cn

A-3-2	Durability (preconditioning)
A-3-3	Temperature life (preconditioning)
A-3-4	Low level contact resistance
A-3-5	Vibration
A-3-6	Low level contact resistance
Group A-4	
No.	Test Item
A-4-1	Low level contact resistance
A-4-2	Durability (preconditioning)
A-4-3	Temperature life (preconditioning)
A-4-4	Low level contact resistance
A-4-5	Mixed flowing gas
A-4-6	Low level contact resistance
A-4-7	Thermal disturbance
A-4-8	Low level contact resistance
A-4-9	Reseating
A-4-10	Low level contact resistance
Group A-7	
No.	Test Item
A-7-1	Dielectric withstanding voltage
A-7-2	Low level contact resistance
A-7-3	Durability (preconditioning)
A-7-4	Insertion force
A-7-5	Extraction force

A-7-6	Durability
A-7-7	Extraction force
A-7-8	Durability
A-7-9	Extraction force
A-7-10	Low level contact resistance
A-7-11	Dielectric withstanding voltage
A-7-12	Insulation Resistance
Group B-1	
No.	Test Item
B-1-4	4-Axis Continuity
Group B-5	
No.	Test Item
B-5-1	Critical Dimensions
Group B-6	
No.	Test Item
B-6-1	Contact Current Rating

7. Test Result Summary

Test Item	Clause	Result
Construction	3.2.1 (6)	Pass
Critical Dimensions	3.2.1 (8)	Pass
Low level contact resistance	3.7.8.1	Pass
Dielectric withstanding voltage	3.7.8.2	Pass
Insulation Resistance	3.7.8.3	Pass
Contact Current Rating	3.7.8.4	Pass
Insertion force	3.8.1.1	Pass
Extraction force	3.8.1.2	Pass
Durability	3.8.1.3	Pass
Reseating	3.8.1.3	Pass
4-Axis Continuity	3.8.1.6	Pass
Temperature life	3.8.2	Pass
Thermal shock	3.8.2	Pass
Cyclic temperature and humidity	3.8.2	Pass
Vibration	3.8.2	Pass
Mixed flowing gas	3.8.2	Pass
Thermal disturbance	3.8.2	Pass



8. Test Detail

8.1. Clause 3.2.1 (6) Construction


Construction			
Testing Period	Measure environment	Test Engineer	Test Result
2022/06/23	Temp.20.65 °C/ 62.9 %RH	Liu Baoming	Pass

EMC ground return path			
Description	Sample Coding		
	B5-1	B5-2	B5-3
1.EMC spring	Y	Y	Y
2.EMC pad	N	N	N
3.Solid bumps	N	N	N
4.Distance between the bumps	N/A	N/A	N/A
Result	Pass	Pass	Pass

Note:
 Receptacle configurations with a conductive shell.
 The requirements apply to the receptacle contact dimensions shown in ALTERNATE SECTION A-A Figure B-5.
 Receptacle configuration with respect to mounting surface: Right angle

Number of pins: 14

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
✓	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	✓
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
✓	N/A	N/A	✓	N/A	✓	✓	✓	✓	N/A	N/A	✓

Tongue photograph

8.2. Clause 3.2.1 (8) Critical Dimensions

B-5-1 Critical Dimensions			
Testing Period	Measure environment	Test Engineer	Test Result
2019/10/08	Temp: 25.6 °C/ 62.9 %RH	Liu Baoming	Pass

Test data: (Unit:mm)			
B-5-1 Critical Dimensions – Receptacle			
Description	Sample Coding		
	B5-1	B5-2	B5-3
1.Receptacle inside opening (8.32~8.40)	8.323	8.324	8.321
2.Receptacle inside opening position tolerance (0.04 with datum A/B/C)	0.028	0.016	0.024
3.Receptacle signal pin length (3.35~3.65)	3.376	3.362	3.369
4.Pin length delta (0.30-0.70)	0.348	0.372	0.373
5.Tongue width (6.635~6.735)	6.714	6.708	6.707
6.Contact width (0.21~0.29)	0.235	0.235	0.243
7.Contact width position tolerance (0.08 with datum A/B/C)	0.010	0.016	0.024
8. Tongue thickness (0.65~0.75)	0.735	0.733	0.739
9.Receptacle inside thickness (2.52~2.60)	2.592	2.597	2.596
Decision result	Pass	Pass	Pass

8.3. Clause 3.7.8.1 Low level contact resistance

A-1-1 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11	Temp: 22.1 °C/ 69.9 %RH	Zhan Xingcheng	Pass
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

测试记录/测试												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A1-1	20.8			20.1	21.6	22.0	21.5	21.5	21.9			20.8
A1-2	21.5			23.8	24.4	22.7	22.0	24.0	28.5			28.6
A1-3	22.5			26.7	21.8	22.7	22.4	21.5	22.7			20.1
A1-4	18.7			21.1	19.7	19.5	19.6	18.7	20.8			18.2
A1-5	21.3			22.3	20.7	20.8	21.1	21.3	22.0			20.7
A1-6	21.4			21.8	21.4	20.7	19.9	20.5	22.1			19.8
A1-7	20.7			21.5	21.7	20.9	20.1	20.9	21.5			22.1
A1-8	22.3			22.4	22.0	22.4	22.0	21.1	22.7			21.5
A1-9	21.4			21.9	22.5	22.2	22.2	24.0	24.8			21.9
A1-10	22.5			22.0	19.7	19.6	19.3	20.7	18.1			18.3
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A1-1	21.2			20.5	19.7	19.4	18.7	19.2	20.9			19.8
A1-2	21.9			22.0	20.2	23.1	19.7	22.8	20.8			18.8
A1-3	18.7			19.2	19.4	19.2	18.1	19.3	20.2			18.4
A1-4	21.7			22.8	21.5	22.5	20.9	21.2	20.2			20.6
A1-5	19.3			19.7	20.3	19.0	18.9	19.1	20.3			20.6
A1-6	22.1			20.3	19.6	19.6	18.3	19.5	20.4			19.8
A1-7	21.3			21.1	20.2	19.8	19.8	27.8	20.8			18.7
A1-8	20.7			20.1	20.1	19.0	19.9	19.6	22.3			18.7
A1-9	19.2			20.3	18.9	19.3	18.1	18.7	20.1			18.6
A1-10	20.9			22.8	22.6	21.1	20.7	20.0	21.3			21.0

A-1-4 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/18	Temp. 22.6°C/78.8 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试结果(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A1-1	23.1			23.3	20.5	21.6	20.8	20.9	22.9			20.9
A1-2	29.1			24.4	23.2	22.0	21.8	22.7	23.4			21.6
A1-3	24.1			22.1	21.2	21.4	21.2	21.0	23.5			23.0
A1-4	20.5			22.3	21.0	20.8	20.8	21.0	21.5			24.6
A1-5	22.5			22.4	20.8	20.9	20.9	20.7	22.4			21.0
A1-6	22.1			22.2	22.8	21.3	20.7	23.2	23.1			20.2
A1-7	21.1			22.3	21.7	22.1	22.2	23.1	20.7			22.3
A1-8	22.6			22.5	21.3	21.7	21.8	22.3	22.8			19.6
A1-9	23.2			23.0	20.5	21.0	21.1	23.1	20.9			20.7
A1-10	21.7			21.2	22.6	22.3	20.0	22.1	21.7			20.8
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A1-1	20.3			21.0	20.8	21.3	20.2	22.0	22.7			20.1
A1-2	23.1			22.6	21.4	21.8	20.4	24.8	21.8			19.5
A1-3	19.0			19.3	19.9	20.1	18.8	20.0	20.6			18.9
A1-4	21.9			20.3	25.2	24.2	24.3	23.4	23.0			28.8
A1-5	20.5			20.8	20.3	20.3	19.4	19.6	22.5			9.5
A1-6	20.4			20.9	20.3	20.5	20.1	19.9	20.9			20.9
A1-7	20.5			20.7	20.8	21.1	21.3	18.2	19.3			18.9
A1-8	20.6			19.5	23.8	21.6	20.5	19.3	20.4			19.3
A1-9	21.5			20.7	20.5	22.3	21.7	19.5	23.3			18.8
A1-10	21.6			21.1	21.5	20.7	21.5	21.5	21.5			20.5

A-1-6 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/18	Temp.22.6 °C/78.8 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试数据表 (mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A1-1	20.7			22.3	21.9	21.9	20.4	21.7	22.2			21.0
A1-2	26.1			23.6	22.5	22.1	22.1	23.3	22.7			22.8
A1-3	23.1			22.8	22.1	20.7	20.5	20.1	21.0			20.5
A1-4	20.0			21.1	20.8	19.7	20.0	19.8	21.5			20.3
A1-5	22.7			20.3	20.7	21.5	20.9	20.2	21.8			22.9
A1-6	21.6			21.9	22.0	21.7	20.4	20.7	21.8			21.7
A1-7	21.1			21.5	21.6	21.3	21.1	20.0	20.6			21.3
A1-8	21.6			22.5	22.3	22.4	21.7	22.8	21.5			21.5
A1-9	21.6			23.1	22.2	21.8	20.9	21.7	22.6			21.4
A1-10	23.3			20.8	20.0	21.0	19.2	20.1	21.2			19.9
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A1-1	20.0			21.6	20.5	20.5	19.5	20.5	19.5			20.8
A1-2	20.1			21.5	20.8	20.9	21.2	26.0	21.4			22.2
A1-3	21.1			21.3	20.9	20.3	19.4	20.6	20.7			21.4
A1-4	25.1			23.1	22.9	24.1	23.7	22.5	24.9			21.8
A1-5	21.7			22.0	21.4	19.9	20.5	19.6	22.9			21.3
A1-6	23.3			22.7	20.7	22.1	19.7	19.4	20.9			19.7
A1-7	21.3			21.5	20.6	20.5	26.7	20.7	23.5			21.7
A1-8	21.7			20.8	21.0	20.7	19.9	20.6	22.2			21.2
A1-9	20.0			20.4	20.5	19.3	18.8	19.4	20.5			19.0
A1-10	21.0			21.7	23.2	21.2	21.1	21.3	24.7			22.9



A-2-1 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/01	Temp. 22.2°C/75.8%RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

测试记录(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A2-1	22.1			23.9	21.8	21.4	21.1	21.6	22.3			22.3
A2-2	28.5			28.8	27.9	21.8	22.6	22.4	22.5			21.4
A2-3	28.2			23.1	21.2	20.8	20.1	20.8	25.9			21.6
A2-4	19.8			20.0	20.0	19.2	18.4	18.9	20.5			18.9
A2-5	22.9			22.2	19.7	20.2	20.1	18.8	20.9			20.7
A2-6	20.1			19.7	18.7	18.5	18.9	19.0	20.1			18.3
A2-7	19.2			19.8	18.9	19.0	19.1	18.9	20.1			19.7
A2-8	21.4			23.4	20.1	20.2	19.4	19.3	20.0			19.0
A2-9	19.5			21.2	19.2	19.2	18.4	19.1	20.9			19.9
A2-10	19.6			22.5	19.1	19.2	19.8	18.5	20.4			19.2
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
B2-1	20.1			22.5	20.3	21.0	19.8	19.7	25.9			21.9
B2-2	20.8			21.9	19.5	19.8	18.8	19.1	20.3			18.2
B2-3	19.5			20.4	20.6	21.1	19.5	23.9	21.4			19.6
B2-4	19.5			22.0	21.1	20.1	19.9	20.2	22.4			21.3
B2-5	20.1			21.3	19.8	19.8	19.2	19.3	20.7			19.8
B2-6	18.8			20.6	20.1	19.8	18.3	18.1	20.1			19.2
B2-7	23.4			22.1	21.9	21.0	20.3	21.4	22.1			23.1
B2-8	23.5			25.6	21.4	25.7	22.1	24.1	30.8			30.1
B2-9	19.9			23.9	21.4	19.6	19.1	20.0	21.8			20.2
B2-10	22.3			23.4	21.1	22.5	21.5	22.3	23.1			22.2



REPORT HISTORY

Report Number	Revision	Description	Issue Date
24B01N000775-001-COM	V1	First release	2024-04-12

A-2-4 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/15	Temp. 22.0 °C/76.0 %RH	Ge Xinglin	Pass
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试数据表(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A2-1	21.8			22.0	22.2	21.5	21.0	21.0	22.5			21.7
A2-2	20.8			26.2	23.7	22.8	24.1	23.4	25.1			25.4
A2-3	20.2			21.4	20.8	20.8	19.4	19.7	22.0			19.2
A2-4	20.1			20.3	20.5	19.6	18.9	21.5	21.3			21.3
A2-5	19.5			20.3	20.2	19.7	19.5	19.0	21.1			19.2
A2-6	19.6			19.3	19.2	19.7	19.6	20.7	20.0			21.6
A2-7	18.7			22.1	21.1	21.8	21.0	19.0	20.8			21.9
A2-8	19.6			21.6	20.7	20.5	21.4	21.0	21.2			29.0
A2-9	31.1			20.2	19.2	19.0	18.5	18.9	20.8			18.7
A2-10	19.8			20.0	19.5	19.0	19.3	18.7	20.3			18.5
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A2-1	19.2			20.8	19.9	20.1	19.4	19.3	21.2			18.5
A2-2	19.9			20.9	20.0	19.9	19.2	19.0	20.1			19.1
A2-3	19.0			20.4	20.6	19.8	19.2	20.6	21.0			20.2
A2-4	20.1			23.0	21.7	21.6	20.2	20.6	22.3			20.6
A2-5	22.2			22.9	22.0	22.4	21.6	22.3	23.0			22.0
A2-6	19.9			20.1	20.2	19.9	19.0	19.4	20.4			19.4
A2-7	22.1			21.5	21.8	20.9	21.2	19.9	21.0			22.3
A2-8	20.0			29.6	22.9	21.9	22.2	20.3	27.9			27.8
A2-9	19.4			19.8	20.1	20.1	19.0	18.6	19.0			20.9
A2-10	21.7			22.7	22.9	21.5	22.4	23.1	23.2			21.2

A-2-6 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/21	Temp.23.0 °C/72.1 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试点电阻(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A2-1	21.8			25.3	22.3	22.4	21.3	21.8	22.9			21.8
A2-2	22.9			24.0	21.7	21.4	22.2	21.3	22.1			23.6
A2-3	20.4			24.9	20.2	21.7	19.6	19.5	19.7			19.1
A2-4	20.0			21.0	20.3	19.4	18.7	19.2	21.4			19.1
A2-5	20.7			21.2	20.9	21.1	20.9	20.5	21.6			19.5
A2-6	19.6			20.1	20.8	19.6	19.4	21.1	20.6			20.1
A2-7	18.8			19.8	19.1	19.3	19.0	18.9	20.1			19.2
A2-8	20.0			19.7	20.4	21.1	20.3	19.3	20.6			19.5
A2-9	19.6			22.8	19.0	19.4	19.6	20.8	18.8			19.5
A2-10	19.0			19.8	19.6	19.0	18.7	18.8	19.1			19.9
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A2-1	19.2			27.3	21.6	19.7	20.5	19.7	21.7			20.3
A2-2	19.8			23.9	19.8	19.9	19.2	19.4	21.1			19.5
A2-3	19.5			22.7	23.0	24.7	20.3	19.6	31.2			19.0
A2-4	19.3			20.9	21.4	20.7	19.8	19.5	21.4			19.6
A2-5	19.6			20.1	20.5	20.6	21.1	20.5	21.5			20.1
A2-6	22.2			22.5	22.2	20.9	20.3	27.8	26.5			19.8
A2-7	21.7			21.8	22.8	21.9	20.3	22.7	24.5			21.5
A2-8	19.5			22.9	20.9	20.5	21.1	28.9	23.4			19.7
A2-9	20.2			20.0	20.6	21.1	19.2	20.2	21.0			18.8
A2-10	21.5			22.4	21.3	22.5	22.4	22.2	22.4			21.6

A-2-8 Low level contact resistance

Testing Period	Measure environment	Test Engineer	Test Result
2022/07/21	Temp.23.0 °C/72.1 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试记录(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A2-1	21.7			23.6	21.4	21.1	20.9	20.8	21.9			22.4
A2-2	27.9			27.6	26.6	22.2	21.5	21.9	22.5			20.9
A2-3	23.3			22.8	21.3	20.7	20.3	20.1	24.7			21.3
A2-4	19.6			20.4	20.5	19.6	18.7	19.3	20.3			19.7
A2-5	21.9			21.9	19.6	20.2	19.3	19.6	21.2			20.3
A2-6	20.5			19.8	18.5	18.7	18.7	16.9	20.4			19.4
A2-7	20.1			20.2	19.3	19.2	19.3	18.5	19.8			20.3
A2-8	20.6			22.8	19.8	20.5	18.7	19.7	19.9			19.5
A2-9	19.8			21.4	20.3	19.4	18.8	19.3	20.3			19.4
A2-10	19.7			20.4	19.5	19.5	20.2	18.5	20.7			19.7
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A2-1	19.9			22.4	20.1	20.8	19.5	19.3	23.8			21.3
A2-2	20.6			21.2	19.6	20.3	18.5	19.8	20.7			19.5
A2-3	20.3			20.5	20.3	21.5	19.8	22.8	21.3			19.7
A2-4	19.6			21.7	20.9	20.7	20.3	20.4	22.6			20.8
A2-5	21.7			20.6	19.9	19.4	19.5	19.7	20.8			19.5
A2-6	18.9			19.5	19.9	19.7	18.7	18.8	20.4			20.3
A2-7	22.6			21.3	22.0	20.6	20.2	20.7	21.7			22.5
A2-8	23.4			24.8	21.2	24.8	21.7	23.8	29.3			28.7
A2-9	20.3			23.6	20.9	19.7	19.6	20.2	21.2			20.7
A2-10	21.7			22.8	22.8	21.9	20.9	21.6	22.5			21.6

A-3-1 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11	Temp.22.2 °C/75.8 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

测试结果mΩ												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A2-1	23.7			23.6	22.5	21.7	21.0	21.2	22.7			21.5
A2-2	21.8			22.9	21.5	22.1	22.8	22.7	24.5			20.8
A2-3	21.6			22.3	21.9	22.7	20.9	21.5	22.8			20.4
A2-4	18.7			19.9	20.1	19.3	18.6	19.8	20.9			19.4
A2-5	19.5			20.7	21.3	20.8	20.6	20.9	21.5			19.1
A2-6	19.8			21.1	21.0	21.0	20.1	20.9	22.3			19.8
A2-7	20.5			21.0	20.9	21.2	20.1	20.8	21.4			18.7
A2-8	20.3			21.7	20.8	22.3	20.6	20.4	21.7			19.0
A2-9	20.2			22.2	21.3	21.6	22.8	21.6	22.0			20.5
A2-10	19.8			20.9	20.2	20.0	20.0	19.9	21.1			19.5
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A3-1	18.6			24.3	20.5	19.9	18.7	19.7	20.9			19.5
A2-2	20.0			28.4	22.6	23.3	21.9	21.8	24.6			22.3
A2-3	21.8			23.6	22.1	23.1	24.2	23.4	26.2			20.5
A2-4	20.2			20.7	21.4	19.0	18.5	19.8	21.9			22.8
A2-5	20.7			21.7	20.5	20.7	20.3	20.8	21.8			19.7
A2-6	21.1			22.2	21.5	21.5	21.3	21.4	22.4			20.0
A2-7	20.1			21.5	21.4	21.3	19.5	20.5	21.7			19.6
A2-8	19.7			20.9	20.8	20.3	20.4	21.2	21.5			19.2
A2-9	21.1			22.6	21.5	21.0	22.2	21.7	22.4			21.2
A2-10	20.1			21.0	20.5	20.2	19.8	19.9	21.0			19.7

A-3-4 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/18	Temp.22.9 °C/78.8 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

样品编号	测试结果(mΩ)											
	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A3-1	20.8			22.1	22.0	21.2	20.9	21.1	22.9			20.9
A3-2	20.4			22.7	21.6	22.3	21.2	22.1	22.7			19.8
A3-3	22.6			22.5	21.5	22.5	21.7	21.2	22.7			20.3
A3-4	20.5			21.4	21.7	22.3	20.9	20.8	22.3			19.8
A3-5	20.9			21.6	21.5	22.0	21.0	21.3	22.3			19.5
A3-6	20.8			21.8	21.3	21.2	20.1	21.0	21.6			19.6
A3-7	20.1			21.7	21.4	21.6	20.6	21.5	22.5			19.2
A3-8	19.2			22.1	22.0	20.5	20.6	21.3	22.0			21.0
A3-9	20.3			22.3	22.0	21.8	20.7	21.6	22.6			20.5
A3-10	20.2			21.5	20.8	20.9	20.7	20.7	21.9			19.8
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A3-1	21.4			21.4	21.9	22.1	20.7	21.5	22.3			19.9
A3-2	22.0			23.1	22.4	22.1	21.7	21.9	22.4			19.9
A3-3	21.5			22.3	22.3	22.6	21.6	21.9	23.1			19.4
A3-4	21.6			22.0	21.2	20.8	22.1	21.3	22.4			20.7
A3-5	21.1			21.7	21.8	22.9	20.4	20.9	22.4			20.5
A3-6	22.2			22.8	22.6	21.7	21.5	21.9	22.8			20.4
A3-7	20.8			22.0	22.4	21.8	21.4	22.9	23.2			20.4
A3-8	20.5			20.1	21.7	20.7	20.4	21.7	21.8			20.0
A3-9	20.7			22.1	21.9	22.2	21.8	21.7	22.1			19.6
A3-10	20.7			21.6	21.2	21.1	19.8	20.1	21.6			20.2



A-3-6 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp.23.3 °C/74.6 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

样品编号	接触电阻(mΩ)											
	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A3-1	20.8			22.1	21.5	21.3	21.1	20.9	22.6			20.6
A3-2	21.1			22.2	22.3	22.1	20.6	21.8	22.8			19.9
A3-3	23.1			22.1	22.9	22.0	21.4	21.8	22.2			19.8
A3-4	20.1			21.0	21.4	21.9	20.7	20.9	22.5			19.1
A3-5	21.2			21.8	22.3	22.2	21.0	21.5	22.1			19.9
A3-6	21.5			21.7	21.1	21.2	20.4	21.0	21.9			19.8
A3-7	20.7			21.9	21.6	22.1	21.6	21.7	22.0			19.0
A3-8	20.6			22.3	21.6	21.8	20.7	21.0	22.0			19.6
A3-9	21.4			22.2	21.7	21.8	20.1	21.4	22.6			20.2
A3-10	20.2			21.8	20.9	20.4	20.5	20.8	22.3			20.0
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A3-1	20.5			22.2	22.1	22.0	21.0	21.7	22.3			20.2
A3-2	20.9			22.6	22.7	21.6	20.8	21.6	22.5			20.7
A3-3	21.1			22.7	22.3	23.0	22.5	22.1	24.3			20.5
A3-4	21.8			22.7	21.9	21.3	21.7	21.0	22.5			19.6
A3-5	21.7			22.5	21.5	21.8	20.5	20.9	22.4			20.7
A3-6	22.0			22.6	22.3	21.6	21.1	21.9	22.8			20.1
A3-7	21.2			22.2	22.4	22.1	20.0	21.4	22.8			20.3
A3-8	20.5			21.5	21.7	20.8	20.6	21.5	21.8			19.6
A3-9	20.8			22.2	21.9	21.9	20.9	21.5	22.3			19.4
A3-10	20.5			21.2	21.9	21.0	19.8	20.8	21.2			19.6



A-4-1 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/08	Temp. 21.2 °C / 68.9%RH	Zhan Xingcheng	Pass
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

样品编号	电阻值(mΩ)											
	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A4-1	19.1			19.7	18.9	19.2	18.5	18.8	19.8			19.4
A4-2	21.6			22.3	20.8	21.2	21.1	21.9	21.6			21.2
A4-3	21.2			21.9	20.1	19.4	19.1	18.7	20.5			19.4
A4-4	20.5			20.8	21.7	21.9	21.6	21.5	22.4			19.6
A4-5	18.5			20.3	19.7	19.4	18.5	19.1	20.1			19.5
A4-6	18.9			20.3	19.5	20.1	18.6	19.2	20.5			18.8
A4-7	21.7			22.6	21.0	21.1	21.2	20.3	22.1			20.1
A4-8	21.8			20.8	20.5	19.5	19.9	19.3	20.4			18.6
A4-9	22.7			24.4	21.0	21.3	21.6	21.8	22.9			20.4
A4-10	26.4			22.3	20.3	19.8	20.1	19.1	20.6			18.8
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A4-1	21.3			22.1	22.0	21.4	20.7	21.0	22.5			21.4
A4-2	19.8			21.1	19.9	19.4	19.1	20.1	20.7			18.9
A4-3	22.5			22.2	22.1	21.4	20.9	21.2	22.4			20.5
A4-4	18.9			22.6	20.3	19.8	18.0	19.9	20.7			19.8
A4-5	21.5			22.3	22.1	21.3	21.1	20.4	23.0			19.5
A4-6	20.6			24.0	21.6	20.9	21.0	21.3	22.0			20.3
A4-7	20.2			20.7	20.3	20.8	20.7	20.4	21.7			21.9
A4-8	20.8			22.4	21.6	23.3	20.6	20.9	22.3			25.0
A4-9	20.3			19.8	20.0	20.1	18.1	18.9	20.6			17.9
A4-10	23.1			22.4	20.2	20.3	19.9	20.8	21.7			19.4

24.2018(m0)												
Station	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A10-11	19.6			19.4	19.6	19.7	18.5	20.1	20.1			18.8
A10-12	20.5			20.3	20.4	20.1	20.6	21.1	21.4			21.4
A10-13	20.8			21.4	21.1	20.6	20.0	18.9	18.8			18.1
A10-14	22.0			20.5	21.2	20.7	19.6	20.9	22.5			20.3
A10-15	20.2			22.6	19.5	19.0	19.2	21.3	22.1			18.6
A10-16	21.5			21.7	20.6	20.2	19.6	21.5	23.1			19.6
A10-17	20.7			23.8	22.7	20.1	16.8	20.8	22.5			18.9
A10-18	22.8			23.6	21.8	21.6	19.5	21.7	21.7			20.6
A10-19	20.0			20.1	20.3	20.8	20.5	22.7	20.8			21.7
A10-20	21.5			22.7	24.1	21.5	19.8	21.1	21.6			20.4
Station	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A10-1	22.0			22.6	20.9	20.8	22.3	22.2	22.7			21.7
A10-2	20.5			21.3	19.6	17.2	19.1	19.5	20.5			18.4
A10-3	21.5			22.3	22.4	22.5	20.4	22.2	22.9			21.2
A10-4	20.5			22.1	20.5	20.3	20.3	24.9	24.1			19.5
A10-5	21.6			24.6	20.6	21.3	21.8	28.6	28.6			20.6
A10-6	22.3			23.7	21.8	21.8	22.6	19.7	22.1			20.6
A10-7	21.8			22.8	22.4	22.3	19.7	21.0	21.9			19.5
A10-8	23.4			24.3	23.7	22.5	23.3	20.6	20.6			18.4
A10-9	24.1			25.7	22.6	22.7	22.8	21.8	24.8			19.4
A10-10	22.3			22.7	21.7	20.6	21.6	22.5	21.7			20.7

A-4-4 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/13	Temp.21.2 °C/67.1 %RH	Zhan Xingcheng	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试数据表(mΩ)												
三品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A41	21.7			20.1	20.6	19.5	19.0	18.8	20.7			20.2
A42	23.7			22.8	22.3	22.5	21.3	21.3	22.6			22.4
A43	20.6			21.3	20.7	19.7	21.1	19.9	20.9			19.7
A44	21.1			21.1	21.8	21.2	21.4	21.4	21.8			20.8
A45	20.5			20.4	20.6	19.9	18.9	21.1	20.4			19.6
A46	18.7			20.3	19.9	20.1	19.9	19.9	21.1			19.9
A47	22.4			21.7	22.6	21.1	21.2	19.6	23.7			21.1
A48	24.1			20.1	21.1	19.9	19.4	21.4	21.4			19.1
A49	23.8			24.1	23.4	21.1	21.6	21.4	23.3			21.1
A410	21.1			21.1	21.1	19.9	20.4	19.9	21.1			18.9
三品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A41	21.2			21.2	21.5	20.4	21.2	21.7	20.7			21.2
A42	20.4			21.2	21.5	20.4	20.2	20.5	21.0			20.4
A43	21.9			22.6	22.7	22.4	21.4	21.3	23.1			21.4
A44	24.1			23.1	21.9	21.1	20.7	21.4	21.7			21.1
A45	21.7			21.1	21.6	21.3	21.2	21.2	23.6			23.2
A46	23.5			24.1	23.7	21.9	22.4	22.9	23.4			21.2
A47	20.7			21.2	21.2	20.1	21.4	21.4	21.1			23.4
A48	22.9			23.4	24.2	23.5	21.1	21.4	24.1			21.2
A49	21.1			19.9	23.1	20.4	18.4	19.9	21.4			16.1
A410	20.4			23.1	21.1	21.1	19.9	21.1	24.1			19.9

測試結果(m/s)												
樣品編號	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A411	21.3			17.8	21.3	20.4	19.8	20.9	20.9			19.9
A412	22.5			21.3	24.5	21.7	19.0	20.5	20.6			21.7
A413	22.7			22.7	22.4	22.9	20.9	19.9	21.7			22.4
A414	22.2			24.5	22.3	22.7	21.4	21.7	22.9			22.6
A415	22.6			23.7	21.8	20.8	21.7	22.9	19.8			21.9
A416	21.7			22.8	20.9	21.7	22.8	22.4	20.3			19.8
A417	20.8			21.7	22.7	21.4	19.9	21.7	22.4			17.9
A418	21.4			20.9	24.8	21.0	20.6	22.9	24.5			19.6
A419	22.4			22.7	22.8	22.4	20.7	20.9	25.0			21.6
A420	22.7			22.4	23.2	23.8	19.7	21.5	22.7			22.7
樣品編號	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A411	25.4			26.0	21.9	22.7	23.2	24.1	22.8			22.9
A412	26.2			25.6	19.8	21.2	22.9	20.7	22.9			23.8
A413	24.8			26.5	19.0	22.4	22.1	21.8	21.8			22.4
A414	22.7			22.7	20.0	22.6	21.4	22.7	23.4			22.7
A415	21.9			21.8	21.5	20.9	21.7	24.5	24.0			22.6
A416	22.6			22.4	21.7	22.5	21.6	22.9	25.9			19.8
A417	21.7			21.7	22.0	21.6	20.8	22.0	22.6			19.8
A418	22.9			22.9	22.1	22.7	20.9	22.4	23.7			20.9
A419	22.1			23.5	22.9	21.3	21.9	21.8	25.4			20.3
A420	21.6			22.9	22.0	22.8	22.7	25.7	25.1			22.6



CONTENTS

1. Test Laboratory	5
1.1. Testing Location	5
1.2. Testing Environment.....	5
1.3. Project Data.....	5
1.4. Signature	5
2. Client Information.....	5
2.1. Applicant Information	5
2.2. Manufacturer Information.....	5
3. Unit Under Test (UUT) Information	6
3.1. About UUT	6
3.2. Sample Coding	6
4. Reference Documents	7
5. USB Type-C Compliance Requirements	7
5.1. DC Electrical.....	7
5.2. Mechanical	8
5.3. Environmental.....	9
6. Test Procedure	10
7. Test Result Summary	13
8. Test Detail	14
8.1. Clause 3.2.1 (6) Construction	14
8.2. Clause 3.2.1 (8) Critical Dimensions	16
8.3. Clause 3.7.8.1 Low level contact resistance	17
8.4. Clause 3.7.8.2 Dielectric withstanding voltage.....	39
8.5. Clause 3.7.8.3 Insulation Resistance.....	40
8.6. Clause 3.7.8.4 Contact Current Rating	41
8.7. Clause 3.8.1.1 Insertion force	42
8.8. Clause 3.8.1.1 Extraction force.....	42
8.9. Clause 3.8.1.3 Durability	44
8.10. Clause 3.8.1.3 Reseating	45
8.11. Clause 3.8.1.6 4-Axis Continuity	46

A-4-6 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/21	Temp. 23.0 °C/ 73.2 %RH	Zhan Xingcheng	Pass
Test condition	Metered: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试结果(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A4-1	18.6			20.0	19.9	19.6	18.9	17.6	20.8			19.2
A4-2	18.6			20.4	20.1	19.8	19.8	19.6	21.0			19.2
A4-3	21.1			22.4	21.3	21.0	21.3	23.3	20.2			21.1
A4-4	17.8			22.7	22.0	19.2	22.4	24.5	20.6			20.3
A4-5	19.9			21.4	22.4	19.6	21.6	19.6	19.9			21.4
A4-6	16.7			22.9	21.7	20.0	21.0	19.5	21.4			22.7
A4-7	18.9			20.8	22.6	21.7	22.0	22.4	22.0			23.6
A4-8	20.1			19.8	23.5	22.4	21.7	21.7	23.1			22.7
A4-9	20.1			19.8	22.0	22.0	19.8	22.4	22.9			25.4
A4-10	19.9			21.7	21.7	21.6	18.4	22.0	21.6			21.6
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A4-1	21.1			21.9	22.5	22.3	21.1	21.1	21.7			22.2
A4-2	20.6			21.9	22.0	21.5	22.4	22.8	22.2			21.0
A4-3	19.6			19.9	21.7	20.3	19.2	19.3	21.4			20.2
A4-4	19.6			21.4	19.8	21.5	23.4	20.3	21.6			22.9
A4-5	18.7			22.4	19.9	20.7	22.6	21.6	21.7			21.9
A4-6	18.0			21.7	21.5	20.9	19.8	23.4	22.4			22.1
A4-7	19.1			23.6	22.6	22.6	17.4	22.5	23.4			25.6
A4-8	20.4			22.7	21.7	22.0	18.6	23.4	22.9			24.8
A4-9	20.5			22.4	21.5	22.6	20.9	23.2	22.8			24.0
A4-10	21.6			23.0	21.2	23.0	20.6	23.0	21.7			21.9

測試結果(m/s)												
樣品編號	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A4-11	18.7			21.1	19.8	19.9	18.7	19.9	20.1			19.9
A4-12	18.7			22.8	21.1	19.6	19.4	19.7	22.4			19.1
A4-13	21.4			22.4	21.4	21.4	22.4	23.4	20.2			21.1
A4-14	18.4			23.8	23.8	19.8	23.4	23.4	21.4			21.4
A4-15	19.1			22.8	21.1	19.7	23.1	19.9	19.9			22.4
A4-16	16.8			21.4	22.4	21.4	22.4	19.1	21.4			22.8
A4-17	19.9			21.9	21.1	21.8	22.4	22.2	23.4			21.2
A4-18	21.2			19.9	23.6	22.8	21.7	21.4	23.9			21.2
A4-19	21.4			19.9	21.1	21.4	19.9	22.8	23.4			21.1
A4-20	19.8			22.4	22.8	22.8	19.1	22.8	23.1			22.8
樣品編號	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A4-11	22.4			22.4	22.5	22.8	21.1	22.4	21.8			22.4
A4-12	21.8			22.8	21.9	22.6	22.8	22.8	22.8			21.4
A4-13	19.9			19.7	22.8	21.8	19.9	19.9	21.4			21.1
A4-14	19.6			21.4	19.9	21.4	23.4	20.3	22.4			22.8
A4-15	18.9			22.8	19.8	21.8	22.8	21.6	22.8			22.8
A4-16	19.9			24.1	21.7	21.4	19.1	23.4	21.4			21.1
A4-17	19.9			24.7	23.6	24.1	17.7	24.1	23.1			21.1
A4-18	21.2			22.2	22.8	23.8	18.7	23.1	22.4			21.9
A4-19	21.4			23.4	21.6	23.4	21.1	23.8	24.2			21.1
A4-20	22.8			23.9	22.8	24.8	23.8	24.1	22.9			22.9

A-4-8 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/22	Temp. 22.6 °C / 71.2 %RH	Zhan Xingcheng	Pass
Test condition	Metered: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

测试结果(mΩ):												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A4-1	19.8			18.3	19.2	19.8	18.4	20.2	20.3			18.9
A4-2	19.9			20.5	23.1	20.4	21.2	22.1	21.8			19.9
A4-3	21.2			21.4	20.4	19.8	19.3	19.2	20.2			19.8
A4-4	22.4			22.2	21.6	20.9	21.2	22.1	20.8			19.7
A4-5	20.8			21.0	19.5	18.5	19.5	19.7	20.3			18.7
A4-6	18.8			21.2	18.7	20.2	18.7	19.3	20.4			18.6
A4-7	20.2			22.2	22.0	22.4	20.8	21.2	21.1			20.3
A4-8	21.3			20.6	21.4	18.8	19.8	19.7	20.4			19.2
A4-9	24.0			23.0	20.8	20.6	21.8	22.6	22.0			19.9
A4-10	23.8			21.4	20.5	18.7	21.1	19.8	20.2			18.7
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A4-1	23.8			22.4	22.0	21.2	22.4	24.3	21.8			23.5
A4-2	21.0			22.2	18.9	18.8	19.4	19.6	20.8			18.8
A4-3	24.8			22.3	21.5	21.3	20.3	20.8	21.2			20.3
A4-4	19.8			21.8	20.2	19.4	19.0	19.8	20.1			19.9
A4-5	20.2			21.4	19.8	21.2	21.3	20.4	23.0			19.6
A4-6	23.4			22.4	20.4	20.1	21.4	21.3	21.4			20.1
A4-7	19.8			20.8	21.5	22.2	21.2	20.8	22.1			21.0
A4-8	20.1			21.5	24.0	24.4	21.2	20.9	21.3			24.1
A4-9	22.0			18.9	19.8	19.9	19.2	18.6	19.2			18.2
A4-10	24.2			21.2	20.5	20.0	19.8	20.2	22.0			19.9

测试结果(mg)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A4-1	18.7			22.0	19.7	18.8	18.6	19.2	20.0			18.8
A4-2	19.2			21.3	20.8	19.9	19.8	19.6	20.8			19.2
A4-B	20.8			24.0	21.4	20.8	21.2	21.4	20.8			20.1
A4-W	22.4			23.2	24.0	19.6	21.0	24.3	25.0			21.5
A4-E	21.3			22.0	24.3	19.8	22.4	20.0	20.1			21.8
A4-B	19.2			21.3	22.0	21.0	21.2	20.1	21.2			21.4
A4-I	20.3			22.1	24.3	21.2	21.4	21.2	21.8			21.6
A4-B	21.4			18.9	24.2	21.4	21.8	21.2	20.8			21.8
A4-F	23.2			19.2	23.8	21.8	20.1	23.0	23.2			20.8
A4-Z	24.0			20.0	20.9	22.0	19.2	20.8	25.1			21.7
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A4-1	23.8			22.3	21.4	22.4	23.1	23.0	22.9			23.0
A4-2	21.2			22.6	24.0	22.1	21.8	22.4	21.6			22.1
A4-B	24.3			19.8	22.9	22.0	19.8	19.7	20.9			21.0
A4-W	14.9			21.0	20.0	21.4	21.4	20.4	21.0			22.5
A4-E	23.0			20.8	20.1	21.6	22.4	21.8	20.9			22.6
A4-B	18.8			20.4	21.0	21.0	19.3	21.2	22.4			23.1
A4-I	19.2			24.6	22.7	23.0	18.2	21.3	24.0			25.3
A4-B	21.0			23.0	22.8	23.4	19.8	23.0	21.2			25.0
A4-F	20.8			23.2	21.6	24.0	21.4	21.4	23.0			24.1
A4-Z	22.0			23.3	22.1	24.6	21.4	23.6	23.0			23.2



A-4-10 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/22	Temp. 22.6 °C/ 71.2%RH	Zhan Xingcheng	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤50 mΩ		

样品编号	测试数据(mΩ)											
	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A#1	19.9			19.9	19.9	19.9	19.9	24.1	20.4			19.9
A#2	19.1			21.4	21.1	21.4	24.1	21.1	21.9			19.1
A#3	21.4			21.8	21.8	19.9	19.9	19.1	21.1			19.1
A#4	22.4			21.4	22.8	21.4	24.1	24.1	23.4			19.2
A#5	21.8			23.2	19.9	19.9	19.9	19.1	21.4			19.5
A#6	19.1			24.1	18.7	21.4	17.7	19.9	21.1			18.7
A#7	21.4			23.1	21.4	21.8	18.4	23.4	24.9			20.4
A#8	21.8			21.4	23.8	19.9	19.9	19.9	21.8			19.9
A#9	24.7			23.1	21.4	21.4	21.1	20.6	24.1			19.9
A#10	24.8			24.7	24.2	19.9	24.1	19.8	21.8			18.9
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A#1	21.1			22.5	21.4	21.4	22.8	24.3	21.8			23.3
A#2	21.4			21.1	19.9	19.9	19.9	19.9	21.4			19.1
A#3	25.1			22.5	22.8	21.5	16.9	21.4	21.4			21.4
A#4	19.9			22.8	21.4	19.9	19.9	19.9	20.4			19.9
A#5	21.4			22.5	19.9	21.4	22.4	21.8	23.8			19.1
A#6	21.4			23.1	20.4	23.4	22.8	22.4	21.4			20.7
A#7	19.9			21.4	21.5	23.4	24.1	21.4	22.8			21.8
A#8	21.1			22.5	25.0	19.9	22.8	20.1	21.8			24.7
A#9	26.1			19.9	19.9	16.8	19.9	19.9	19.9			19.1
A#10	25.9			21.0	20.0	21.4	19.1	20.1	22.8			19.4

牌尺站米(米)												
牌尺编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A411	18.4			20.8	19.8	19.9	18.7	19.9	20.1			19.1
A412	19.9			21.4	20.8	19.8	19.6	19.1	20.1			20.1
A413	20.4			24.6	21.6	16.7	21.4	20.5	20.4			20.1
A414	22.8			23.8	20.4	19.9	21.8	20.1	21.4			20.1
A415	21.4			22.8	20.8	19.1	23.7	20.1	21.8			19.9
A416	19.9			21.8	22.8	21.4	21.4	21.4	21.1			16.9
A417	21.4			22.4	20.1	22.8	21.8	19.9	20.7			22.2
A418	23.4			18.7	21.1	22.1	20.1	21.1	20.1			23.4
A419	23.1			19.9	21.1	22.4	20.8	20.1	21.1			20.8
A420	25.1			21.1	21.4	20.1	19.9	25.7	25.7			21.1
牌尺编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A411	23.4			23.4	20.1	23.8	20.1	21.1	21.9			23.4
A412	21.8			22.8	21.1	22.8	21.1	22.5	21.9			23.1
A413	24.7			19.9	21.4	23.7	19.8	19.9	24.1			22.8
A414	19.8			21.1	23.8	22.7	21.4	21.1	20.7			22.4
A415	23.8			20.8	21.1	22.8	22.5	21.1	21.1			22.1
A416	19.1			20.1	22.4	24.1	19.9	21.4	22.5			20.1
A417	19.9			20.1	23.8	23.8	18.4	21.8	25.1			20.1
A418	21.8			23.8	20.1	23.4	19.9	21.4	20.1			20.6
A419	21.4			21.4	22.1	21.1	21.4	23.4	21.1			20.1
A420	22.8			23.4	20.7	20.1	22.8	20.1	24.4			23.3

A-7-2 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3°C / 74.6 %RH	Ge Xinglin	Pass
Test condition	Mated: Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

测试记录表(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A7-1	17.9			21.8		14.5	13.3	15.8	22.1			22.7
A7-2	17.8			21.4		17.5	16.6	17.3	22.2			20.2
A7-3	17.9			22.0		19.3	17.7	19.2	23.1			23.6
A7-4	24.1			24.4		22.1	18.3	24.4	24.8			22.6
A7-5	18.3			23.1		22.5	21.2	17.8	24.4			23.2
A7-6	19.6			24.0		21.2	26.1	25.7	22.1			19.0
A7-7	23.6			19.3		15.5	15.6	15.1	25.0			18.2
A7-8	19.8			24.6		18.4	19.6	18.7	21.5			19.1
A7-9	19.0			20.1		19.7	19.8	17.3	25.7			22.7
A7-10	22.9			20.9		18.5	17.0	17.8	23.5			20.9
样品编号	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
A7-1	20.6			21.3		16.6	13.3	14.1	21.1			17.9
A7-2	22.1			20.1		16.7	21.0	18.6	23.2			21.1
A7-3	21.3			21.4		18.8	20.7	18.2	23.2			21.4
A7-4	20.1			24.7		23.4	21.6	18.1	22.1			22.2
A7-5	22.5			20.0		17.3	17.4	18.8	25.7			21.7
A7-6	21.5			24.2		24.3	20.4	28.0	26.5			21.5
A7-7	21.1			19.4		16.5	16.7	15.2	25.0			19.7
A7-8	20.6			20.8		16.7	15.7	18.8	21.0			18.1
A7-9	21.8			24.3		18.9	23.9	18.0	25.6			21.5
A7-10	22.2			21.9		18.9	16.8	18.4	23.7			19.7



A-7-10 Low level contact resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2019/10/11	Temp.26.3 °C/66.6 %RH	Ge Xinglin	Pass
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.		
Criteria	≤40 mΩ (Initial)		

测试结果(mΩ)												
样品编号	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
A7-1	19.2			20.7		22.3	20.4	15.3	50.4			22.4
A7-2	22.3			25.4		27.5	21.4	27.3	29.5			21.5
A7-3	25.2			25.5		32.4	32.2	23.4	23.7			22.2
A7-4	27.7			52.1		30.7	18.4	22.4	17.3			22.4
A7-5	51.5			23.6		27.6	20.3	20.1	23.4			22.9
A7-6	25.9			29.4		28.3	10.4	32.3	26.4			24.3
A7-7	25.6			28.7		31.7	32.8	28.9	25.9			26.8
A7-8	29.6			22.5		32.6	32.7	20.8	22.6			21.0
A7-9	26.3			28.7		35.0	22.5	32.6	22.9			28.7
A7-10	22.6			22.2		24.7	30.6	15.6	23.2			25.6
样品编号	B1	B2	H1	H4	A1	H6	R7	38	B9	B10	D11	D12
A7-1	10.2			26.1		29.4	27.3	21.2	25.4			27.4
A7-2	21.4			20.3		23.4	22.6	20.8	26.9			25.4
A7-3	22.7			20.8		25.9	22.5	21.2	28.1			25.6
A7-4	27.9			21.4		23.4	18.9	18.9	25.4			24.2
A7-5	25.3			20.4		26.1	15.3	20.7	20.4			26.4
A7-6	26.4			22.5		41.2	32.3	23.6	31.5			25.4
A7-8	32.2			25.7		21.6	28.9	27.9	22.6			20.8
A7-8	27.8			21.2		22.6	32.3	32.4	27.7			20.5
A7-9	26.6			21.8		20.7	23.2	23.3	26.3			21.2
A7-10	24.6			20.6		26.7	21.8	25.4	22.8			22.8

8.4. Clause 3.7.8.2 Dielectric withstanding voltage

A-7-1 Dielectric withstanding voltage			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 26.7 °C/ 75.6 %RH	Ge Xinglin	Pass
Test condition	Mated: 100 VAC (RMS), 1 min. The test voltage shall be applied between adjacent contacts.		
Criteria	A failure is the occurrence of adisruptive discharge as evidenced by flashover (surface discharge), sparkover (air discharge), breakdown (puncture discharge) or leakage in excess of 5 mA.		

A-7-11 Dielectric withstanding voltage			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/25	Temp. 29.1 °C/ 64.2 %RH	Ge Xinglin	Pass
Test condition	Mated: 100 VAC (RMS), 1 min. The test voltage shall be applied between adjacent contacts.		
Criteria	A failure is the occurrence of adisruptive discharge as evidenced by flashover (surface discharge), sparkover (air discharge), breakdown (puncture discharge) or leakage in excess of 5 mA.		

8.5. Clause 3.7.8.3 Insulation Resistance

A-7-12 Insulation Resistance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/25	Temp: 29.1 °C/ 84.2 %RH	Ge Xinglin	Pass
Test condition	Mated and Unmated, 500 Vdc, 2min. The test voltage shall be applied between adjacent contacts:		
Criteria	≥100MΩ		

A-7-12 Insulation Resistance (GΩ)					
Sample Coding	A7-1	A7-2	A7-3	A7-4	A7-5
Test contacts					
A6 to A7	99.9	99.9	99.9	99.9	99.9
A7 to A8	99.9	99.9	99.9	99.9	99.9
A8 to A9	99.9	99.9	99.9	99.9	99.9
B6 to B1	99.9	99.9	99.9	99.9	99.9
B7 to B8	99.9	99.9	99.9	99.9	99.9
Sample Coding	A7-6	A7-7	A7-8	A7-9	A7-10
Test contacts					
A6 to A7	99.9	99.9	99.9	99.9	99.9
A7 to A8	99.9	99.9	99.9	99.9	99.9
A8 to A9	99.9	99.9	99.9	99.9	99.9
B6 to B1	99.9	99.9	99.9	99.9	99.9
B7 to B8	99.9	99.9	99.9	99.9	99.9
Note: Followed by the specific resistance value.					



8.12. Clause 3.8.2 Temperature life	47
8.13. Clause 3.8.2 Thermal shock.....	47
8.14. Clause 3.8.2 Cyclic temperature and humidity.....	48
8.15. Clause 3.8.2 Vibration.....	48
8.16. Clause 3.8.2 Mixed flowing gas	49
8.17. Clause 3.8.2 Thermal disturbance	49
9. Test Equipments Utilized	50
ANNEX A: UUT photograph	52
ANNEX B: Drawing	53
ANNEX C: Insertion Force & Extraction Force Test Layout.....	54
ANNEX D: Durability Test Layout	55
ANNEX E: Dielectric withstanding voltage Test Layout.....	56
ANNEX F: Vibration Test Layout.....	57
ANNEX G: Contact Current Rating Test Layout.....	58

8.6. Clause 3.7.8.4 Contact Current Rating

B-6-1 Contact Current Rating			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/13	Temp. 23.8°C / 67.7 %RH	Zhan Xingcheng	Pass
Test condition	1. 5A applied collectively to VBUS pins (i.e., pins A4, A9, B4, and B9) . 2. 1.25A applied to the Vconn pin (i.e., B5) ,terminated. 3. 0.25 A applied individually to all the other contacts.		
Criteria	The temperature rise shall not exceed 30°C at the outside surface of the shell.		

Test data:			
B-6-1 Contact Current Rating			
Sample Coding	Ambient temperature (°C)	Thermocouple temperature (°C)	Temperature rise (°C)
B6-1	23.8	48.7	24.9
B6-2	23.8	49.1	25.3
B6-3	23.8	48.1	24.3

Note: Temperature rise of sample = Thermocouple temperature - Ambient temperature:

8.7. Clause 3.8.1.1 Insertion force

A-7-4 Insertion Force			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3 °C / 74.6 %RH	Ge Xinglin	Pass
Test condition	Speed: 12.5mm/min; Insertion depth: 4.8mm.		
Criteria	Insertion force: 5N~20N		

Test data:					
A-7-4 Insertion Force					
Sample Coding	A7-1	A7-2	A7-3	A7-4	A7-5
Insertion force (N)	10.1	10.5	12.0	10.1	10.2
Sample Coding	A7-6	A7-7	A7-8	A7-9	A7-10
Insertion force (N)	7.7	10.6	11.8	9.8	11.5

8.8. Clause 3.8.1.1 Extraction force

A-7-5 Extraction Force			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3 °C / 74.6 %RH	Ge Xinglin	Pass
Test condition	Speed: 12.5mm/min; Extraction depth: 4.8mm.		
Criteria	Extraction force: 8N~20N (Initial reading)		

A-7-7 Extraction Force			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3 °C / 74.6 %RH	Ge Xinglin	Pass
Test condition	Speed: 12.5mm/min; Extraction depth: 4.8mm.		
Criteria	Extraction force: 8N~20N; 33% of the initial reading.		

A-7-9 Extraction Force			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/22	Temp. 22.8 °C / 74.1 %RH	Ge Xinglin	Pass
Test condition	Speed: 12.5mm/min; Extraction depth: 4.8mm.		
Criteria	Extraction force: 6N~20N.		

Test data:					
A-7-5 Extraction Force					
Sample Coding	A7-1	A7-2	A7-3	A7-4	A7-5
Extraction force (N)	19.8	18.5	19.6	18.4	19.0
Sample Coding	A7-6	A7-7	A7-8	A7-9	A7-10
Extraction force (N)	14.2	18.8	18.0	19.2	19.0
A-7-7 Extraction Force					
Sample Coding	A7-1	A7-2	A7-3	A7-4	A7-5
Extraction force (N)	19.6	13.7	15.0	14.2	19.8
$\frac{ (A-7-7)-(A-7-5) }{(A-7-5)} * 100\%$	1.0%	25.9%	23.5%	22.8%	0.4%
Sample Coding	A7-6	A7-7	A7-8	A7-9	A7-10
Extraction force (N)	12.8	16.6	14.6	16.0	16.2
$\frac{ (A-7-7)-(A-7-5) }{(A-7-5)} * 100\%$	9.9%	7.8%	18.9%	16.7%	14.7%
A-7-9 Extraction Force					
Sample Coding	A7-1	A7-2	A7-3	A7-4	A7-5
Extraction force (N)	12.3	6.4	7.6	6.1	6.4
Sample Coding	A7-6	A7-7	A7-8	A7-9	A7-10
Extraction force (N)	6.1	6.1	6.2	6.0	13.8

8.9. Clause 3.8.1.3 Durability

A-1-2 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11	Temp. 22.1 °C/ 69.9 %RH	Zhan Xingcheng	Pass
Test condition	Auto cycle: cycle rate: 500±50/h; Number of cycles: 50.		
Criteria	No evidence of physical damages.		

A-2-2 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11	Temp. 22.2 °C/ 75.8 %RH	Ge Xinglin	Pass
Test condition	Auto cycle: cycle rate: 500±50/h; Number of cycles: 50.		
Criteria	No evidence of physical damages.		

A-3-2 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11	Temp. 22.2 °C/ 75.8 %RH	Ge Xinglin	Pass
Test condition	Auto cycle: cycle rate: 500±50/h; Number of cycles: 50.		
Criteria	No evidence of physical damages.		

A-4-2 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/08	Temp. 21.2 °C/ 68.9 %RH	Zhan Xingcheng	Pass
Test condition	Auto cycle: cycle rate: 500±50/h; Number of cycles: 50.		
Criteria	No evidence of physical damages.		

A-7-3 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3 °C/ 74.6 %RH	Ge Xinglin	Pass
Test condition	Manual mating/unmating 4 cycles.		
Criteria	No evidence of physical damages.		

A-7-6 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 23.3 °C/ 74.6 %RH	Ge Xinglin	Pass
Test condition	Manual mating/unmating 25 cycles.		
Criteria	No evidence of physical damages.		

A-7-8 Durability			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/20	Temp. 24.1 °C/ 76.2 %RH	Ge Xinglin	Pass
Test condition	Auto cycle- cycle rate: 500±50/h; Number of cycles: 10000. 2468 cycles (normal) + 2500 cycles (Rotate the receptacle 180°) + 2500 cycles (normal) + 2500 cycles (Rotate the receptacle 180°)		
Criteria	No evidence of physical damages.		

8.10. Clause 3.8.1.3 Reseating

A-1-5 Re-seating			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/18	Temp. 22.6 °C/ 78.8%RH	Zhan Xingcheng	Pass
Test condition	Manual mating/unmating 3 cycles.		
Criteria	No evidence of physical damages.		

A-2-7 Re-seating			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/21	Temp. 23.0 °C/ 72.1 %RH	Ge Xinglin	Pass
Test condition	Manual mating/unmating 3 cycles.		
Criteria	No evidence of physical damages.		

A-4-9 Re-seating			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/22	Temp. 22.6 °C/ 71.2 %RH	Zhan Xingcheng	Pass
Test condition	Manual mating/unmating 3 cycles.		
Criteria	No evidence of physical damages.		

8.11. Clause 3.8.1.6 4-Axis Continuity

B-1-4 4-Axis Continuity			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/25	Temp. 21.2 °C/76.9 %RH	Liu Baoming	Pass
Test condition	Mated, 20N Force at 15 mm from receptacle shell mating edge. Duration: 10 seconds; Direction: 0, 90, 180, 270.		
Criteria	No discontinuities greater than 1.0 microsecond during 10 seconds at each axis.		


8.12. Clause 3.8.2 Temperature life

A-1-3 Temperature Life			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11-2022/07/16	Temp. 21.2 °C/ 69.9%RH	Zhan Xingcheng	Pass
Test condition	Mated; Temperature: 105±2°C; Duration: 120h.		
Criteria	No evidence of physical damages.		

A-3-3 Temperature Life			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11-2022/07/14	Temp. 21.2 °C/ 71.2 %RH	Zhan Xingcheng	Pass
Test condition	Mated; Temperature: 105±2°C; Duration: 72h.		
Criteria	No evidence of physical damages.		


A-4-3 Temperature Life			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/08-2022/07/11	Temp. 21.2 °C/ 67.8 %RH	Zhan Xingcheng	Pass
Test condition	Mated; Temperature: 105±2°C; Duration: 72h.		
Criteria	No evidence of physical damages.		

8.13. Clause 3.8.2 Thermal shock

A-2-3 Thermal Shock			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/11-2022/07/11	Temp. 22.3 °C/ 67.8 %RH	Zhan Xingcheng	Pass
Test condition	Mated; -55±0°C to 85±1°C, 10 cycles; High/low temperature transfer time within 5 min. 		
Criteria	No evidence of physical damages.		

8.14. Clause 3.8.2 Cyclic temperature and humidity

A-2-5 Cyclic temperature and humidity			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/15-2022/07/18	Temp. 21.2 °C/ 67.9 %RH	Zhan Xingcheng	Pass
Test condition	Mated: Temperature of 25°C ±3°C relative humidity of 80%±3% to Temperature of 65°C ±3°C relative humidity of 50%±3% . Thermal emptytime 0.5 hour . maintain 1 hour . 24 cycles.		
Criteria	No evidence of physical damages.		


8.15. Clause 3.8.2 Vibration

A-3-5 Vibration			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/19	Temp. 28.0 °C/ 78.8 %RH	Ge Xinglin	Pass
Test condition	Mated: random vibration: Frequency:20-500Hz; 15min./axis for 3 axis (X,Y,Z); Power spectral density:0.02g ² /Hz, Acceleration:3.1grms.		
Criteria	No evidence of physical damages. No discontinuities of 1us or greater duration happened		

8.16. Clause 3.8.2 Mixed flowing gas

A-4-5 Mixed flowing gas			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/13-2022/07/20	Temp: 24.8 °C/ 70.4 %RH	Zhan Xingcheng	Pass
Test condition	CL2:(10±3) ppb; NO2:(200±50) ppb; H2S:(10±5) ppb SO2:(100±20) ppb; Temperature:(30±1)°C; Humidity:(70±2)%RH. 1/3 days and then unmated for 2/3 days. The others are exposed mated for full 7 days test period.		
Criteria	No evidence of physical damages.		

8.17. Clause 3.8.2 Thermal disturbance

A-4-7 Thermal disturbance			
Testing Period	Measure environment	Test Engineer	Test Result
2022/07/21-2022/07/22	Temp: 21.2 °C/ 67.9 %RH	Zhan Xingcheng	Pass
Test condition	Mated Cycle the connector or socket between 15 °C ± 3 °C and 85 °C ± 3 °C, as measured on the part. Ramps should be a minimum of 2 °C per minute, and dwell times should insure that the contacts reach the temperature extremes (a minimum of 5 minutes). Humidity is not controlled. Perform 10 such cycles.		
Criteria	No evidence of physical damages.		

9. Test Equipments Utilized

Name	Model	Serial number	Calibration Date	Expire Date
Oven Machine (ESPEC)	LC-213	1010170285	2023.11.24	2024.11.23
Thermal Shock Chamber(ESPEC)	TSE-12-A	161003228	2023.12.05	2024.12.04
Temperature & Humidity Chamber	GPL-2	0010-003613	2023.11.24	2024.11.23
Mixed Flow Gas Chamber(Yamasaki)	GH-180/VL	705	2023.12.05	2024.12.04
Vibration machine	V455-PAL1000 L	1020385-1	2023.11.24	2024.11.23
Durability Tester	YH-8816USDT	17068816077	2023.11.27	2024.11.26
Durability Tester	YH-8816USDT	17068816079	2023.11.27	2024.11.26
4-axis Tester	YH-8812WEXT	17068812429	2023.11.27	2024.11.26
4-axis Tester	YH-8812WEXT	17068812430	2023.11.27	2024.11.26
Microscope	MM-400/L	3413948	2023.11.27	2024.11.26
Micro-ohmmeter	RM3545	170938239	2023.11.27	2024.11.26
Electronic load meter	63610-80-20	636001001093	2023.11.27	2024.11.26
Electronic load meter	63610-80-20	636001001094	2023.11.27	2024.11.26
DC power supply	DH-1756-2	105910112004 7	2023.11.27	2024.11.26
Temperature rise test system	GP10	S5T909482	2023.11.27	2024.11.26
Moment disconnection tester	NM11B	20010112	2023.11.29	2024.11.28



1. Test Laboratory

1.1. Testing Location

Location: SAICT

Address: Building G, Shenzhen International Innovation Center, No.1006 Shenran Road, Futian District, Shenzhen, Guangdong, P. R. China 518000

1.2. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 25-85%RH

Atmospheric pressure: 86-106kPa

1.3. Project Data

Testing Start Date: 2022-06-23

Testing End Date: 2022-07-25

1.4. Signature

Zhan WeiLong

Prepared this test report

Wang Yang

Reviewed this test report

Wei Ming

Approved this test report

2. Client Information

2.1. Applicant Information

Company Name: Guangdong Jingshengxin Industry Share Co., Ltd.
Address: 158 Quan Tong Road, Dalang Town, Dongguan City,
Guangdong Province
City: Dongguan
Country: China
Email: raoweimin@jstxconn.cn


2.2. Manufacturer Information

Company Name: Guangdong Jingshengxin Industry Share Co., Ltd.
Address: 158 Quan Tong Road, Dalang Town, Dongguan City,
Guangdong Province
City: Dongguan
Country: China
Telephone: 0769-82913101




Electrical Safety Analyzer	TOS9201	XK002479	2023.11.27	2024.11.26
AVO meter	87VC	37980325WS	2023.11.27	2024.11.26

ANNEX A: UUT photograph



ANNEX B: Drawing



ANNEX C: Insertion Force & Extraction Force Test Layout



ANNEX D: Durability Test Layout



ANNEX E: Dielectric withstanding voltage Test Layout

ANNEX F: Vibration Test Layout

ANNEX G: Contact Current Rating Test Layout

END OF REPORT



3. Unit Under Test (UUT) Information

3.1. About UUT

Description:	USB2.0 Type-C Receptacle Connector
Brand Name:	Guangdong Jinshengxin Industry Share Co., Ltd.
Marking Name:	USB TYPE C FEMALE 16PIN 180° TYPE
Model Name:	JSX-CF-009
Hardware Version:	A

3.2. Sample Coding

Test Group	Number of Plug/Receptacle	Qty of Specimen
Group A-1	A1-1 to A1-10	10 pcs
Group A-2	A2-1 to A2-10	10 pcs
Group A-3	A3-1 to A3-10	10 pcs
Group A-4	A4-1 to A4-20	20 pcs
Group A-7	A7-1 to A7-10	10 pcs
Group B-1	B1-1 to B1-8	8 pcs
Group B-5	B5-1 to B5-3	3 pcs
Group B-6	B6-1 to B6-3	3 pcs

4. Reference Documents



1. EN IEC 62680-1-3:2022, Universal serial bus interfaces for data and power-Part 1-3: Common components – USB Type-C Cable and Connector Specification
2. Universal Serial Bus Type-C Connectors and Cable Assemblies Compliance Document Revision 2.1b:2021

5. USB Type-C Compliance Requirements

5.1. DC Electrical

Clause	Test Item	Test Procedure	Requirement
3.7.8.1	Low Level Contact Resistance (LLCR)	EIA 364-23 The low level contact resistance (LLCR) measurement is made across the plug and receptacle mated contacts and does not include any internal paddle, cast, or substrate of the plug or receptacle. The test boards shall be provided with the connectors to be tested. - Measure at 20 mV (max) open circuit at 100 mA.	The following requirements apply to the power and signal contacts: +40 mΩ (max) initial for VBUS, GND and all other contacts. +50 mΩ maximum after initial measurement.
3.7.8.2	Dielectric Withstanding Voltage	EIA 364-20 Applicable to both receptacle and plug. - Measurement per Method E.	The dielectric shall withstand 100 VAC (RMS) for one minute at sea level for the environmental tests defined in Table 4-8, Test Group A-7.
3.7.8.3	Insulation Resistance	EIA 364-21 Applicable to both receptacle and plug. See Table 4-8, Test Group A-7.	A minimum of 100 MΩ insulation resistance is required between adjacent contacts of unmated and mated connectors.
3.7.8.4	Contact Current Rating	A current of 5 A shall be applied collectively to VBUS pins (i.e., pins A4, A9, B4, and B9) and 1.25 A shall be applied to the VCONN pin (i.e., B5) as applicable, to minimize it through the corresponding GND pins (i.e., pins A1, A2, B1, and B2). A minimum current of 0.25 A shall also be applied individually to all the other contacts, as applicable.	The temperature rise of the outside shell surface of the mated pair above the VBUS and GND contacts shall not exceed 30°C above the ambient temperature.

5.2. Mechanical

Clause	Test Item	Test Procedure	Requirement
32.1	Critical Dimensions	 <p>(See Appendix D for detailed test fixtures)</p>	
38.1.1	Insertion force	EIA 364-13 The insertion force test shall be done at a maximum speed of 12.5 mm (0.492") per minute.	Within the range from 5 N to 20 N. The requirement does not apply to the plugs that are used for direct docking without a cable.
38.1.2	Extraction force	EIA 364-13 The extraction force test shall be done at a maximum speed of 12.5 mm (0.492") per minute.	Within the range of 5 N to 20 N, measured after a pre-conditioning of five insertion/extraction cycles (i.e., the sixth extraction). After an additional twenty-five insertion/extraction cycles, the extraction force shall be measured again (i.e., the thirty-third extraction) and the extraction force shall be within: <ul style="list-style-type: none"> a) 85% of the initial reading, and b) within the range of 5 N to 20 N. The extraction force shall be within the range of 5 N to 20 N after 10,000 insertion/extraction cycles. The requirement does not apply to the plugs that are used for direct docking without a cable.
38.1.3	Durability	EIA 364-09	10,000 cycles minimum. Low level contact resistance and debris withstanding voltage shall be checked to be within spec after the 10,000 durability cycles according to Table 4-8, Test Group A-7.
38.1.6	4-Wire Continuity	See Appendix D for detailed test fixtures and procedures. Plug and Receptacle: Subject the mating interface to the moments defined in appendix D for at least 10 seconds.	No discontinuities greater than 1 microsecond duration in any of the four wires to be tested.

5.3. Environmental

Clause	Test Item	Test Procedure	Requirement
3.8.2	Temperature life	EIA 364-17, Method A. 105°C without applied voltage for 120 hours. 105°C without applied voltage for 72 hours when used as preconditioning.	Low level contact resistance: meets spec before and after the Temperature Life test.
3.8.2	Vibration	EIA 364-28 Test Condition VII, Test Letter D.	No evidence of physical damages and no discontinuity longer than 1 microsecond. Low level contact resistance: meets spec before and after the Vibration test.
3.8.2	Cyclic temperature and humidity	EIA 364-31.	Low level contact resistance: meets spec before and after the Cyclic Temperature and Humidity test.
3.8.2	Thermal shock	EIA 364-32, Test Condition I 10 Cycles -55°C and +65°C.	No evidence of any physical damage. Low level contact resistance: meets spec before and after the Thermal Shock test.
3.8.2	Mixed flowing gas	IA 364-65, Class B A Samples should be placed in an environmentally controlled test chamber that is monitored by a gas analyzing system for controlled concentrations of the specified gas mixture. Test coupons shall also be used and the weight gain reported. Test duration is 7 days.	Low level contact resistance: meets spec before and after the Mixed Flowing Gas test.

6. Test Procedure

For the DC electrical, Mechanical and Environmental compliance requirements of Type-C connector, refer to the grouping and test methods in the EIA364-1 000.01 standard to implement the test:

Group A-1	
No.	Test Item
A-1-1	Low level contact resistance
A-1-2	Durability (preconditioning)
A-1-3	Temperature life
A-1-4	Low level contact resistance
A-1-5	Reseating
A-1-6	Low level contact resistance
Group A-2	
No.	Test Item
A-2-1	Low level contact resistance
A-2-2	Durability (preconditioning)
A-2-3	Thermal shock
A-2-4	Low level contact resistance
A-2-5	Cyclic temperature and humidity
A-2-6	Low level contact resistance
A-2-7	Reseating
A-2-8	Low level contact resistance
Group A-3	
No.	Test Item
A-3-1	Low level contact resistance