



CE EMC TEST REPORT

for

Product: PC Power Supply

Model: ATX-1350 (See model list on page 11-15)

Report No.: PTC26032101501E-EM01

Issued for

Guangzhou Herui Electronic Technology Co., Ltd.

**Room 402 \ 404, 4th Floor, No. 70, Xingshan Middle Road, Zhongluotan Town,
Baiyun District, Guangzhou City**

Issued by

Precise Testing & Certification (Guangdong) Co., Ltd.

**Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong,
China.**

TEL: +86-769-3880 8222

FAX: +86-769-3882 6111

Note: This report shall not be reproduced except in full, without the written approval of Precise Testing & Certification (Guangdong) Co., Ltd. This document may be altered or revised by Precise Testing & Certification (Guangdong) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results presented in this report only relate to the tested sample.





TABLE OF CONTENTS

1. TEST CERTIFICATION	3
2. TEST SUMMARY	4
3. TEST SITE	5
3.1. TEST FACILITY	5
3.2. MEASUREMENT UNCERTAINTY	5
3.3. DECISION RULE	5
3.4. LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
4. EUT DESCRIPTION	10
5. TEST METHODOLOGY	16
5.1. TEST MODE	16
5.2. EUT SYSTEM OPERATION	16
6. SETUP OF EQUIPMENT UNDER TEST	17
6.1. DESCRIPTION OF SUPPORT UNITS	17
6.2. CONFIGURATION OF SYSTEM UNDER TEST	17
7. EMISSION TEST	18
7.1. CONDUCTED EMISSION MEASUREMENT	18
7.2. RADIATED EMISSION MEASUREMENT	22
7.3. HARMONICS CURRENT MEASUREMENT	26
7.4. VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT	34
8. IMMUNITY TEST	36
8.1. GENERAL DESCRIPTION	36
8.2. GENERAL PERFORMANCE CRITERIA DESCRIPTION	37
8.3. ELECTROSTATIC DISCHARGE (ESD)	38
8.4. RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS)	42
8.5. ELECTRICAL FAST TRANSIENT (EFT)	45
8.6. SURGE IMMUNITY TEST	47
8.7. CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)	49
8.8. POWER FREQUENCY MAGNETIC FIELD	51
8.9. VOLTAGE DIP & VOLTAGE INTERRUPTIONS	53
9. PHOTOGRAPHS OF THE TEST CONFIGURATION	55
10. PHOTOGRAPHS OF EUT	59



1. TEST CERTIFICATION

Product:	PC Power Supply
Model:	ATX-1350(See model list on page 11-15)
Applicant :	Guangzhou Herui Electronic Technology Co., Ltd.
Address:	Room 402-404, 4th Floor, No. 70, Xingshan Middle Road, Zhongluotan Town, Baiyun District, Guangzhou City
Manufacturer:	Guangzhou Guanghai Electronic Co., Ltd.
Address:	No. 388, Guangcong 5th Road, Zhongluotan Town, Baiyun District, 510550 Guangzhou, PEOPLE'S REPUBLIC OF CHINA.
Test Date:	April 25,2024 to May 13,2024
Issued Date:	April 02,2026
Test Voltage:	AC 230V/50Hz
Applicable Standards:	EMC Directive 2014/30/EU EN 55032:2015+A11:2020+A1:2020 EN 55035: 2017+A11:2020 EN IEC 61000-3-2:2019+A1:2021+A2:2024 EN 61000-3-3:2013+A1:2019+A2:20211

The above equipment has been tested by Precise Testing & Certification (Guangdong) Co., Ltd. and found compliance with the requirements in the technical standards mentioned above. The test results presented in this report only relate to the product/system tested. The Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Test Engineer:

Technical Manager:



Carson Zhang / Engineer

Simon Pu / Manager



2. TEST SUMMARY

EMISSION			
Standard	Item	Result	Remarks
EN 55032:2015+A11:2020+A1:2020	Conducted emission (Mains Port)	PASS	Meet Class B limit
	Radiated emission	PASS	Meet Class B limit
EN IEC 61000-3-2:2019+A1:2021+A2:2024	Harmonic current emissions	PASS	Complied with limit
EN 61000-3-3:2013+A1:2019+A2:2021	Voltage fluctuations & flicker	PASS	Complied with limit

IMMUNITY			
Standard	Item	Result	Remarks
IEC 61000-4-2:2008	ESD	PASS	Complied with the requirements
IEC 61000-4-3:2006+A1:2008+A2:2010	RS	PASS	Complied with the requirements
IEC 61000-4-4:2012	EFT	PASS	Complied with the requirements
IEC 61000-4-5:2005	Surge	PASS	Complied with the requirements
IEC 61000-4-6:2008	CS	PASS	Complied with the requirements
IEC 61000-4-8:2009	PFMF	N/A	N/A
IEC 61000-4-11:2004	Voltage dips & voltage variations	PASS	Complied with the requirements

Note: 1) The test result verdict is decided by the limit of test standard.

2) The information of measurement uncertainty is available upon the customer's request.

3) This report is derived and reported based on PTC24042413301

4) As declared by client that the name (or registered trade mark) and address of the certificateholder (manufacturer) or the importer or authorized representative based within the European Economic Area will be clearly affixed on the product or where that is not possible, on the packaging or in a document accompanying the product.



3. TEST SITE

3.1. TEST FACILITY

Precise Testing & Certification (Guangdong) Co., Ltd.

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.

☆ CNAS Registration No.: CNAS L5772

☆ FCC Registration No.: 790290

☆ A2LA Certificate No.: 4408.01

☆ IC Registration No.: 12191A

3.2. MEASUREMENT UNCERTAINTY

Parameter	U _{lab}	U _{cispr}
Temperature	± 1° C	-
Humidity	± 5%	-
DC and Low Frequency Voltages	± 3%	-
Conducted Emission(9KHz-150KHz)	± 3.60dB	± 3.80dB
Conducted Emission(9KHz-30MHz)	± 3.60dB	± 3.40dB
Conducted Emission(Control port)	± 3.46dB	± 5.00dB
Disturbance Power	± 3.68dB	± 4.50dB
Loop	± 4.02dB	± 3.30dB
Radiated Emission(30MHz-1GHz)	± 4.76dB	± 6.30dB
Radiated Emission (1GHz-6GHz)	± 4.44dB	± 5.20dB
Radiated Emission (6GHz-18GHz)	± 4.44dB	± 5.50dB

Note 1: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.3. DECISION RULE

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The U_{lab} is less than U_{cispr}, compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; non-compliance is deemed to occur if any



measured disturbance level exceeds the disturbance limit.

3. For conducted emission test of laboratory have a measurement uncertainty greater than that specified in harmonized standard, this equipment can still be used provided that an adjustment is made follows: any additional uncertainty in the test system over and above that specified in harmonized standard should be used to tighten the test requirements-making the test harder to pass. This procedure will ensure that a test system not compliant with harmonized standard does not increase the probability of passing a EUT that would otherwise have failed a test if a test system compliant with harmonized standard had been used.

3.4. LIST OF TEST AND MEASUREMENT INSTRUMENTS

3.4.1. For conducted emission at the mains terminals test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 17,2023	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	Aug. 17,2023	1 Year
ISN	Rohde&Schwarz	ENY81	100118	Aug. 17,2023	1 Year
ISN	Rohde&Schwarz	NTFM8158	00252	Jul. 24,2023	1 Year
Test S/W	Tonscend	JS32-CE/4.0.0.3			

3.4.2. For radiated emission test (30MHz-1GHz)

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 17,2023	1 Year
Bilog Antenna	SCHWARZBECK	VULB 9160	9160-3355	Aug. 19,2023	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9745	9745-0013	Mar. 23, 2024	1 Year
Test S/W	Tonscend	JS32-RE/4.0.0.0			

**3.4.3. For radiated emission test (1GHz above)**

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Spectrum Analyzer	Rohde&Schwarz	FSVR40	6625-01-588-5515	Aug. 17,2023	1 Year
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	Aug. 19,2023	1 Year
High NOISE AMPLIFIER	ZHINAN	ZN3380C	15002	Aug. 17,2023	1 Year
Test S/W	Tonscend	JS32-RE/4.0.0.0			

3.4.4. For harmonic current emissions and voltage fluctuations/flicker test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Harmonics / Flicker Test System	California Instruments	CTS/PACS-1-115	1534A00401	Aug. 17,2023	1 Year
AC Power Source	California Instruments	3001IX-208-CTS	1534A00401	Aug. 17,2023	1 Year
Test S/W	AMETEK	CTS 4			

3.4.5. For electrostatic discharge immunity test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
ESD Generator	EMPEK	ESD-2030G	2510007	Aug. 17,2023	1 Year

3.4.6. For radio frequency electromagnetic field immunity (R/S) test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Power meter	Agilent	E4419B	GB42421440	Aug. 17,2023	1 Year



Isotropic Field Probe	Narda	EP-601	611WX80275	Mar. 22,2024	1 Year
Amplifier	SKET	HAP_801000M-250W	201811050	Mar. 22,2024	1 Year
Amplifier	SKET	HAP_0103G-75W	201811051	Mar. 22,2024	1 Year
Amplifier	SKET	HAP_0306G-20W	201811052	Aug. 17,2023	1 Year
Log-periodic Antenna	SKET	ZDSZ-80T1000M-231	SKT231015	Aug. 17,2023	1 Year
Log-periodic Antenna	SKET	ZDSZ-1T6G-232	SKT232079	Aug. 17,2023	1 Year

3.4.7. For electrical fast transient/burst immunity test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
EFT Tester	HTEC	HV1P16T/HCOM PACT52	170901/190901	Aug. 17,2023	1 Year
EFT Coupling Clamp	HTEC	HEFT 51-C	1416011	Aug. 17,2023	1 Year

3.4.8. For surge immunity test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Surge Tester	HTEC	HCWG 71	174302	Aug. 17,2023	1 Year
Surge Tester	HTEC	TCOMB 4	142103	Aug. 17,2023	1 Year
Surge Tester	HTEC	HTSG 70	175002	Aug. 17,2023	1 Year

3.4.9. For injected currents susceptibility test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
C/S Test System	SCHLODER	CDG-6000-25	126A1279/2014	Aug. 17,2023	1 Year



Coupling Decoupling Network	SCHLODER	CDN-M2+3	A2210251/2013	Aug. 17,2023	1 Year
Electromagnetic Injection Clamp	Luthi	EM101	36041	Aug. 17,2023	1 Year
Test S/W	SCHLODER	CDG/1.0.0.0			

3.4.10. For power frequency magnetic field immunity test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Magnetic Field Tester	HTEC	HMFG-100	HMFG-100	Aug. 17,2023	1 Year

3.4.11. For voltage dips and short interruptions immunity test

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Calibration Interval
Dips Tester	HTEC	HV1P16T/HCOM PACT52	170901/190901	Aug. 17,2023	1 Year



4. EUT DESCRIPTION

Product	PC Power Supply
Model	ATX-1350(See model list on page 11-15)
Supplied Voltage	See model list on page 11-15
Power	N/A

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
AC Port	1	<input checked="" type="checkbox"/>
DC Port	1	<input type="checkbox"/>



Models Difference

Model	Input	Output			
		Total Output Power	DC Output Power	DC Output Voltage	DC Output Current
ATX-4** (**=50-99)	200-240V~, 8A, 50Hz, Class I	200W	80W	+3.3V	13A
				+5V	13A
			199.2W	+12V	16.6A
			3.6W	-12V	0.3A
12.5W		+5VSB	2.5A		
ATX-5** (**=00-49)		230W	80W	+3.3V	13A
				+5V	13A
			229.2W	+12V	19.1A
			3.6W	-12V	0.3A
12.5W		+5VSB	2.5A		
ATX-5** (**=50-99)		250W	80W	+3.3V	13A
				+5V	13A
			249.6W	+12V	20.8A
			3.6W	-12V	0.3A
12.5W		+5VSB	2.5A		
ATX-6** (**=00-49)		270W	80W	+3.3V	13A
	+5V			13A	
270W	+12V	22.5A			



			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-6** (**=50-99)	300W	100W	+3.3V	15A	
			+5V	15A	
		300W	+12V	25A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-7** (**=00-49)	350W	100W	+3.3V	15A	
			+5V	15A	
		349.2W	+12V	29.1A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-7** (**=50-99)	400W	100W	+3.3V	15A	
			+5V	15A	
		399.6W	+12V	33.3A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-8** (**=00-49)	450W	100W	+3.3V	15A	
			+5V	15A	
		450W	+12V	37.5A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-8** (**=50-99)	500W	100W	+3.3V	15A	
			+5V	15A	



			499.2W	+12V	41.6A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-9** (**=00-49)	550W	100W	+3.3V	15A	
			+5V	15A	
		549.6W	+12V	45.8A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-9** (**=50-99)	600W	100W	+3.3V	15A	
			+5V	15A	
		600W	+12V	50A	
		3.6W	-12V	0.3A	
		12.5W	+5VSB	2.5A	
ATX-10** (**=00-49)	650W	100W	+3.3V	15A	
			+5V	15A	
		649.2W	+12V	54.1A	
		3.6W	-12V	0.3A	
ATX-10** (**=50-99)	700W	100W	+3.3V	15A	
			+5V	15A	
		699.6W	+12V	58.3A	
		3.6W	-12V	0.3A	
ATX-11**	750W	100W	+5VSB	2.5A	
			+3.3V	15A	



(**=00-49)				+5V	15A
			750W	+12V	62.5A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-11** (**=50-99)		800W	100W	+3.3V	15A
				+5V	15A
			799.2W	+12V	66.6A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-12** (**=00-49)		850W	100W	+3.3V	15A
				+5V	15A
			849.6W	+12V	70.8A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-12** (**=50-99)		900W	100W	+3.3V	15A
				+5V	15A
			900W	+12V	75A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A
ATX-13** (**=00-49)		950W	100W	+3.3V	15A
				+5V	15A
			949.2W	+12V	79.1A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A



ATX-13** (**=50-99)		1000W	100W	+3.3V	15A
				+5V	15A
			999.6W	+12V	83.3A
			3.6W	-12V	0.3A
			12.5W	+5VSB	2.5A

Note:

*=00-49 or 50-99, to distinguish between different sales customers or sales regions, differences do not affect product safety and electromagnetic compatibility.



5. TEST METHODOLOGY

5.1. TEST MODE

The EUT was tested together with the thereafter additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The following test mode(s) were assessed.

	Test Items	Test Mode
Emission	Conducted Emission	Full Load
	Radiated Emission	Full Load
	Harmonic current emissions	Full Load
	Voltage fluctuations & flicker	Full Load
Immunity	ESD	Full Load
	RS	Full Load
	EFT	Full Load
	Surge	Full Load
	C/S	Full Load
	PFMF	N/A
	Dips	Full Load

5.2. EUT SYSTEM OPERATION

1. Set up EUT with the support equipment.
2. Make sure the EUT work normally during the test.



6. SETUP OF EQUIPMENT UNDER TEST

6.1. DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1.	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Note: 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

6.2. CONFIGURATION OF SYSTEM UNDER TEST



(EUT: PC Power Supply)



7. EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. LIMITS

FREQUENCY (MHz)	Class A		Class B	
	Quasi-peak dB(μ V)	Average dB(μ V)	Quasi-peak dB(μ V)	Average dB(μ V)
0.15 - 0.5	79	66	66-56	56-46
0.5 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Note: 1) The lower limit shall apply at the transition frequencies.

2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

7.1.2. TEST PROCEDURES

The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane. When the EUT is floor standing equipment, it is placed on the ground plane, which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane. The EUT should be 0.8 m apart from the AMN, where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the centre into a bundle no longer than 0.4 m, Details please refer to test setup photography.


The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes. During the above scans, the emissions were maximized by cable manipulation.

A scan was taken on both of the power lines, Line and neutral, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The test data of the worst-case condition(s) was recorded.

The test data of the worst-case condition(s) was recorded.

Note: Test Software Name: Tonscend,JS32-RE/4.0.0.3.

7.1.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.4. TEST RESULT

Product name	PC Power Supply	Tested By	Dad
Model	ATX-1350	Detector Function	Peak / Quasi-peak/AV
Test Mode	Full Load	6 dB Bandwidth	9 kHz
Environmental Conditions	25°C, 60 % RH, 101.5 kPa	Test Result	Pass

Note:

L = Line Line, N = Neutral Line

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = attenuator + Cable loss

Level (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Over Limit (dB) = Level (dB μ V) – Limit (dB μ V)


QP = Quasi-Peak

AV = Average



Please refer to the following diagram:

Line:




Final Data List

NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.200	49.00	0.11	49.11	63.63	14.52	44.22	44.33	53.63	9.30	PASS
2	0.303	44.28	0.13	44.41	60.16	15.75	43.05	43.18	50.16	6.98	PASS
3	0.402	43.69	0.12	43.81	57.81	14.00	42.26	42.38	47.81	5.43	PASS
4	0.605	43.10	0.12	43.22	56.00	12.78	42.13	42.25	46.00	3.75	PASS
5	0.906	41.90	0.12	42.02	56.00	13.98	38.88	39.00	46.00	7.00	PASS
6	17.228	49.40	0.81	50.21	60.00	9.79	38.70	39.51	50.00	10.49	PASS



Neutral:



Final Data List

NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.200	49.18	0.11	49.29	63.63	14.34	42.59	42.70	53.63	10.93	PASS
2	0.299	44.78	0.13	44.91	60.28	15.37	42.85	42.98	50.28	7.30	PASS
3	0.398	43.19	0.12	43.31	57.91	14.60	41.00	41.12	47.91	6.79	PASS
4	0.600	41.31	0.12	41.43	56.00	14.57	39.32	39.44	46.00	6.56	PASS
5	0.798	41.25	0.12	41.37	56.00	14.63	38.74	38.86	46.00	7.14	PASS
6	16.575	50.27	0.88	51.15	60.00	8.85	38.14	39.02	50.00	10.98	PASS



7.2. RADIATED EMISSION MEASUREMENT

7.2.1. LIMITS

FREQUENCY (MHz)	Class A(At 3m)	Class B(At 3m)
	Quasi-peak dB(μV/m)	Quasi-peak dB(μV/m)
30 ~ 230	50	40
230 ~ 1000	57	47

Table clause	Frequency range MHz	Measurement		Class B limits dB(μV/m)
		Distance m	Detector type/ bandwidth	F50ATS (see Table A.1)
A5.1	1 000 – 3 000	3	Average/ 1 MHz	50
	3 000 – 6 000			54
A5.2	1 000 – 3 000		Peak/ 1 MHz	70
	3 000 – 6 000			74

Apply A5.1 and A5.2 across the frequency range from 1 000 MHz to the highest required frequency of measurement derived from Table 1.

Note: 1) The lower limit shall apply at the transition frequencies.

2) Emission level (dBμV/m) = 20 log Emission level (μV/m).

7.2.2. TEST PROCEDURE

The equipment was set up as per the test configuration to simulate typical usage per the user’s manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is floor standing equipment, it is placed on the ground plane which has a 0.1 m non-conductive covering to insulate the EUT from the ground plane.

The antenna was placed at 3 meter away from the EUT. The antenna connected to the spectrum analyzer via a cable and at times a pre-amplifier would be used.


The analyzer / receiver quickly scanned from 30 MHz to 1000 MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

During the above scans, the emissions were maximized by cable manipulation. Each modes is measured, recorded at least the six highest emissions. The emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

The test data of the worst-case condition(s) was recorded.

Note: Test Software Name: Tonscend,JS32-RE/4.0.0.0.

7.2.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration

7.2.4. TEST RESULT

Product name	PC Power Supply	Antenna Distance	3 m
Model	ATX-1350	Antenna Pole	Vertical / Horizontal
Test Mode	Full Load	Detector Function	Peak / Quasi-peak
Environmental Conditions	25°C, 60 % RH, 101.5 kPa	6 dB Bandwidth	120 kHz
Tested by	JIANG	Test Result	Pass

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading(dB μ V)

Corr.Factor (dB/m)=Antenna factor(dB/m)+Cable loss(dB)-Preamp Factor(dB)

Measurement (dB μ V/m)=Reading level(dB μ V)+ Corr. Factor (dB/m)

Limit (dB μ V/m) = Limit stated in standard

Over Limit (dB) = Measurement (dB μ V/m) – Limit (dB μ V/m)


QP = Quasi-Peak

The highest frequency of the internal sources of the EUT was less than 108 MHz, so the measurement was only made up to 1 GHz.



Please refer to the following diagram:


Vertical:



Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Polarity	Verdict
1	68.80	42.23	-22.09	20.14	40.00	19.86	Vertical	PASS
2	152.22	50.32	-18.15	32.17	40.00	7.83	Vertical	PASS
3	189.08	53.43	-19.04	34.39	40.00	5.61	Vertical	PASS
4	300.63	49.95	-15.19	34.76	47.00	12.24	Vertical	PASS
5	375.32	52.92	-13.67	39.25	47.00	7.75	Vertical	PASS
6	426.73	48.01	-12.53	35.48	47.00	11.52	Vertical	PASS



Horizontal:



Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Polarity	Verdict
1	63.95	37.92	-22.21	15.71	40.00	24.29	Horizontal	PASS
2	148.41	53.88	-18.06	35.82	40.00	4.18	Horizontal	PASS
3	198.78	51.10	-18.98	32.12	40.00	7.88	Horizontal	PASS
4	288.02	48.10	-15.81	32.29	47.00	14.71	Horizontal	PASS
5	372.41	51.54	-13.66	37.88	47.00	9.12	Horizontal	PASS
6	415.09	47.09	-12.77	34.32	47.00	12.68	Horizontal	PASS



7.3. HARMONICS CURRENT MEASUREMENT

7.3.1. LIMITS OF HARMONICS CURRENT MEASUREMENT

Limit for Class A equipment		Limit for Class D equipment		
Harmonics Order N	Max. permissible harmonics current A	Harmonics Order n	Max. permissible harmonics current per watt mA/W	Max. permissible harmonics current A
Odd harmonics		Odd Harmonics only		
3	2.30	3	3.4	2.30
5	1.14	5	1.9	1.14
7	0.77	7	1.0	0.77
9	0.40	9	0.5	0.40
11	0.33	11	0.35	0.33
13	0.21	13	0.30	0.21
15 ≤ n ≤ 39	0.15x(15/n)	15 ≤ n ≤ 39 (odd harmonics only)	3.85/n	0.15x(15/n)
Even harmonics				
2	1.08			
4	0.43			
6	0.30			
8 ≤ n ≤ 40	0.23x8/n			

Limit for Class C equipment ^a	
Harmonics Order n	Max. permissible harmonics current expressed as a percentage of the input current at the fundamental frequency A
2	2
3	27 ^b
5	10
7	7
9	5
11 ≤ n <= 39 (odd harmonics only)	3

^a:For some Class C products, other emission limits apply (see EN IEC 61000-3-2 7.4).

^b:The limit is determined based on the assumption of modern lighting technologies having power factors of 0,90 or higher

Note: Class A, B, C and D are classified according to item 7.3.2.of this report



7.3.2. TEST PROCEDURES

The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic. The classification of EUT is according to section 5 of EN IEC 61000-3-2.

The EUT is classified as follows:

Class A:

Equipment not specified as belonging to Class B, C or D shall be considered as Class A equipment.

Some examples of Class A equipment are:

- balanced three-phase equipment;
- household appliances, excluding those specified as belonging to Class B, C or D;
- vacuum cleaners;
- high pressure cleaners;
- tools, excluding portable tools;
- independent phase control dimmers;
- audio equipment;
- professional luminaires for stage lighting and studios.

NOTE 1 Equipment that can be shown to have a significant effect on the supply system might be reclassified in a future edition of this document, taking into account the following factors:

- number of pieces of equipment in use;
- duration of use;
- simultaneity of use;
- power consumption;
- harmonic spectrum, including phase.

Class B:

- portable tools;
- arc welding equipment which is not professional equipment.

Class C:

- lighting equipment.

Class D:


Equipment having a specified power less than or equal to 600 W according to 6.3.2, of the following types:

- personal computers and personal computer monitors;
- television receivers;
- refrigerators and freezers having one or more variable-speed drives to control compressor motor(s).

NOTE 2 Class D limits are reserved for equipment that, by virtue of the factors listed in note 1, can be shown to have a pronounced effect on the public electricity supply system.

The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

7.3.3. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.3.4. TEST RESULT

Product	PC Power Supply	Tested by	Bruce
Model	ATX-1350	Limits	Class <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D
Test Mode	Full Load	Observation Period (Tp)	2.5 mins
Environmental Conditions	24.3°C, 52.1 % RH, 101.1 kPa	Test Result	Pass



Please refer to the following test data:

EUT: PC Power Supply M/N:ATX-1350

Tested by: Tested by

Test category: Class-D (European limits)

Test Margin: 100

Test date: 2024/3/13

Start time: 15:29:16

End time: 15:31:57

Test duration (min): 2.5

Data file name: H-000588.cts_data


Comment: Comment

Customer: Guangzhou Herui Electronic Technology Co., Ltd.

Test Result: Pass


Source qualification: Normal

Current & voltage waveforms



Harmonics and Class D limit line

European Limits



Test result: Pass Worst harmonics H3-26.3% of 150% limit, H3-39.1% of 100% limit



Current Test Result Summary (Run time)

EUT: PC Power Supply M/N:ATX-1350 **Tested by:** Tested by
Test category: Class-D (European limits) **Test Margin:** 100
Test date: 2024/3/13 **Start time:** 15:29:16 **End time:** 15:31:57
Test duration (min): 2.5 **Data file name:** H-000588.cts_data
Comment: Comment **Customer:** Guangzhou Herui Electronic Technology Co., Ltd.
Test Result: Pass **Source qualification:** Normal
THC(A): 0.868 **I-THD(%):** 31.8 **POHC(A):** 0.026 **POHC Limit(A):** 0.257

Highest parameter values during test:

V_RMS (Volts): 220.10 **Frequency(Hz):** 50.00
I_Peak (Amps): 5.499 **I_RMS (Amps):** 2.874
I_Fund (Amps): 2.734 **Crest Factor:** 1.919
Power (Watts): 597.0 **Power Factor:** 0.946

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.044	0.000	N/A	0.047	0.000	N/A	Pass
3	0.793	2.030	39.1	0.801	3.045	26.3	Pass
4	0.010	0.000	N/A	0.011	0.000	N/A	Pass
5	0.322	1.134	28.4	0.323	1.701	19.0	Pass
6	0.005	0.000	N/A	0.006	0.000	N/A	Pass
7	0.052	0.597	8.7	0.053	0.895	5.9	Pass
8	0.008	0.000	N/A	0.009	0.000	N/A	Pass
9	0.094	0.298	31.6	0.095	0.448	21.3	Pass
10	0.002	0.000	N/A	0.002	0.000	N/A	Pass
11	0.045	0.209	21.6	0.046	0.313	14.5	Pass
12	0.007	0.000	N/A	0.007	0.000	N/A	Pass
13	0.032	0.179	18.0	0.033	0.269	12.3	Pass
14	0.005	0.000	N/A	0.006	0.000	N/A	Pass
15	0.050	0.155	31.9	0.050	0.233	21.5	Pass
16	0.007	0.000	N/A	0.007	0.000	N/A	Pass
17	0.024	0.137	17.2	0.024	0.206	11.9	Pass



18	0.002	0.000	N/A	0.002	0.000	N/A	Pass
19	0.010	0.121	N/A	0.011	0.182	N/A	Pass
20	0.002	0.000	N/A	0.002	0.000	N/A	Pass
21	0.001	0.109	N/A	0.001	0.164	N/A	Pass
22	0.001	0.000	N/A	0.001	0.000	N/A	Pass
23	0.009	0.100	N/A	0.010	0.150	N/A	Pass
24	0.003	0.000	N/A	0.003	0.000	N/A	Pass
25	0.015	0.092	N/A	0.015	0.138	N/A	Pass
26	0.003	0.000	N/A	0.004	0.000	N/A	Pass
27	0.008	0.085	N/A	0.010	0.128	N/A	Pass
28	0.004	0.000	N/A	0.005	0.000	N/A	Pass
29	0.011	0.079	N/A	0.012	0.119	N/A	Pass
30	0.003	0.000	N/A	0.003	0.000	N/A	Pass
31	0.003	0.074	N/A	0.003	0.111	N/A	Pass
32	0.004	0.000	N/A	0.005	0.000	N/A	Pass
33	0.011	0.069	N/A	0.013	0.104	N/A	Pass
34	0.003	0.000	N/A	0.004	0.000	N/A	Pass
35	0.004	0.066	N/A	0.004	0.099	N/A	Pass
36	0.002	0.000	N/A	0.003	0.000	N/A	Pass
37	0.007	0.062	N/A	0.008	0.093	N/A	Pass
38	0.003	0.000	N/A	0.003	0.000	N/A	Pass
39	0.004	0.059	N/A	0.004	0.089	N/A	Pass
40	0.001	0.000	N/A	0.002	0.000	N/A	Pass

Note: Dynamic limits were applied for this test. The highest harmonics values in the above table may not occur at the same window as the maximum harmonics/limit ratio.

**Voltage Source Verification Data (Run time)**

EUT: PC Power Supply M/N:ATX-1350 Tested by: Tested by
Test category: Class-D (European limits) Test Margin: 100
Test date: 2024/3/13 Start time: 15:29:16 End time: 15:31:57
Test duration (min): 2.5 Data file name: H-000588.cts_data
Comment: Comment Customer: Guangzhou Herui Electronic Technology Co., Ltd.
Test Result: Pass Source qualification: Normal

Highest parameter values during test:

Voltage (Vrms):	220.10	Frequency(Hz):	50.00
I_Peak (Amps):	5.499	I_RMS (Amps):	2.874
I_Fund (Amps):	2.734	Crest Factor:	1.919
Power (Watts):	597.0	Power Factor:	0.946

Harm#	Harmonics V-rms	Limit V-rms	% of Limit	Status
2	0.115	0.440	26.14	OK
3	0.393	1.981	19.83	OK
4	0.066	0.440	14.98	OK
5	0.091	0.880	10.30	OK
6	0.030	0.440	6.80	OK
7	0.017	0.660	2.64	OK
8	0.026	0.440	5.86	OK
9	0.031	0.440	7.02	OK
10	0.023	0.440	5.13	OK
11	0.033	0.220	15.09	OK
12	0.011	0.220	4.90	OK
13	0.027	0.220	12.06	OK
14	0.007	0.220	3.32	OK
15	0.027	0.220	12.46	OK
16	0.013	0.220	5.86	OK
17	0.020	0.220	9.27	OK
18	0.008	0.220	3.85	OK



Report No.: PTC26032101501E-EM01

19	0.010	0.220	4.44	OK
20	0.012	0.220	5.62	OK
21	0.005	0.220	2.40	OK
22	0.005	0.220	2.46	OK
23	0.009	0.220	4.01	OK
24	0.008	0.220	3.58	OK
25	0.014	0.220	6.50	OK
26	0.008	0.220	3.43	OK
27	0.011	0.220	4.78	OK
28	0.010	0.220	4.57	OK
29	0.016	0.220	7.45	OK
30	0.008	0.220	3.83	OK
31	0.005	0.220	2.45	OK
32	0.007	0.220	3.01	OK
33	0.015	0.220	6.62	OK
34	0.008	0.220	3.82	OK
35	0.009	0.220	3.95	OK
36	0.005	0.220	2.50	OK
37	0.014	0.220	6.27	OK
38	0.007	0.220	3.00	OK
39	0.009	0.220	4.11	OK
40	0.013	0.220	5.70	OK

7.4. VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT


7.4.1. LIMITS OF VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT

TEST ITEM	LIMIT	REMARK
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
T_{dt} (ms)	500	T_{dt} means maximum time that dt exceeds 3 %.
d_{max} (%)	4/6/7 %	d_{max} means maximum relative voltage change.
dc (%)	3.3 %	dc means relative steady-state voltage change

7.4.2. TEST PROCEDURE

The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under Full Load operating conditions. During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

7.4.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.4.4. TEST RESULT

Product	PC Power Supply	Tested by	Bruce
Model	ATX-1350	Observation Period (Tp)	10 mins
Test Mode	Full Load	Test Result	Pass
Environmental Conditions	24.2°C, 53.5 % RH, 101.1 kPa		



Please refer to the following test data:

EUT: PC Power Supply M/N: ATX-1350

Tested by: Bruce

Test category: All parameters (European limits)

Test Margin: 100

Test date: 2024/5/9

Start time: 10:13:00

End time: 10:23:27

Test duration (min): 10

Data file name: F-000425.cts_data


Comment: Comments

Customer: Guangzhou Herui Electronic Technology Co., Ltd.


Test Result: Pass

Status: Test Completed

Pst and limit line European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt): 220.13

Highest dt (%):

Test limit (%):

T-max (mS): 0

Test limit (mS): 500.0 Pass

Highest dc (%): 0.00

Test limit (%): 3.30 Pass

Highest dmax (%): 0.00

Test limit (%): 4.00 Pass

Highest Pst (10 min. period): 0.242

Test limit: 1.000 Pass

Highest Plt (2 hr. period): 0.106

Test limit: 0.650 Pass



8. IMMUNITY TEST

8.1. GENERAL DESCRIPTION

Product Standard	EN 55035	
	Test Type	Minimum Requirement
Basic Standard, Specification, and Performance Criterion required	IEC 61000-4-2	Electrostatic Discharge – ESD: ±8 kV air discharge, ±4 kV Contact discharge, Performance Criterion B
	IEC 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80MHz-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz, 3 V/m, 80 % AM(1 kHz), Performance Criterion A
	IEC 61000-4-4	Electrical Fast Transient/Burst - EFT, Power line: ±1 kV, Signal line: ±0.5 kV, Performance Criterion B
	IEC 61000-4-5	Surge Immunity Test: 1.2/50 μs Open Circuit Voltage, 8 /20 μs Short Circuit Current, Power Port ~ Line to line: ±1 kV, Line to earth: ±2 kV Signal Port : ±0.5 kV Performance Criterion B
	IEC 61000-4-6	Conducted Radio Frequency Disturbances Test –CS: 0.15MHz-10MHz: 3V, 10MHz-30MHz: 3V to 1V 30MHz-80MHz: 1V, 3 V r.m.s, 80 % AM, 1 kHz, Performance Criterion A
	IEC 61000-4-8	Power frequency magnetic field immunity test 50 Hz, 1 A/m Performance Criterion A



	IEC 61000-4-11	<p>Voltage Dips: 50/60Hz</p> <p>i) 0% reduction for 0.5 period, Performance Criterion B</p> <p>ii) 70% reduction for 25/35 periods, Performance Criterion C</p> <p>Voltage Interruptions: 0% reduction for 250/300periods, Performance Criterion C</p>
--	----------------	--

8.2. GENERAL PERFORMANCE CRITERIA DESCRIPTION

Criteria A:	<p>During and after the test the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a minimum performance level specified by the manufacturer when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.</p>
Criteria B:	<p>After the test, the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance.</p> <p>During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.</p>
Criteria C:	<p>During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.</p> <p>Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>



8.3. ELECTROSTATIC DISCHARGE (ESD)

8.3.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-2
Discharge Impedance:	330 Ω
Charging Capacity:	150 pF
Discharge Voltage:	Air Discharge: ± 8 kV (Direct) Contact Discharge: ± 4 kV (Direct/Indirect)
Polarity:	Positive & Negative
Number of Discharge:	10 (Air discharge for single polarity discharge) 25 (Contact discharge for single polarity discharge)
Discharge Mode:	1 time/s
Performance Criterion:	B

8.3.2. TEST PROCEDURE

The discharges shall be applied in two ways:

- a) Contact discharges to the conductive surfaces and coupling planes:
50 dischargers (25 with positive and 25 with negative polarity) shall be applied on each accessible metallic part of the enclosure, terminals are excluded. In case of a non-conductive enclosure, dischargers shall be applied on the horizontal or vertical coupling planes. Test shall be performed at a maximum repetition rate of one discharge per second.
- b) Air discharges at slots and apertures and insulating surfaces:
On those parts of the EUT where it is not possible to perform contact discharge testing, the equipment should be investigated to identify user accessible points where breakdown may occur. Such points are tested using the air discharge method. This investigation should be restricted to those area normally handled by the user. A minimum of 10 single air discharges shall be applied to the selected test point for each such area.


The basic test procedure was in accordance with IEC 61000-4-2:

- a) The EUT was located 0.1 m minimum from all side of the HCP (dimensions 1.6 m x 0.8 m).
- b) The support units were located another table 30 cm away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10cm with EUT.



- c) The time interval between two successive single discharges was at least 1 second.
- d) Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- e) Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- f) At least ten single discharges (in the most sensitive polarity) were applied at the front edge of each HCP opposite the center point of each unit of the EUT and 0.1 meter from the front of the EUT. The long axis of the discharge electrode was in the plane of the HCP and perpendicular to its front edge during the discharge.
- g) At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane (VCP) in sufficiently different positions that the four faces of the EUT were completely illuminated. The VCP (dimensions 0.5 m x 0.5 m) was placed vertically to and 0.1 meter from the EUT.

8.3.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

Note:

1) TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the ground reference plane (GRP). The GRP consisted of a sheet of aluminum at least 0.25 mm thick, and 2.5 meters square connected to the protective grounding system. A horizontal coupling plane (HCP) (1.6 m x 0.8 m) was placed on the table and attached to the GRP by means of a cable with 940k total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were placed on the HCP and isolated by an insulating support of 0.5 mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

2) FLOOR-STANDING EQUIPMENT

The equipment under test was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were isolated from the ground reference plane by an insulating support of 0.1 meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25 mm thick, and 2.5 meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.



8.3.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	24.2°C, 55 % RH, 101.5kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass

Air Discharge					
Test Points	Test Levels	Results			
	± 8 Kv	Pass	Fail	Observation	Performance Criterion
Hull 4 Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
Gap 2 Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B

Contact Discharge					
Test Points	Test Levels	Results			
	± 4 Kv	Pass	Fail	Observation	Performance Criterion
HCP 4 Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
VCP 4 Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B

- Note: A) There was no change compared with initial operation during the test.
 B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.
 C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.



8.4. RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS)

8.4.1. TEST SPECIFICATION


Basic Standard:	IEC 61000-4-3
Frequency Range:	80 MHz ~ 1000 MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz
Field Strength:	3 V/m
Modulation:	1 kHz Sine Wave, 80 %, AM Modulation
Frequency Step:	1 % of preceding frequency value
Polarity of Antenna:	Horizontal and Vertical
Test Distance:	3 m
Antenna Height:	1.5 m
Performance Criterion:	A

8.4.2. TEST PROCEDURE

The test procedure was in accordance with IEC 61000-4-3

- The testing was performed in a fully anechoic chamber. The transmit antenna was located at a distance of 3 meters from the EUT.
- The frequency range is swept from 80 MHz to 1000 MHz, with the signal 80% amplitude modulated with a 1 kHz sine-wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s, where the frequency range is swept incrementally, the step size was 1 % of preceding frequency value.
- The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.
- The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

8.4.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

Note:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.



8.4.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	24.1°C, 53 % RH, 101.1kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass

Frequency (MHz)	Polarity	Position	Field Strength (V/m)	Observation	Performance Criterion
80 ~ 1000, 1800, 2600, 3500, 5000	V&H	Front	3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A
80 ~ 1000, 1800, 2600, 3500, 5000	V&H	Rear	3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A
80 ~ 1000, 1800, 2600, 3500, 5000	V&H	Left	3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A
80 ~ 1000, 1800, 2600, 3500, 5000	V&H	Right	3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A

Note: A) There was no change compared with initial operation during the test.

B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.



8.5. ELECTRICAL FAST TRANSIENT (EFT)

8.5.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-4
Test Voltage:	Power Line: ± 1 kV Signal/Control Line: ± 0.5 kV
Polarity:	Positive & Negative
Impulse Frequency:	5 kHz
Impulse Wave-shape:	5/50 ns
Burst Duration:	15 ms
Burst Period:	300 ms
Test Duration:	2 mins
Performance Criterion:	B

8.5.2. TEST PROCEDURE

EUT is placed on a 0.1 m tall wooden table.

EUT operate at normal mode, the transient/burst was 5/50 ns in accordance with EN 61000-4-4, both positive and negative polarity burst waveform were applied.

The duration time of each test line was 2 minutes.

8.5.3. TEST SETUP

The EUT installed in a representative system as described in section 7 of IEC 61000-4-4.

For the actual test configuration, please refer to the related item – photographs of the test configuration.



8.5.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	24.3°C, 54 % RH, 101.2 kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass

Test Point	Polarity	Test Level (kV)	Observation	Performance Criterion
L	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
N	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
L – N	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
PE	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
L – PE	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
N – PE	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
L – N – PE	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
RJ45 UTP cable	--	--	--	--

Note: A) There was no change compared with initial operation during the test.

B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer’s instructions.



8.6. SURGE IMMUNITY TEST

8.6.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-5 Combination Wave
Wave-Shape:	1.2/50 μ s Open Circuit Voltage 8/20 μ s Short Circuit Current
Test Voltage:	Power Port ~ Line to line: ± 1 kV, Line to ground: ± 2 kV
Surge Input/Output:	Power Line: L-N / L-PE / N-PE
Generator Source Impedance:	2 Ω between networks 12 Ω between network and ground
Polarity:	Positive/Negative
Phase Angle:	0° /90° /180° /270°
Pulse Repetition Rate:	1 time / min
Number of Tests:	5 positive polarity pulses, and 5 negative polarity pulses
Performance Criterion:	B


8.6.2. TEST PROCEDURE

EUT is placed on a 0.8 m tall wooden table.

EUT operate at normal mode, two types of combination wave generator (1.2/50 us open-circuit voltage and 8/20 us short-circuit current) are applied to the EUT power supply terminals via the capacitive coupling network.

The power cord between the EUT and the coupling/decoupling network shall not exceed 2 m in length.

8.6.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

8.6.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	24.3°C, 52 % RH, 101.2 kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass

Test Point	Polarity	Test Level (kV)	Observation	Performance Criterion
L - N	+/-	1	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
L - PE	+/-	2	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
N - PE	+/-	2	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B

Note: A) There was no change compared with initial operation during the test.

B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

8.7. CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)

8.7.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-6
Frequency Range:	0.15MHz-10MHz: 3V, 10MHz-30MHz: 3V to 1V 30MHz-80MHz: 1V
Field Strength:	3 V
Modulation:	1 kHz Sine Wave, 80 %, AM Modulation
Frequency Step:	1 % of preceding frequency value
Coupled cable:	Power Mains, Shielded
Coupling device:	CDN-M3/2 (3 wires/2 wires)
Performance Criterion:	A


8.7.2. TEST PROCEDURE

The EUT shall be tested within its intended operating and climatic conditions.

The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn, while the other non-excited RF input ports of the coupling devices are terminated by a 50 Ω load resistor.

The frequency range was swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal was modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. The sweep rate was 1.5×10^{-3} decades/s. Where the frequency range is swept incrementally, the step size was 1 % of preceding frequency value the dwell time of the amplitude modulated carrier at each frequency was 0.5 s.

8.7.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration

Note: 1) The EUT is setup 0.1 m above Ground Reference Plane

2) All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.



8.7.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	23.9°C, 50 % RH, 100.6 kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass

Frequency (MHz)	Field Strength (Vrms)	Injected Position	Injection Method	Observation	Performance Criterion
0.15-10	3	AC Mains	CDN-M3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A
10-30	3V to 1V	AC Mains	CDN-M3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A
30-80	1V	AC Mains	CDN-M3	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	A

Note: A) There was no change compared with initial operation during the test.

B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.



8.8. POWER FREQUENCY MAGNETIC FIELD

8.8.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-8
Frequency Range:	50 Hz
Field Strength:	1 A/m
Observation Time:	5 minutes
Inductance Coil:	Rectangular type, 1 m x 1 m
Performance Criterion:	A

8.8.2. TEST PROCEDURE


The equipment is configured and connected to satisfy its functional requirements. It shall be placed on the GRP with the interposition of a 0.1 m-thick insulating support.

The equipment cabinets shall be connected to the safety earth directly on the GRP via the earth terminal of the EUT.

The power supply, input and output circuits shall be connected to the sources of power supply, control and signal.

The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.

8.8.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration Note:

TABLETOP EQUIPMENT

The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

FLOOR-STANDING EQUIPMENT

The equipment shall be subjected to the test magnetic field by using induction coils of suitable dimensions. The test shall be repeated by moving and shifting the induction coils, in order to test the whole volume of the EUT for each orthogonal direction. The test shall be repeated with the coil shifted to different positions along the side of the EUT, in steps corresponding to 50 % of the shortest side of the coil. The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

8.8.4. TEST RESULT

N/A

8.9. VOLTAGE DIP & VOLTAGE INTERRUPTIONS

8.9.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-11
Test Duration Time:	3 test events in sequence
Interval Between Event:	10 seconds
Phase Angle:	0°
Test Cycle:	3 times
Performance Criterion:	0% U_T / 0.5 P, Criterion: B 70% U_T / 25 P(50Hz)30 P(60Hz), Criterion: C 0% U_T / 250 P(50Hz)300 P(60Hz), Criterion: C

8.9.2. TEST PROCEDURE


The EUT and support units were located on a wooden table, 0.8 m away from ground floor.

Setting the parameter of tests and then perform the test software of test simulator.

Changes to the voltage level shall occur at 0 degree crossing point in the a.c. voltage waveform.

Record the test result in test record form.

8.9.3. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



8.9.4. TEST RESULT

Product	PC Power Supply	Environmental Conditions	24.3°C, 54 % RH, 101.2 kPa
Model	ATX-1350	Tested By	Bruce
Test mode	Full Load	Test Result	Pass


Test Power: 230 Vac, 50 Hz&110 Vac, 60 Hz			
Voltage (% Reduction)	Duration (Period)	Observation	Performance Criterion
0	0.5 P	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	B
70	25 P(50Hz)30 P(60Hz)	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	C
0	250 P(50Hz)300 P(60Hz)	Note <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C	C

- Note: A) There was no change compared with initial operation during the test.
 B) During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.
 C) During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

9. PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



HARMONICS & FLICKER TEST



ESD TEST





DIPS TEST



EFT TEST



SURGE TEST





CS TEST






10. PHOTOGRAPHS OF EUT









— End of report —