

Reference No. : WTU24N01019652E
Applicant : Taizhou Tonhe Flow Control Co.,Ltd.
Address : No.3 building, Xinchun SME pioneer park, Jiangkou street, Huangyan, Taizhou city, 318020, Zhejiang, China
Manufacturer : Same as applicant
Address : Same as applicant
Product : flow control device
Model No. : A20-T15-B2-C N/C BR202-AC/DC9-24V, details see attachment
Technical data : AC/DC 9 - 24 V, other details see attachment

Test Standards:**EN 55032:2015+A11:2020****EN 55035:2017+A11:2020**

The above product has been tested by us with the listed standards and found in compliance with the European Electromagnetic Compatibility Directive 2014/30/EU. It is possible to use CE marking to demonstrate the compliance with this EMC Directive.

EN 55032: Electromagnetic compatibility of multimedia equipment - Emission Requirements**EN 55035: Electromagnetic compatibility of multimedia equipment - Immunity requirements**

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the above mentioned EU Directive. Other relevant Directives have to be observed.

After preparation of the necessary technical documentation as well as the EU Declaration of Conformity, the CE marking as shown below can be affixed on the equipment under the sole responsibility of the manufacturer.



Manager: Jianzhong Mao

Date: 2024-04-23

The statement is based on a single evaluation of the sample of above mentioned product. It does not imply an assessment of the whole production.

Waltek Testing Group (Ningbo) Co., Ltd.**Hotline: 400-840-2288 E-mail: nb@waltek.com.cn****Http://www.waltek.com.cn**

Ver.10.22, WALTEK is registered trademark. Utilisation and application requires prior approval.

Attachment

Model list



Reference No: WTU24N01019652E

No.	Model	Rated Voltage	Note
1.	A20-T*_**_***-N/**** BR** ***02-AC/DC9-24V	AC/DC 9 - 24 V	/
Remarks: "*" means Body Size, can be coded 8(DN8), 10(DN10), 15(DN15), 20(DN20), 25(DN25), 32(DN32); "**" means valve material and ports, can be code S2(stainless steel two way), B2(brass two way), P2(PVC two way), N2(nickel plate brass two way), N3(nickel plate brass three way), S3(stainless steel three way), B3(brass three way), E2 (PPE two way valve) E3((PPE three way valve), P3((PVC three way valve); "***" means indication state, can be code A (no indicator, no manual override on actuator), B (with indicator & manual override on actuator), C (with indicator, no manual override on actuator) or CH (higher top cover with indication); "****" means Actuator power off state, code O (normally open) or C (normally close); "*****" means Cable cores, can be code 5(five wires) or 2(two wires).			

