



A P P R O V A L S ®

## Certificate of Suitability

**Certificate No.:** SAA212601

**Certificate Holder:** Risunic Technology (Shenzhen) Co.,Ltd  
Room 701, 801 and 901, Building 2,  
Fubilon Technology Factory District, Tantou Community,  
Songgang Street, Bao'an District,  
Shenzhen City,  
P.R. China

**Regulatory Definition:** Non-Prescribed  
**Product Description:** POE Power Supply (Desktop type)  
**Trade Name/s:** RISUNIC  
**Model No.:** RP024W01-4800500ZG  
**Rating/Marking/s:** Input: 100-240Vac 50/60Hz, 0.6A Max  
Output: 48.0Vdc 0.5A 24.0W  
Class II

**Standard/s:** AS/NZS 62368.1:2018  
**Condition/s:** Nil

**Approval Marks:** RCM (In accordance with AS/NZS 4417 and EESS requirements)  
and  
SAA212601

**Initial Issue Date:** 6 December 2021  
**Expiry Date:** 6 December 2026


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 31-08-22 212601  
Corrected Page 1 of 4



A P P R O V A L S ®

## Certificate of Suitability

Additional Models	Trade Name	Rating/Marking
RP024W01-4800500ZE	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800500ZV	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800500ZX	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800320ZG	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800320ZE	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800320ZV	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800320ZX	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800350ZG	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800350ZE	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800350ZV	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 31-08-22 212601  
Corrected Page 2 of 4





A P P R O V A L S ®

## Certificate of Suitability

Additional Models	Trade Name	Rating/Marking
RP024W01-4800320ZX	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.5A 24.0W Class II
RP024W01-4800350ZG	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800350ZE	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800350ZV	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800350ZX	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.35A 16.8W Class II
RP024W01-4800450ZG	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.45A 21.6W Class II
RP024W01-4800450ZE	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.45A 21.6W Class II
RP024W01-4800450ZV	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.45A 21.6W Class II
RP024W01-4800450ZX	RISUNIC	Input: 100-240Vac 50/60Hz, 0.6A Max Output: 48.0Vdc 0.45A 21.6W Class II


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 31-08-22 212601  
Corrected Page 4 of 4