



Attestation of Compliance

Reference No. : LCSB11064019S

Applicant : Guangdong Mason Technologies Co., Ltd.

Address : No.2, Industrial West #1 Road, Songshan Lake High-tech Industrial Development Zone, Dongguan, Guangdong, China

Product : LED Flood Light

Trade Mark : Masonled

Model(s) : SEE ANNEX I

Parameters : SEE ANNEX I

Tested according to : EN 60598-2-5:2015; EN IEC 60598-1:2021+A11:2022;
EN 62493:2015+A1:2022; EN IEC 62031:2020+A11:2021

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/35/EU, Referred to as the Low Voltage Directive. It confirms that the listed product complies with all essential requirements of the LVD Directive and applies only to the sample and its technical documentation submitted to Shenzhen Southern LCS Compliance Testing Co., Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: December 03, 2024



Shenzhen Southern LCS Compliance Testing Co., Ltd.
Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Tel: (86)0755-29871520 Fax: (86)0755-29871521
Http://www.lcs-cert.com Email: webmaster@lcs-cert.com

ANNEX I:



Reference No. : LCSB11064019S

Model(s) :

Model	Rating	LED driver	Size (mm)	Mounting height (m)	LED chip
MS-FL13620 20	120-277V~, 50/60Hz, 20W, IP66, ta50°C	BQ-40F2-260-V	L242*W169*H51	5	3030
MS-FL13630 30	120-277V~, 50/60Hz, 30W, IP66, ta50°C				
MS-FL13640 50	120-277V~, 50/60Hz, 50W, IP66, ta50°C	BQ-60F2-260-V	L283*W220*H52	8	
MS-FL13640 80	120-277V~, 50/60Hz, 80W, IP66, ta50°C	BQ-80F2-260-V	L369*W278*H52	10	
MS-FL13651 00	120-277V~, 50/60Hz, 100W, IP66, ta50°C	BQ-100F2-260-V			
MS-FL13661 20	120-277V~, 50/60Hz, 120W, IP66, ta50°C	BQ-120F2-260-V	L394*W395*H57	15	
MS-FL13661 50	120-277V~, 50/60Hz, 150W, IP66, ta50°C	BQ-150F2-260-V			
MS-FL13671 80	120-277V~, 50/60Hz, 180W, IP66, ta50°C	BQ-200F2-260V	L445*W392*H57	20	
MS-FL13672 00	120-277V~, 50/60Hz, 200W, IP66, ta50°C				
MS-FL13682 50	120-277V~, 50/60Hz, 250W, IP66, ta50°C	BQ-250F2-260-V	L497*W392*H59	20	
MS-FL13693 00	120-277V~, 50/60Hz, 300W, IP66, ta50°C	BQ-150F2-260-V x 2pcs	L524*W545*H65	25	
MS-FL13693 50	120-277V~, 50/60Hz, 350W, IP66, ta50°C	BQ-200F2-260-V x 2pcs			
MS-FL13704 00	200-277V~, 50/60Hz, 400W, IP66, ta50°C				

