



WhatsApp



WeChat



Official Website

Add: No.19, Nanyang 9th Rd, Taizhou Bay Eco & Tech
Development Area, Taizhou, Zhejiang, China

ELECTRIC MOTORCYCLE



lvjiaev.com

Leading Professional EV Manufacturer

Dedication • Expertise • Future

+86 151 6761 0369



WHO WE ARE

—The China leading manufacturer & exporter of 2/3/4 WHEELER EV SHOCK ABSORBER & HUB MOTOR since 1999



WHY CHOOSE US

- 26-year manufacturing and service experience for global markets
- 2,500 employees including 35 senior engineers, 166 technicians more than 200 administrators
- Overseas warehouses are more convenient and swift for local customers
- Quick response, good production capacity and flexible delivery ability
- ODM/OEM available, design & produce according to customer's requirements
- Passed ISO9001/CE/E-mark/CCC certificate

PROFESSIONAL MANUFACTURER

ONE STOP FOR ALL
YOUR NEEDS.

**YOUR ULTIMATE
E-BIKE PARTS HUB**

ELECTRIC BIKE



MOTOR

Through wind and rain, experience
power that flows effortlessly.
Expertly crafted to be your reliable
companion, ensuring graceful
mobility from dawn to dusk.



SHOCK ABSORBERS



JIYAO-m

Drive at Full Throttle, Make a Grand Entrance

Size : 1930×715×1155mm	Controller : 12-Tube
Battery : 72V32Ah	Brake (F/R) : Disc Brakes
Motor : 1500W	Tire (F/R) : 90-60-12/100-80-12
Max speed : 60km/h	Range : 80km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 11°	Net Weight : 145kg
Shock Absorbers (F/R): Hydraulic	



YUFENG

Ride the wind, a step ahead of the rest.

...



Size : 2030×600×1130mm	Controller : 18-Tube
Battery : 72V32Ah	Brake (F/R) : Disc Brakes
Motor : 3000W	Tire (F/R) : 90-90-14/100-80-14
Max speed : 90km/h	Range : 60km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 21°	Net Weight : 88.1kg
Shock Absorbers (F/R): Hydraulic	

FEITUO0008

Race Your Life, Expand Your World.

...



Size : 2100×640×1130mm	Controller : 18-Tube
Battery : 72v70Ah(Lithium)	Brake (F/R) : Disc Brakes
Motor : 3000W	Tire (F/R) : 90-90-14/100-80-14
Max speed : 90km/h	Range : 170km(45km/h)
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 21°	Net Weight : 88.6kg
Shock Absorbers (F/R): Hydraulic	

FEITUO0007

Your Trusted Mate for a Smooth Ride.

...



Size : 1960×620×1130mm	Controller : 18-Tube
Battery : 72v70Ah(Lithium)	Brake (F/R) : Disc Brakes
Motor : 3000W	Tire (F/R) : 90-90-14/100-80-14
Max speed : 90km/h	Range : 170km(45km/h)
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 21°	Net Weight : 85kg
Shock Absorbers (F/R): Hydraulic	

GUANGCHI

Ride the Light, Glide Through the City.



Size : 2030×620×1150mm	Controller : 18-Tube
Battery : 72V80Ah	Brake (F/R) : Disc Brakes
Motor : 3000W	Tire (F/R) : 110-70-12/130-70-12
Max speed : 80km/h	Range : 180km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 21°	Net Weight : 105kg
Shock Absorbers (F/R): Hydraulic	

TESILA

Electric Surge, Future's Drive.



Size : 1780×750×1150mm	Controller : 12-Tube
Battery : 60V20Ah	Brake (F/R) : Disc/Drum Brake
Motor : 1200W	Tire (F/R) : 90-90-10
Max speed : 45km/h	Range : 50km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 10°	Net Weight : 120kg
Shock Absorbers (F/R): Hydraulic	

MILAN

Silent Journeys, with Wind and Poetry.



Size : 1800×710×1200mm	Controller : 12-Tube
Battery : 72V32Ah	Brake (F/R) : Disc/Drum Brake
Motor : 1200W	Tire (F/R) : 90-90-12
Max speed : 60km/h	Range : 80-100km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 10°	Net Weight : 120kg
Shock Absorbers (F/R): Hydraulic	

Q MENG-O

City Moe Master's Sweet Street Debut

Size : 1630*710*1030mm

Controller : 12-Tube

Battery : 72V20Ah

Brake (F/R) : Disc/Drum Brake

Motor : 800W

Tire (F/R) : 3.00-10

Max speed : 45km/h

Range : 70km

Load Capacity : 150kg

Charging Time : 4-6h

Gradeability : 7°

Net Weight : 110kg

Shock Absorbers (F/R): Hydraulic



YUNDUO-M

Urban Mobility, Aesthetic Vehicle.

Size : 1735*715*1060mm

Battery : 72V20Ah

Motor : 800W

Controller : 12-Tube

Max speed : 45km/h

Range : 70km

Brake (F/R) : Disc/Drum Brake

Tire (F/R) : 3.0-10

Load Capacity : 150kg

Charging Time : 4-6h

Gradeability : 7°

Net Weight : 92kg

Shock Absorbers (F/R): Hydraulic



CAIHONG-M

Ride in Color, Full of Fun.

Size : 1610×710×1150mm

Battery : 72V20Ah

Motor : 800W

Controller : ZWK072030A

Max speed : 45km/h

Range : 60km

Brake (F/R) : Disc/Drum Brake

Tire (F/R) : 3.0-8/3.0-10

Load Capacity : 150kg

Charging Time : 4-6h

Gradeability : 7°

Net Weight : 60kg

Shock Absorbers (F/R): Spring Hydraulic



XINGJI-M

Stellar Wit , Untamed Trailblazer.

Size : 1790×745×1125mm	Controller : ZWK072032A
Battery : 72V20Ah	Brake (F/R) : Disc/Drum Brake
Motor : 1000W	Tire (F/R) : 3.0-10
Max speed : 55km/h	Range : 50km
Load Capacity : 150kg	Charging Time : 6-8h
Gradeability : 9°	Net Weight : 80kg
Shock Absorbers (F/R): Spring Hydraulic	



TANTU-M

Smooth as a Plain, the Journey Never Ends

Size : 1805×750×1065mm
Battery : 72V20Ah
Motor : 1000W
Controller : ZWK072030A
Max speed : 56km/h
Range : 50km
Brake (F/R) : Disc/Drum Brake
Tire (F/R) : 3.0-10
Load Capacity : 150kg
Charging Time : 6-8h
Gradeability : 9°
Net Weight : 70kg
Shock Absorbers (F/R): Spring Hydraulic



J39-M

Instant Thrill. Electrifying Drive.

Size : 1820*690*1180mm
Battery : 72V32Ah
Motor : 1500W
Controller : 12-Tube
Max speed : 65km/h
Range : 80km
Brake (F/R) : Disc Brakes
Tire (F/R) : 90-90-12/110-70-12
Load Capacity : 150kg
Charging Time : 4-6h
Gradeability : 15°
Net Weight : 128kg
Shock Absorbers (F/R): Hydraulic



ZT137

Simple Style,Your Everyday.

...



Size : 1695*720*1060mm	Controller : 12-Tube
Battery : 60V20Ah	Brake (F/R) : Disc Brakes
Motor : 1000W	Tire (F/R) : 12"
Max speed : 45km/h	Range : 60km
Load Capacity : 150kg	Charging Time : 4-6h
Gradeability : 9°	Net Weight : 55.4kg
Shock Absorbers (F/R): Hydraulic	

SHARING

Start rolling, and join the green pulse of the city.

...



Max speed : 25km/h	Range : 60-80km
Battery : 60V24Ah Lithium	Brake (F/R) : Drum Brakes
Load Capacity : 100kg	

ENERGY+ H1

Ride Simple,Live Light.

...



Size : 1415×600×1035mm	Controller : 18-MOSFET
Battery : 48V12Ah	Brake (F/R) : Drum Brakes
Motor : 300W	Tire (F/R) : 60-90-10
Max speed : 25km/h	Range : 50-55km
Load Capacity : 150kg	Charging Time : 4h
Gradeability : 10°	Net Weight : 60kg
Shock Absorbers (F/R): Hydraulic	

ZHANSHEN1.6

Tough Roads.,Tougher Ride.

...



Size : 3065X1180X1410mm

Battery : Lead-Acid/Lithium-Ion

Motor : 1500W

Max speed : 51km/h

Load Capacity : 375kg

Shock Absorbers (F/R): 37/43 Externally Sprung

Controller : 30-MOSFET

Brake (F/R) : Drum Brakes

Tire (F/R) : 3.75/400-12

Gradeability : 25°

Charging Time : 4-6h

TUKTUK

Be the center of the moving scene.

...



Size : 3000*1250*1800mm

Battery : Lead-Acid/Lithium-Ion

Motor : 2000W

Max speed : 50km/h

Load Capacity : 600kg

Gradeability : 25°

Controller : 36G

Brake (F/R) : Drum Brakes

Tire (F/R) : 375-12/400-12

Net Weight : 320kg

Charging Time : 4-6h

Shock Absorbers (F/R): Externally Sprung



INVERSION 910

Center distance (mm) :	910
Mounting diameter :	φ54-φ60
Fork tube diameter :	φ48
Shaft bore diameter :	φ20.1
Itinerary (mm) :	244
Restore damping :	23Gears
Compression damping :	15Gears



M3 FRONT SHOCK

Center distance (mm) :	660
Fork tube diameter :	φ31
Shaft bore diameter :	φ12.1
Itinerary (mm) :	103.5
Damping force :	120±30N 0.3m/S



E300 LP265

Length :	265
Hole mounting dimensions :	2-φ10.1
Mounting hole width :	21-21.1-33
Restore damping :	400
Compression damping :	200



XIYAN 725A

Center distance (mm) :	725
Mounting diameter :	φ52-φ54
Fork tube diameter :	φ41
Shaft bore diameter :	φ15
Itinerary (mm) :	115



M3 REAR SHOCK

Length :	245
Hole mounting dimensions :	2-φ10
Mounting hole width :	2--25



XIYAN310

Length :	310
Hole mounting dimensions :	2-φ10
Mounting hole width :	2--25



BAODIAO 670

Center distance (mm) :	670
Mounting diameter :	φ50-φ54
Fork tube diameter :	φ37
Shaft bore diameter :	φ15
Itinerary (mm) :	100



ST-2 150 ADJUSTABLE

Length :	150
Hole mounting dimensions :	2-φ10
Mounting hole width :	2--24
Restore damping :	14Gears

10"215 ELECTRIC BICYCLE MOTOR

Working voltage(V) :	48
Rated power(W) :	500
Stacking height(mm) :	24
Peak power(W)	1000-1100
No-load-speed(Rpm) :	540
Peak torque(N.m) :	50-75
Peak efficiency(%) :	88%-93%
Protection level(IP) :	67
Insulation level :	B
Sensor type :	Hall
Brake type :	Disc/Drum



10"223 HIGH POWER MOTOR

Working voltage(V) :	48-96
Rated power(W) :	400-2000
Stacking height(mm) :	25-50
Peak power(W)	1100-8000
No-load-speed(Rpm) :	400-1000
Peak torque(N.m) :	80-230
Peak efficiency(%) :	88-93
Protection level(IP) :	67
Insulation level :	B
Sensor type :	Hall
Brake type :	Disc brake



10"215 ELECTRIC MOTORCYCLE MOTOR

Working voltage(V) :	60
Rated power(W) :	1100
Stacking height(mm) :	30
Peak power(W)	1600-1700
No-load-speed(Rpm) :	640
Peak torque(N.m) :	90-110
Peak efficiency(%) :	88-93
Protection level(IP) :	67
Insulation level :	B
Sensor type :	Hall
Brake type :	Disc/Drum

