Professional to build foreign trade export products

(Optional for multiples languages)

Professional OEM/ODM manufacture
With ISO9001 quality management system certification

GB/T 19001-2016/IS0 9001:2015

Huarui brand
CCTV exhibition brand

New model, Best seller

H30
Israel 360 degree automatic special mortise



452MM×76MM×60MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H32
Deadbolt lock pro max (dual mortise)



268.4MM×71.4MM×74.5MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H34
US standard lock



140MM×72MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H27
High partition glass door smart lock



151.4MM×634MM×72.5MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H29
Ecological magnetic lock



162.1MM×36.3MM×54MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H34
Face recognition automatic slim aluminum lock



375MM×414MM×215MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H30
Face recognition door lock



452MM×76MM×60MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H20
Face recognition door lock



429MM×69MM×53MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H10
Face recognition door lock



408MM×80MM×60MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

H8
Face recognition door lock



408MM×80MM×60MM

Technical parameters

Power supply	Lithium battery
unlock ways	Fingerprint, card, password, Wechat mini program (Optional with Cateye, APP, RF remote)
Material	Aluminium alloy
Fingerprint capacity	<=100
Card capacity	<=100
Password capacity	<=100
RF remote capacity	<=30
Resolution	500DPI
False rejection rate	≤0.15%
False recognition rate	≤0.00004%
Work Temperature	-10℃ ~ 60℃
Related Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

Automatic slim aluminum door lock(push & pull style)
Intelligent lock



357MM×41MM×55MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

Semi-auto slim aluminum door lock
Intelligent lock



357MM×41MM×58MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃ ~ 60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-16

Automatic indoor lock



Electronic mortise

260MM×60MM×35MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-17

Automatic indoor lock



Electronic mortise

260MM×60MM×35MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-12
HR-12P

Entrance door lock



370MM×73MM×72MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-26

Entrance door lock



287MM×70MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-09

Room door lock



186MM×68MM×71MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-25

Room door lock



210MM×68MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-06

Room door lock



280MM×63MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-07

Room door lock



280MM×63MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-01

Room door lock



240MM×60MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-02

Room door lock



260MM×62MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-03

Integrated room door lock(mortise fixed on the rear panel)



260MM×62MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-04

Room door lock



240MM×60MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

HR-05

Room door lock



240MM×60MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

Muxing #2

Room door lock



260MM×62MM×75MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

Export

Luxury apartment gate lock



165MM×60MM×28MM
230MM×60MM×50MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

US standard

Deadbolt lock



139MM×58MM×18MM
155MM×68MM×50MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
Mechanical Key
IC card
Dynamic Password
USB Emegency Power supply

TT lock

Fingerprint access control



150MM×80MM×22MM

Technical parameters

Working Voltage	powered by 12vdc electric
Unlock ways	Fingerprint, Card, Pincode, (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Fingerprint
Password
Optional: RF Remote/APP
IC card
Dynamic Password

Export

Face fingerprint access control



150MM×80MM×22MM

Technical parameters

Working Voltage	powered by 12vdc electric
Unlock ways	Fingerprint, Card, Pincode, (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃~60℃
Humidity	20% ~ 93%

Unlock ways

Face recognition
Fingerprint
Password
Optional: RF Remote/APP
IC card
Dynamic Password

HR-24

Handle level lock



155MM×62MM×65MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃～60℃
Humidity	20% ～ 93%

Unlock ways

Fingerprint · Password · Optional: RF Remote/APP · Mechanical Key · IC card · Dynamic Password · USB Emegency Power supply

HR-28

Room door lock



77MM×82MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃～60℃
Humidity	20% ～ 93%

Unlock ways

Fingerprint · Password · Optional: RF Remote/APP · Mechanical Key · IC card · Dynamic Password · USB Emegency Power supply

4#

Ip65 Waterproof version gate lock



168MM×68MM×45MM
130MM×100MM×40MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃～60℃
Humidity	20% ～ 93%

Unlock ways

Fingerprint · Password · Optional: RF Remote/APP · Mechanical Key · IC card · Dynamic Password · USB Emegency Power supply

1#

Normal version gate lock



168MM×68MM×45MM
130MM×100MM×40MM

Technical parameters

Working Voltage	4X AA 5# alkaline batteries(Not include)
Unlock ways	Fingerprint, Card, Pincode, Key (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃～60℃
Humidity	20% ～ 93%

Unlock ways

Fingerprint · Password · Optional: RF Remote/APP · Mechanical Key · IC card · Dynamic Password · USB Emegency Power supply

TT lock

Fingerprint access control



165MM×60MM×28MM

Technical parameters

Working Voltage	powered by 12vdc electric
Unlock ways	Fingerprint, Card, Pincode, (Optional for App or Remote control)
Fingerprint Capacity	<=100
Card Capacity	<=100
Password Capacity	<=100
Remote control capacity	<=120
Resolution	500DPI
FRR (False Reject Rate)	≤0.15%
FAR (False Accept Rate)	≤0.00004%
Working Temperature	-10℃～60℃
Humidity	20% ～ 93%

Unlock ways

Fingerprint · Password · Optional: RF Remote/APP · IC card · Dynamic Password

Other series

RFID Lock

130MM×100MM×40MM

Motored lock

130MM×100MM×40MM

Infrared sensors



Power supply case

250MM×165MM×72MM

Door closer

Magnetic lock

doorbell

Power supply