



## Zhongshan Anxing Locks Manufacturer Catalogue

<http://www.zsanxing.com>

### Electric Rim Lock Series(Domestic)

| PIC                                                                                 | PARAMETER                                                                                                                                                       | PIC                                                                                 | PARAMETER                                                                                                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Model Item: AX001<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |    | Model Item: AX002<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|    | Model Item: AX003<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |    | Model Item: AX005<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|   | Model Item: AX006<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |   | Model Item: AX007<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|  | Model Item: AX008<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX009<br>Lock Size : 125.5×101×39 mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |

### Electro Magnetic Lock Series

| PIC                                                                                 | PARAMETER                                                                                                                                                                       | PIC                                                                                 | PARAMETER                                                                                                                                                                     |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX60KG<br>Lock Size : 80×38×25 mm<br>Holding force: 60kg<br>Working voltage: 12V DC<br>Working current: 130mA<br>Fail safe                                          |  | Model Item: AX180KGA<br>Lock Size : 184×30.5×22.5 mm<br>Holding force: 180kg<br>Working voltage: 12V DC<br>Working current: 360mA<br>Fail safe                                |
|  | Model Item: AX180KGB<br>Lock Size : 170×40×21 mm<br>Holding force: 180kg<br>Working voltage: 12V DC<br>Working current: 360mA<br>Fail safe                                      |  | Model Item: AX180KGC<br>Lock Size : 210×40×21 mm<br>Holding force: 180kg<br>Working voltage: 12/24V DC<br>Working current: 360/180mA<br>Fail safe,with LED                    |
|  | Model Item: AX180KGCT<br>Lock Size : 210×40×21 mm<br>Holding force: 180kg<br>Working voltage: 12/24V DC<br>Working current: 310/170mA<br>Fail safe,with LED,Time-delay Function |  | Model Item: AX180KGD<br>Lock Size : 210×40×21 mm<br>Holding force: 180kg<br>Working voltage: 12/24V DC<br>Working current: 310/170mA<br>Fail safe,with LED,NO/NC/COM Function |

|                                                                                     |                                                                                                                                                                                  |                                                                                      |                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Model Item: AX180KGE<br>Lock Size : 340×40×21 mm<br>Holding force: 360kg<br>Working voltage: 12V DC<br>Working current: 400mA<br>Fail safe                                       |    | Model Item: AX230KGA<br>Lock Size : 224×40×25 mm<br>Holding force: 230kg<br>Working voltage: 12V DC<br>Working current: 330mA<br>Fail safe                                       |
|    | Model Item: AX230KGB<br>Lock Size : 250×47×25 mm<br>Holding force: 230kg<br>Working voltage: 12/24 VDC<br>Working current: 330/165mA<br>Fail safe,with LED                       |     | Model Item: AX230KGC<br>Lock Size : 250×47×25 mm<br>Holding force: 230kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe,with LED ,Time-delay Function  |
|    | Model Item: AX230KGD<br>Lock Size : 250×47×25 mm<br>Holding force: 230kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe,with LED ,NO/NC/COM Function   |    | Model Item: AX230KGE<br>Lock Size : 500×47×25 mm<br>Holding force: 460kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe,with LED                       |
|    | Model Item: AX230KGE-C<br>Lock Size : 500×47×25 mm<br>Holding force: 460kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe,with LED,Time-delay Function |    | Model Item: AX230KGE-D<br>Lock Size : 500×47×25 mm<br>Holding force: 460kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe,with LED,NO/NC/COM Function  |
|  | Model Item: AX280KGA<br>Lock Size : 257×50×27 mm<br>Holding force: 280kg<br>Working voltage: 12 VDC<br>Working current: 400mA<br>Fail safe                                       |    | Model Item: AX280KGB<br>Lock Size : 250×50×27 mm<br>Holding force: 280kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe.With LED                       |
|  | Model Item: AX280KGC<br>Lock Size : 250×53×27 mm<br>Holding force: 280kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe.With LED,Time-delay Function   |   | Model Item: AX280KGD<br>Lock Size : 250×53×27 mm<br>Holding force: 280kg<br>Working voltage: 12/24 VDC<br>Working current: 400/200mA<br>Fail safe.With LED,NO/NC/COM Function    |
|  | Model Item: AX280KGE<br>Lock Size : 500×53×27 mm<br>Holding force: 560kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe,with LED                       |  | Model Item: AX280KGE-C<br>Lock Size : 500×53×27 mm<br>Holding force: 560kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe,with LED,Time-delay Function |
|  | Model Item: AX280KGE-D<br>Lock Size : 500×53×27 mm<br>Holding force: 560kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe,with LED,NO/NC/COM Function  |  | Model Item: AX350KGA<br>Lock Size : 255×56×32 mm<br>Holding force: 350kg<br>Working voltage: 12V DC<br>Working current: 400mA<br>Fail safe                                       |
|  | Model Item: AX350KGB<br>Lock Size : 250×64×32 mm<br>Holding force: 350kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED                       |   | Model Item: AX350KGC<br>Lock Size : 250×64×32 mm<br>Holding force: 350kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED,Time-delay Function   |
|  | Model Item: AX350KGD<br>Lock Size : 250×64×32 mm<br>Holding force: 350kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED, NO/NC/COM Function   |  | Model Item: AX500KGB<br>Lock Size : 265×73×39 mm<br>Holding force: 500kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED                       |

|                                                                                   |                                                                                                                                                                                 |                                                                                   |                                                                                                                                                                               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX500KGC<br>Lock Size : 265×73×39 mm<br>Holding force: 500kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED, Time-delay Function |  | Model Item: AX500KGD<br>Lock Size : 265×73×39 mm<br>Holding force: 500kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED,NO/NC/COM Function |
|  | Model Item: AX500KGE<br>Lock Size : 530×73×39 mm<br>Holding force: 1200kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Fail safe.With LED                     |                                                                                   |                                                                                                                                                                               |

### Waterproof Electro Magnetic Lock Series

| PIC                                                                               | PARAMETER                                                                                                                                                                                               | PIC                                                                               | PARAMETER                                                                                                                                                                                               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX280KGS<br>Lock Size : 220×48×23 mm<br>Holding force: 280kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Shell material: Stainless Steel<br>Fail safe.NO/NC/COM Function |  | Model Item: AX500KGS<br>Lock Size : 222×60×42 mm<br>Holding force: 500kg<br>Working voltage: 12/24V DC<br>Working current: 400/200mA<br>Shell material: Stainless Steel<br>Fail safe.NO/NC/COM Function |

### Shear Lock

|                                                                                     |                                                                                                                                                                                                                                                                                                          |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX1200KG<br>Lock body Size : 182×30×25 mm<br>Armature Plate size: 182x30x23.6mm<br>Holding force: 2400lbs<br>Working voltage: 12/24V DC<br>Working current: 12Vdc: pull in:900mA, holding:220mA<br>24Vdc: pull in:900mA, holding:190m<br>Fail safe.With LED, Time-delay & NO/NC/COM Function |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Accessories & Bracket Series for Electro Magnetic Lock

| PIC                                                                                              | PARAMETER                                                                                                                                    | PIC                                                                                              | PARAMETER                                                                                                                                        |
|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
|               | ROLLING CONTROL BOX<br>Model Item: AX020<br>Lock Size:120x86x35mm<br>Working voltage:12V DC<br>Working current:350mA<br>Fail safe,Time-delay |               | PUSH BUTTON CONTROL BOX<br>Model Item: AX021<br>Lock Size:120x86x35mm<br>Working voltage:12V DC<br>Working current:350mA<br>Fail safe,Time-delay |
| <br>U BRACKET | Model Item: AX60PU<br>Size : 70×36×28 mm<br>Suitable for: 60KG magnetic lock<br>Glass door thickness:less than 15mm                          | <br>U BRACKET | Model Item: AX180PU<br>Size : 130×46×28 mm<br>Suitable for: 180KG magnetic lock<br>Glass door thickness: Less than 15mm                          |
| <br>L BRACKET | Model Item: AX180PL<br>Size : 170×38 mm<br>Suitable for: 180KGB magnetic lock                                                                | <br>L BRACKET | Model Item: AX180PL1<br>Size : 210×38 mm<br>Suitable for: 180KG C&D magnetic lock                                                                |

|                                                                                                       |                                                                                                                         |                                                                                                       |                                                                                                                                 |
|-------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <br>Z BRACKET        | Model Item: AX180PZ<br>Size : 130×37 mm<br>Suitable for: 180KG magnetic lock                                            | <br>U BRACKET        | Model Item: AX230/280PU<br>Size : 180×45×28 mm<br>Suitable for: 230/280KG magnetic lock<br>Glass door thickness: Less than 15mm |
| <br>L BRACKET        | Model Item: AX230/280PL<br>Size : 250×47 mm<br>Suitable for: 230/280KG magnetic lock                                    | <br>Z BRACKET        | Model Item: AX230/280PZ<br>Size : 180×53mm<br>Suitable for: 230/280KG magnetic lock                                             |
|                      | Model Item: AX350PU<br>Size : 158×58×38 mm<br>Suitable for: 350KG magnetic lock<br>Glass door thickness: Less than 20mm |                      | Model Item: AX350PL<br>Size : 250×62 mm<br>Suitable for: 350KG magnetic lock                                                    |
|                      | Model Item: AX350PZ<br>Size : 180×50 mm<br>Suitable for: 350KG magnetic lock                                            | <br>U BRACKET        | Model Item: AX500PU<br>Size : 185×70×39 mm<br>Suitable for: 500KG magnetic lock<br>Glass door thickness: Less than 20mm         |
| <br>L BRACKET        | Model Item: AX500PL<br>Size : 267×76 mm<br>Suitable for: 500KG magnetic lock                                            | <br>Z BRACKET        | Model Item: AX500PZ<br>Size : 185×60 mm<br>Suitable for: 500KG magnetic lock                                                    |
| <br>SPECIAL BRACKET | Model Item: AX280P<br>Suitable for: 230/280KG magnetic lock                                                             | <br>SPECIAL BRACKET | Model Item: AX500P<br>Suitable for: 500KG magnetic lock                                                                         |
|                    | Model Item: AX280SPL<br>Size : 220×52 mm<br>Suitable for: AX280KGS magnetic lock                                        |                    | Model Item: AX500SPL<br>Size : 222×68 mm<br>Suitable for: AX500KGS magnetic lock                                                |

### Silence Lock Series

| PIC                                                                                 | PARAMETER                                                                                                                                                    | PIC                                                                                 | PARAMETER                                                                                                                                                    |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX130<br>Lock Size : 126×105×41mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX131<br>Lock Size : 126×105×41mm<br>Working Voltage : 12V DC<br>Working Current : 3.5A<br>Power to unlock<br>Guarantee: More than 200,000 times |

### Intelligent Lock Series (Steel)

| PIC                                                                                 | PARAMETER                                                                                                                                                  | PIC                                                                                 | PARAMETER                                                                                                                                                  |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX060<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times |  | Model Item: AX061<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times |

|                                                                                   |                                                                                                                                                                                                                             |                                                                                   |                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX061A<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED,Green button to open<br>Guarantee: More than 200,000 times                                            |  | Model Item: AX062<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times<br>Feature:One cylinder,can Reading card from outside to open    |
|  | Model Item: AX063<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times<br>Feature:Single cylinder,can Reading card on both side to open |  | Model Item: AX066<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times<br>Feature:Double cylinder,can Reading card on both side to open |

### Intelligent Lock Series (Stainless Steel)

| PIC                                                                                 | PARAMETER                                                                                                                                                                                                                   | PIC                                                                               | PARAMETER                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Model Item: AX067<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED,Single cylinder<br>Guarantee: More than 200,000 times                                                  |  | Model Item: AX068<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED,Double cylinder<br>Guarantee: More than 200,000 times |
|  | Model Item: AX069<br>Lock Size : 130×98×41mm<br>Working Voltage : 12V DC<br>Working Current : Over 100mA<br>With LED<br>Guarantee: More than 200,000 times<br>Feature:Double cylinder,can Reading card on both side to open |                                                                                   |                                                                                                                                                                            |

### Stainless Steel Lock Series

| PIC                                                                                 | PARAMETER                                                                                                                                                       | PIC                                                                                 | PARAMETER                                                                                                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX090<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX091<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|  | Model Item: AX092<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX093<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|  | Model Item: AX096<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX097<br>Lock Size : 125×98×36 mm<br>Working Voltage : 12V DC<br>Working Current : Over 2A<br>Power to unlock<br>Guarantee: More than 200,000 times |

|                                                                                   |                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>Model Item: AX098<br/> Lock Size : 125×98×36 mm<br/> Working Voltage : 12V DC<br/> Working Current : Over 2A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p> |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Exporting Electric Rim Lock(C Series)

| PIC                                                                                 | PARAMETER                                                                                                                                                                         | PIC                                                                                  | PARAMETER                                                                                                                                                                                                                        |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <p>Model Item: AX030<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>      |    | <p>Model Item: AX031<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                     |
|    | <p>Model Item: AX032<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>      |    | <p>Model Item: AX033<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                     |
|   | <p>Model Item: AX034<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>      |   | <p>Model Item: AX034<br/> Lock Size : 148×107×35 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                     |
|  | <p>Model Item: AX037<br/> Lock Size : 125×98×36 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>       |  | <p>Model Item: AX038<br/> Lock Size : 125×98×36 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                      |
|  | <p>Model Item: AX039<br/> Lock Size : 125×98×36 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>       |  | <p>Model Item: AX040<br/> Lock Size : 126×101×39 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times<br/> Function: With extra security bar, more safety</p> |
|  | <p>Model Item: AX041<br/> Lock Size : 126×101×39 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>      |  | <p>Model Item: AX042<br/> Lock Size : 126×101×39 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                     |
|  | <p>Model Item: AX043<br/> Lock Size : 126×101×39 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>      |  | <p>Model Item: AX044<br/> Lock Size : 126×101×39 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                     |
|  | <p>Model Item: AX045 (YL)<br/> Lock Size : 140×116×55 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p> |  | <p>Model Item: AX046 (AB)<br/> Lock Size : 140×116×55 mm<br/> Working Voltage : 12V DC<br/> Working Current : 3A<br/> Power to unlock<br/> Guarantee: More than 200,000 times</p>                                                |

|                                                                                   |                                                                                                                                                                    |                                                                                    |                                                                                                                                                                    |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX047 (SN)<br>Lock Size : 140×116×55 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times   |   | Model Item: AX048 (SNGP)<br>Lock Size : 140×116×55 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times |
|  | Model Item: AX049 (SBNB)<br>Lock Size : 140×116×55 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times |  | Model Item: AX050<br>Lock Size : 120×66×35 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times         |
|  | Model Item: AX052<br>Lock Size : 126×101×35 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times        |   | Model Item: AX053<br>Lock Size : 126×101×35 mm<br>Working Voltage : 12V DC<br>Working Current : 3A<br>Power to unlock<br>Guarantee: More than 200,000 times        |

### Electric Dropbolt Series

| PIC                                                                                 | PARAMETER                                                                                                                                                                                                                                                  | PIC                                                                                  | PARAMETER                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Model Item: AX070<br>Lock Size : 205×35×42 mm<br>Working voltage: 12V DC<br>Current: Standby 400mA / Working 410mA<br>Feature: Standard<br>Power to lock                                                                                                   |  | Model Item: AX071<br>Lock Size : 205×35×42 mm<br>Working voltage: 12V DC<br>Current: Standby 100mA/Working 900mA<br>Feature: Low or normal temperature<br>Power to lock                                                                                    |
|  | Model Item: AX072<br>Lock Size : 205×35×42 mm<br>Working voltage: 12V DC<br>Current: Standby 100mA / Working 900mA<br>Function: Time-delay<br>Feature: Low temperature or normal temperature<br>Power to lock                                              |   | Model Item: AX073<br>Lock Size : 148×43×39mm<br>Working voltage: 12V DC<br>Function: Time-delay & Feedback signal<br>Feature: Using with frameless glass doors and glass wall<br>Power to lock                                                             |
|  | Model Item: AX074<br>Lock Size : 205×35×42 mm<br>Working voltage: 12V DC<br>Current: Standby 100mA / Working 900mA<br>Function: Time-delay & Feedback signal<br>Feature: Low temperature or normal temperature<br>Power to lock                            |  | Model Item: AX075<br>Lock Size : 235×35×42 mm<br>Working voltage: 12V DC<br>Current: Standby 100mA / Working 900mA<br>Feature: Standard & Time-delay & Feedback signal (optional)<br>Power to lock                                                         |
|  | Model Item: AX076A AX076B<br>Lock Size : 192×25×37 mm<br>Working voltage: 12V DC<br>Current: Standby 1000mA / Working 150mA<br>Function: Time-delay & Feedback signal<br>Feature: Low temperature or normal temperature<br>Power to lock/unlock (optional) |  | Model Item: AX077A AX077B<br>Lock Size : 205×30×38 mm<br>Working voltage: 12V DC<br>Current: Standby 1000mA / Working 150mA<br>Function: Time-delay & Feedback signal<br>Feature: Low temperature or normal temperature<br>Power to lock/unlock (optional) |

|                                                                                   |                                                                                                                                                                                                                                                  |                                                                                   |                                                                                                         |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
|  | Model Item: AX079<br>Lock Size : 268×30×48 mm<br>Working voltage: 12V DC<br>Current: Standby 1000mA /Working 150mA<br>Function: Time-delay & Feedback signal<br>Feature:Low temperature or normal temperature<br>Power to lock/unlock (optional) |                                                                                   |                                                                                                         |
|  | U bracket-1 for electric dorpbolt series<br>Size : 65×45×25 mm<br>Glass door thickness: Less than 15mm                                                                                                                                           |  | U bracket-2 for electric dorpbolt series<br>Size : 148×43×39 mm<br>Glass door thickness: Less than 15mm |

### Electric Strike Series

| PIC                                                                                 | PARAMETER                                                                                                                                                                           | PIC                                                                                  | PARAMETER                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Model Item:AX080<br>Lock Size: 250x25x31mm<br>Voltage: 12V DC<br>Current: 700mA<br>Function:NO/NC<br>Power to lock/unlock (optional)                                                |     | Model Item:AX081<br>Lock Size: 110x25x31mm<br>Voltage: 12V DC<br>Current: 700mA<br>Function:NO/NC<br>Power to lock/unlock (optional)                                                        |
|  | Model Item:AX082<br>Lock Size: 149x28x31mm<br>Voltage: 12V DC<br>Current: 400mA<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional)                             |  | Model Item:AX082A AX082B<br>Lock Size: 149x28x31mm<br>Voltage: 12V DC<br>Current: 400mA<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional)                             |
|  | Model Item:AX083<br>Lock Size: 149x39x34mm<br>Voltage: 12V DC<br>Current: 400mA<br>Function:Feedback signal<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional) |  | Model Item:AX083A AX083B<br>Lock Size: 149x39x34mm<br>Voltage: 12V DC<br>Current: 400mA<br>Function:Feedback signal<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional) |
|  | Model Item:AX086<br>Lock Size: 149x39x34mm<br>Voltage: 12V DC<br>Current: 400mA<br>Function:Feedback signal<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional) |   | Model Item:AX087<br>Lock Size: 149x39x34mm<br>Voltage: 12V DC<br>Current: 400mA<br>Function:Feedback signal<br>Strike Width:30mm/45mm (optional)<br>Power to lock/unlock (optional)         |

### Access Control Series

| PIC                                                                                 | PARAMETER                                                                 | PIC                                                                                 | PARAMETER                                                                       |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
|  | PUSH BUTTON<br>Model Item:AX010<br>Size: 85x85x36 mm<br>Material: Plastic |  | PUSH BUTTON<br>Model Item:AX011<br>Size: 101x30 mm<br>Material: Stainless Steel |

|                                                                                   |                                                                                                                                                                          |                                                                                   |                                                                                                                                                                                                         |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>PUSH BUTTON</p> <p>Model Item:AX012</p> <p>Size: 92x92x28 mm</p> <p>Material: Stainless Steel</p>                                                                     |  | <p>PUSH BUTTON</p> <p>Model Item:AX014</p> <p>Material: zinc alloy</p> <p>Surface treatment: Die-casting zinc alloy</p>                                                                                 |
|  | <p>READER 1</p> <p>Model Item:AX013</p> <p>Size : 85×85×18 mm</p> <p>Current Standby 100MA / working 1000MA</p> <p>Working voltage: 12V DC</p> <p>For 2000 user card</p> |  | <p>READER 2</p> <p>Model Item:AX016</p> <p>Size : 117×117×21 mm</p> <p>Current Standby 100MA / working 1000MA</p> <p>Working voltage: 12V DC</p> <p>For 2000 user card</p> <p>Feature:With password</p> |
|  | <p>Key tag</p> <p>For reader</p>                                                                                                                                         |  | <p>RFID access control card</p> <p>For reader</p>                                                                                                                                                       |

### Power Supply Cabinet Lock & Door Closer

|                                                                                     |                                                                                                                                                           |                                                                                     |                                                                                                                                                                 |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <p>Remote Transformer</p> <p>Model Item:AX161</p> <p>Size:85x85x48mm</p> <p>Input:AC 220V</p> <p>Output: 12V DC</p> <p>Suitable for Electric Rim Lock</p> |    | <p>Power Supply</p> <p>Model Item: AX166</p> <p>Size:130x75x40 mm</p> <p>Input: 220V</p> <p>Output: 12/24V</p> <p>Current: 1.5A/3A/5A</p>                       |
|  | <p>Power Supply</p> <p>Model Item: AX167</p> <p>Size:183x78x60 mm</p> <p>Input: 220V</p> <p>Output: 12/24V</p> <p>Current: 1.5A/3A/5A</p>                 |  | <p>Power Supply with standby battery</p> <p>Model Item: AX168</p> <p>Size:205x165x73 mm</p> <p>Input: 220V</p> <p>Output: 12/24V</p> <p>Current: 1.5A/3A/5A</p> |