

OmniTech



**PROFESSIONAL
CHARGER MANUFACTURER
SINCE 2015**

NEW CATALOG

ABOUT US

Established in 2015, Omnitech is a professional manufacturer of consumer electronics products. Integrating R&D, production, and sales, we provide global customers with a wide range of charging solutions, including travel chargers, wireless chargers, car chargers, and power strips.

Our factories are located in Shenzhen and Yangzhou, with a scale of over 10,000 square meters production base and more than 400 skilled workers.



20

Experienced R&D Engineers

10,000+

Square meters of Factories

1,200,000 PCS

Production Capacity Per Month

OEM/ODM Projects are warmly welcomed.

We have obtained various quality management system and safety certification, including ISO9001, ISO14001, and BSCI, etc.

Relying on the innovative and experienced R&D team, our products have been certified by numerous international standards, such as UL, ETL, CE, CCC, UKCA, CB, SAA, GS, GRS, PSE, KC, and ERP, etc.

TRAVEL CHARGER



OT-TC-037

- GaN 70W Travel Charger (Compatible for Laptop, Phone, Tablet, Switch, etc)
- Retractable USB-C Cable (20,000 times lifetime)
- Smart TFT Screen

OT-TC-037

NEW



Input	110-240V ~ 50/60Hz, 1.7A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20.3V/3.45A (70W Max)
USB-A Output	5V/3A, 9V/3A, 12V/3A, 20V/3A (60W Max)
Combined Outputs	C1 + C2: 45W + 20W C1 + USB-A: 45W + 18W C2 + USB-A: 5V/3A
C1 Cable Length	80 ± 5 cm
Total Output Power	70W Max

OT-TC-036

NEW



Input	100-240V ~ 50/60Hz, 2.5A Max
USB-C1/C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A(100W Max)
USB-C3/C4 Output	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A(30W Max)
Dual QC 3.0 Output	4.5V/5A, 5V/4.5A, 9V/3A, 12V/2.5A, 20V/1.5A(30W Max)
Wireless Output	15W fast charge
Total Output	100W Max
Dimensions	118*85*32m(L × W × H)
Certifications	

OT-TC-035

NEW



Input	100-240V ~ 50/60Hz, 2.1A Max
USB-3.1 C1/C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A (140W)
USB-C3 Output	5V/3A, 9V/3A, 12V/1.67A (20W)
USB-A Output	5V/2.4A, 9V/2A, 12V/1.5A (18W Max)
Total Output Power	140W
Plug Type	US / EU / UK / KC / AU
Dimensions	73*65*30m(L × W × H)
Certifications	

OT-TC-034

Input	100-240V ~ 50/60Hz, 1.5A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W)
USB-C3 Output	5V/3A, 9V/3A, 12V/1.67A (20W)
USB-A Output	5V/2.4A, 9V/2A, 12V/1.5A (18W Max)
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AU
Dimensions	65*65*30m(L × W × H)
Certifications	

OT-TC-032



Input	100-240V ~ 50/60Hz, 1.5A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/2.4A, 9V/2A, 12V/1.5A (18W Max)
Combined Outputs	C1+C2: 45W+20W; C1+USB-A: 45W +18W; C2+USB-A: 5V/2.4A; C1+C2+USB-A: 45W+12W
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	55*55*30mm (L × W × H)
Certifications	

OT-TC-031



Input	100-240V ~ 50/60Hz, 1.7A Max
USB-C1 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A (18W Max)
Combined Outputs	C+USB-A: 5V/3A
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	55*55*30mm (L × W × H)
Certifications	

OT-TC-030



Input	100-240V ~ 50/60Hz, 1.7A Max
USB-C1 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (45W Max)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A (18W Max)
Combined Outputs	C + USB-A: 5V/3A
Total Output Power	45W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	55*55*30mm (L x W x H)
Certifications	

OT-TC-029



Input	100-240V ~ 50/60Hz, 1.7A Max
USB-C1 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A (18W Max)
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	55*55*30mm (L x W x H)
Certifications	

OT-TC-028



Input	100-240V ~ 50/60Hz, 1.7A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/2.4A, 9V/2A, 12V/2.5A, 15V/3A, 20V/1.5A (30W Max)
Combined Outputs	C1+C2: 45W+20W; C1+USB-A: 45W+18W; C2+USB-A: 20W+18W; C1+C2+USB-A: 45W+10W+10W
Total Output Power	65W Max
Plug Type	US / EU / UK
Dimensions	61x 47 x 40mm(L x W x H)
Weight	Approximately 128g
Certifications	

OT-TC-027



Input	100-240V ~ 50/60Hz, 1.7A Max
USB-C1 Output	5V/3A, 9V/3A, 12V/2.9A, 15V/2.33A, 20V/1.75A (65W Max)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A(18W Max)
Combined Outputs	C1 + USB-A: 5V/3A
Total Output Power	35W Max
Plug Type	US / EU / UK
Dimensions	61x 47 x 40mm (L x W x H)
Weight	Approximately 100g
Certifications	

OT-TC-026



Input	100-240V ~ 50/60Hz, 1.2A
USB-C1/C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/2.66A, 20V/2A (40W)
C1+C2 Combined Output	20W+20W
Total Output Power	40W
Plug Type	UK / US / EU
Size	43x 42 x32 mm
Weight	Approximately 63g
Certifications	

OT-TC-025



Input	100-240V ~ 50/60Hz, 1A
USB-C Output	5V/3A, 9V/3A, 12/2.91A, 15V/2.33A, 20V/1.75A (35W)
USB-A Output	5V/3A, 9V/3A, 12/2.91A, 20V/1.5A
A+C Combined Output	5V/3.4A
Total Output Power	35W
Plug Type	UK / US / EU
Size	43x 42 x32 mm
Weight	Approximately 60g
Certifications	

OT-TC-018

NEW



Input	100-240V ~ 50/60Hz, 0.8A
USB-C Output	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
USB-A Output	5V/3A, 9V/2A, 12V/1.5A
A+C Combined Output	5V/3A
Total Output Power	30W
Plug Type	US
Size	65 × 41 × 16 mm
Weight	Approximately 53g
Certifications	

OT-TC-017

NEW



Input	100-240V ~ 50/60Hz, 0.8A
USB-C Output	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
Total Output Power	30W
Plug Type	US
Size	65 × 41 × 16 mm
Weight	50g
Certifications	

OT-TC-012

HOT



Input	110-240V ~ 50/60Hz, 1.7A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/3A, 9V/3A, 12V/3A, 20V/3A (60W Max)
C1 Cable Length	80 ± 5 cm
Total Output Power	65W Max
Plug Type	US / EU / UK
Dimensions	51.5 × 50 × 50 mm (L × W × H)
Weight	Approximately 147g
Certifications	

OT-TC-011

HOT



Input	100-240V ~ 50/60Hz, 1.2A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/2.66A, 20V/2A (40W Max)
USB-A Output	5V/2.4A, 9V/2A, 12V/1.5A (18W Max)
Combined Outputs	C1 + C2: 20W + 12W
C1 Cable Length	80 ± 5 cm
Total Output Power	40W Max
Plug Type	US / EU / UK
Dimensions	71 × 52 × 31.5 mm (L × W × H)
Weight	Approximately 60g
Certifications	

OT-TC-010



Input	100-240V ~ 50/60Hz, 1.5A Max
USB-C1 / C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/2.4A, 9V/2A, 12V/1.5A (18W Max)
Combined Outputs	C1+C2: 45W+20W; C1+USB-A: 45W+18W, C2+USB-A: 5V/2.4A; C1+C2+USB-A: 45W+12W
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	46 × 46 × 28 mm (L × W × H)
Weight	Approximately 94g
Certifications	

OT-TC-009



Input	100-240V ~ 50/60Hz, 1.5A Max
USB-C Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A (18W Max)
Combined Output	45W + 5V/2.4A (USB-C + USB-A)
Total Output Power	65W Max
Plug Type	US / EU / UK / KC / AS
Dimensions	46 × 46 × 28 mm (L × W × H)
Weight	Approximately 92g
Certifications	

65W



CAR CHARGER

OT-CC-012

NEW

Input	DC 12-24V Max
USB-C Output(35W Max)	5V/3A, 9V/3A, 12V/2.92A, 15V/2.33A, 20V/1.75A
USB-C Cable Output(30W Max)	5V/3A, 9V/3A, 12V/2.5A
USB Output	5V/3A, 9V/3A, 10V/2.25A, 12V/2.5A
USB-C Cable+USB-C Combined Output	30W+35W
USB-C Cable+USB Combined Output	30W+30W
USB-C+USB Combined Output	5V/3A
USB-C Cable+USB-C+USB Combined Output	30W+15W
Cable Length	66 cm
Total Output	65W
Material	PC
Product Dimensions	85 x 55 x 45 mm
Weight	63g (±5g)



OT-CC-011



Input	DC 12-24V Max
USB Cable Output(45W Max)	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/2.25A
Cable Length	65 cm
Total Output	45W
Material	PC
Product Dimensions	105 x 49 x 22.5 mm
Weight	63g (±5g)

OT-CC-010

HOT



Input	12-24V
USB Outputs	USB-C1 (100W): 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A; USB-C2 (45W): 5V/3A, 9V/3A, 12V/3A, 15V/3A; USB-A (30W): 5V/3A, 9V/3A, 12V/2.5A
Combined Outputs	C1+C2: 100W+45W; C1+A: 100W+30W; C2+A: 5V/3A(15W); C1+C2+A: 100W+35W+30W
Total Output	65W
Product Dimensions	84.69*42.9*19.75mm (±0.5 mm)
Weight	70g (±5g)
Shell Material	ABS + PC (94V0)

OT-CC-009



Input	12-24V
USB Outputs	USB-C1 (30W): 5V/3A, 9V/3A, 12V/2.5A USB-C2 (30W): 5V/3A, 9V/3A, 12V/2.5A USB-A (30W): 5V/3A, 9V/3A, 12V/2.5A
Combined Outputs	C1+C2: 30W+30W; C1+A: 30W+30W; C1+C2+A: 30W+30W+30W
Total Output	90W
Product Dimensions	80.62 x 74.96 x 34.95 mm (±0.5 mm)
Weight	70g (±5g)
Shell Material	ABS + PC (94V0)

OT-CC-007



Input	DC 12-24V Max
Outputs	Type-C (30W Max): 5V/3A, 9V/2A, 10V/2.25A, 12V/2.5A 5V/3A, 9V/3A
Lightning+Type-C Combined Output	DC 5V/3A
Cable Length	90 cm
Material	PC
Product Dimensions	76.3 x 46 mm
Weight	75g (±5g)

WIRELESS CHARGER



OT-MD-013

NEW

Charging Power	Phone: 15W Max (5W, 7.5W, 10W, 15W) Watch: 2.5W Max; Earphone: 5W Max
Total Charging Power	15W + 2.5W + 5W
LED warm white light	
Input	5V/3A, 9V/3A (QC 3.0, PD)
Product Size	65 x 65 x 81 mm
Weight	292g
Material	ABS
Certifications	CE FC 



OT-MD-012



Charging Power	Phone: 15W Max (5W, 7.5W, 10W, 15W); Watch: 2.5W Max; Earphone: 5W Max
Input	5V/3A, 9V/3A (QC 3.0, PD)
Total Charging Power	15W + 2.5W + 5W
Product Size	105*66*24 mm
Weight	190g
Material	Aluminum + PC + ABS
Certifications	CE FC 

OT-MD-011



Charging Power	Phone: 15W Max (5W, 7.5W, 10W, 15W); Watch: 2.5W Max; Earphone: 5W Max
Input	5V/3A, 9V/3A (QC 3.0, PD)
Total Charging Power	15W + 2.5W + 5W
Product Size	95*65*30 mm
Weight	175g
Material	PC + ABS
Certifications	CE FC 

OT-MD-010



Charging Power	Phone: 15W Max (5W, 7.5W, 10W, 15W); Watch: 2.5W Max; Earphone: 5W Max
Input	5V/3A, 9V/3A (QC 3.0, PD)
Total Charging Power	15W + 2.5W + 5W
Product Size	42.5*26.5*30.5 mm
Weight	149g
Material	Aluminum + ABS
Certifications	CE FC 

OT-MD-009



Charging Power	Phone: 15W Max (5W, 7.5W, 10W, 15W); Watch: 2.5W Max; Earphone: 5W Max
Colorful Lighting Output	1W Max
Input	5V/3A, 9V/2A, 12V/1.5A (QC 3.0, PD)
Total Charging Power	15W + 2.5W + 5W
Product Size	68x 68 x 67 mm
Weight	218g
Material	PC + ABS
Certifications	CE FC 

POWER STRIPS



OT-AC-003 B

NEW

Input	100V-125V, 50/60Hz, 1.5A
Max Power	100V-125VAC, 10A, 1250W
AC Outlets	3 outlets located on separate sides
AC Cable Length	1.5m
USB-C Outputs (C1/C2/C3)	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.35A (67W)
PPS	3V-11V/5A
Total Output	65W
Plug Type	US
Product Size	60*60*45mm
Certifications	



OT-AC-003 A

NEW

Input	100V-125V, 50/60Hz, 1.5A
Max Power	100V-125VAC, 10A, 1250W
AC Outlets	3 outlets located on separate sides
AC Cable Length	1.5m
USB-C Outputs (C1/C2)	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.35A (67W)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A
Total Output	65W
Plug Type	US
Product Size	60 x 60 x 45 mm
Certifications	



OT-AC-004

Product Size	67*41mm(L x W x H)
Weight	Approximately 245g
USB-C Outputs (C1/C2)	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W)
USB-C3 Output	5V/3A, 9V/2.22A, 12V/1.67A(20W)
USB-A Output	5V/3A, 9V/2A, 12V/1.5A(18W)
Total Output	65W
AC Cable Length	1.5m
Plug Type	EU/UK/US



OT-AC-005

Input	100V-125V, 50/60Hz, 1.5A
Max Power	100V-125VAC, 13A, 1650W
AC Outlets	2 outlets located on separate sides
AC Cable Length	1.5m
USB-C Outputs (C1/C2)	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W)
USB-A Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W)
Total Output	65W
Plug Type	US



OT-AC-006

AC Outlets	3 outlets
AC Cable Length	1.5m
USB 3.1-C1 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A (140W)
USB-C2 Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W)
USB-C3/C4 Output	5V/3A, 9V/2.22A, 12V/2.5A, 15V/2A, 20V/1.5A, (30W)
Total Output	240W
Plug Type	EU/UK
Product Size	123*66*34 mm(L x W x H)



POWER BANKS

OT-PBW-019

NEW



Battery Capacity	5000mAh/3.85V/19.25Wh
Mobilephone Output	15W/10W/7.5W/5W
iWatch Output	2.5W
Headphone Output	5W
Type-C Input	5V/3A, 9V/2A, 12V/1.5A (18W)
Type-C Output	5V/3A, 9V/2.22A, 12V/1.67A (20W)
Dimensions	132*75*42mm(L x W x H)
Weight	Approx. 325g
Shell material	ABS+Zinc Alloy

OT-PBW-018

NEW



Battery Capacity	10000mAh/3.85V/37.5Wh
USB-C /USB-C Cable Input	5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A (20W)
USB-C /USB-C Cable Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A(45W)
Lighting Cable Output	45W
Cable Length	80cm
Dimensions	127*58*22mm(L x W x H)
Weight	Approx. 245g
Shell material	ABS+PC

OT-PBW-017



Battery Capacity	10000mAh/3.85V/38.5Wh
USB-C/USB-C Cable Input	5V/2.5A, 9V/2A (20W)
USB-C/USB-C Cable Output	5V/2.5A, 9V/2A, 12V/1.5A (18W)
Lighting Cable Output	5V/2.4A
Cable Length	65 cm
Dimensions	119*64*25mm(L x W x H)
Weight	Approx. 245g
Shell Material	ABS+PC

OT-PBW-016

HOT



Battery Capacity	10000mAh/3.85V/38.5Wh
USB-C Cable Output	5V/3A, 9V/2.22A, 12V/1.67A (20W)
Type-C Input	5V/3A, 9V/2A, 12V/1.5A (18W)
Type-C Output	5V/3A, 9V/2.22A, 12V/1.67A (20W)
USB-A Output	4.5V5A 5V4.5A 5V3A 9V2A 12V1.5A
Cable Length	65cm
Dimensions	112*64*26mm(L x W x H)
Weight	Approx. 177g
Shell Material	ABS+PC

67W GaN POWER STRIP



MULTIPOINT CHARGING

PD and QC multi-interface



3-IN-1 MAGNETIC WIRELESS CHARGER STATION



OmniTech



OmniTech(Shenzhen) Co., Ltd.

Office Address:

Office 815, 8th Floor, JiangNan Times Building, 4033 Banxue Gang Avenue, Longgang District, Shenzhen, CN.

Factory Address:

(Shenzhen) 3rd Floor, Building 1, Fuan First Industrial City, 99 Dayang Road, Fuhai Street, Baoan District, Shenzhen, CN.

(Yangzhou) No. 9 Yinbai Road, Hanjiang Industrial Park, Yangzhou, Jiangsu, CN.

Contact: Henry Zhang / CEO

Tel: +86 13905273603

Email: sales@omnitechstar.com

Website: <http://www.globalsources.com/omnitechstar.co>



Website