

NINGBO WISHING MACHINERY & ELECTRIC LIMITED

1 X 40V PROJECTS 2026 NEW



OTHER
NEW
MODELS
ON
THE
WAY

One battery for all

40V BRUSHLESS DRILL

Model : TKDY4065

SPECIFICATIONS

Battery: 40V

Chuck Diameter(mm): 13

No load speed Low: 0-500 r/min

High: 0-2000 r/min

Max torque Low: 20+1 N.m

High: 65 N.m

Max drilling capacity

Steel: \varnothing 13 mm

Wood: \varnothing 38 mm

Net Weight: 1.0 kg

FEATURE

1. 13 mm metal chuck
2. 145 mm compact body design
3. Dual Led light



40V BRUSHLESS IMPACT DRILL

Model : TKDY4065I

SPECIFICATIONS

Battery: 40V

Chuck Diameter(mm): 13

No load speed Low: 0-500 r/min

High: 0-2000 r/min

Max torque Low: 20+2 N.m

High: 65 N.m

Max drilling capacity

Steel: ϕ 13 mm

brick: ϕ 13 mm

Wood: ϕ 38 mm

Net Weight: 1.1 kg

FEATURE

1. 13 mm metal chuck
2. 157 mm compact body design
3. Dual led light



40V BRUSHLESS IMPACT DRIVER

Model : TKDY40230

SPECIFICATIONS

No-load speed: 0-3300 r/min
Impact frequency: 0-3500 ipm
Holding capacity: 1/4"(6.35 mm)
Max. Torque: 230 N.m
Net Weight: 1.0 kg

FEATURE

1. 123 mm head length
2. 230 N·m fastening torque
3. Quick change collet



40V

BRUSHLESS IMPACT WRENCH

Model : TKDY40400

SPECIFICATIONS

Battery: 40V

Standard Bolt(mm) M6-M16

High Tensile Bolt(mm): M10-M14

No load speed: 0-2500 r/min

Impact Frequency: 0-3600 bpm

Max torque: 400 N.m

Max nut-busting torque: 600 N.m

Anvil Size: 12.7 mm (1/2") square

Net Weight: 1.1 kg

FEATURE

1. Auto-stop nut-busting function
2. 400 N.m max fastening torque



40V

BRUSHLESS IMPACT WRENCH

Model : TKDY40600

SPECIFICATIONS

Battery: 40V

Standard Bolt (mm) M12-M22

High Tensile Bolt(mm): M8-M18

No load speed: 0-1200/1800/2400 r/min

Impact Frequency: 0-1000/2400/3200 bpm

Max torque: 600 N.m

Max nut-busting torque: 900 N.m

Anvil Size: 12.7mm (1/2") square

Net Weight: 1.3 kg

FEATURE

1. Auto-stop nut-busting function
2. 600 N.m max fastening torque
3. Detachable heat insulation shield



40V

BRUSHLESS IMPACT WRENCH

Model : TKDY40960

SPECIFICATIONS

Battery: 40V

Standard Bolt (mm) M12-M24

High Tensile Bolt(mm): M8-M18

No load speed: 0-2000 r/min

Impact Frequency: 0-2600 bpm

Max torque: 960 N.m

Max nut-busting torque: 1100 N.m

Anvil Size: 12.7mm (1/2") square

Net Weight: 2.0 kg

FEATURE

1. Decoupled anti-vibration mechanism
2. 3 speed selection and auto mode
3. House cover with impact and heat-resistant design



40V

BRUSHLESS IMPACT WRENCH

Model : TKDY401800

SPECIFICATIONS

Battery: 40V

Standard Bolt(mm) M12-M36

High Tensile Bolt(mm): M10-M27

No load speed: 0-900/1000/1700 r/min

Impact Frequency: 0-1800/2000/2400 bpm

Max torque: 1800 N.m

Max nut-busting torque: 2100 N.m

Anvil Size: 19 mm (3/4")square

Net Weight: 3.2 kg

FEATURE

1. APP anti-vibration technology
2. 1800 N.m max. fastening for heavy duty
3. 3 model torque setting



40V

BRUSHLESS ROTARY HAMMER

Model : TKDY4022

SPECIFICATIONS

Battery: 40V

No load speed: 0-1400 r/min

Impact Frequency: 0-4500 bpm

Drilling Capacity: 8-12 mm

Rated impact energy: 2.3 J

Chuck Type: SDS-Plus

Net Weight: 1.8 kg

FEATURE

1. Accurate positioning, reliable and durable
2. New four-function gear adjustment structure
3. Mechanical-electronic dual clutch
4. 22 mm large cylinder
- 2 3 1 high-energy output



40V BRUSHLESS ROTARY HAMMER

Model : TKDY4028

SPECIFICATIONS

Battery: 40V

No load speed: 0-1050 r/min

Impact Frequency: 0-5100 bpm

Drilling Capacity: 8-18 mm

Rated impact energy: 3.8 J

Chuck Type: SDS-Plus

Net Weight: 3.1 kg

FEATURE:

1. Smart e-clutch technology
2. Dual anti-vibration design



40V BRUSHLESS ANGLE GRINDER

Model : TKDY40100

SPECIFICATIONS

Battery: 40V

No load speed: 3500/6200/9500 r/min

Max wheel Dia.: \varnothing 100 mm

Hole Dia. of wheel: \varnothing 16 mm

Spindle Thread: M10

Net Weight: 1.3 kg

FEATURE :

1. Magnetic air duct patent technology
2. Auto-stop for safety protection



40V BRUSHLESS ANGLE GRINDER

Model : TKDY40125

SPECIFICATIONS

Battery: 40V

No load speed: 3500/6200/9500 r/min

Max wheel Dia.: \varnothing 125 mm

Hole Dia. of wheel: \varnothing 22mm

Spindle Thread: M14

Net Weight: 1.5 kg

FEATURE :

1. Magnetic air duct patent technology
2. Auto-stop for safety protection



40V BRUSHLESS CIRCULAR SAW

Model : TKDY40150

SPECIFICATIONS

Battery: 40V

No load speed: 6200r/min

Blade Dia.: 150mm

Internal bore Dia: 20mm

Cutting capacity: 55mm (0°)

Angle adjustment: 0-45°

Net Weight: 1.8 kg

FEATURE

1. Automatic dust blow design
2. 360° adjustable dust outlet
3. Soft start



40V

BRUSHLESS RECIPROCATING SAW

Model : TKDY4032

SPECIFICATIONS

Battery 40V

Strokes Per Minute 0 - 1000/2800spm

Capacity: 32mm

Net Weight: 2.8 kg

FEATURE

1. 2-speed brushless motor delivers 0-2300 (Low) and 0 - 2800 (High) strokes per minute
2. Refined crank mechanism design minimizes blade deflection and reduces vibration
3. "Tool - less" blade change system allows for faster blade installation and removal for increased productivity



40V

BRUSHLESS RECIPROCATING SAW

Model : TKDY4026

SPECIFICATIONS

Battery: 40V

Reciprocating Stroke: 26 mm

Strokes Per Minute: 0 - 1600/3100 spm

Capacity Wood: 250 mm, pipe: 20 mm

Net Weight 1.8 kg

FEATURE

1. Powerful Brushless motor
2. Low vibration design to ease user fatigue
3. Tool - free quick change blade for easy operation



40V BRUSHLESS TRIMMER

Model : TKDY40635

SPECIFICATIONS

Battery: 40V

Chuck Capacity: 6.35 mm

No Load Speed: 10000 - 30000 r/min

Net Weight: 1.3 kg

FEATURE

1. Equipped with drop detection
2. Electronic speed control maintains constant speed under load



40V BRUSHLESS JOBSITE BLOWER

Model : TKDY297

SPECIFICATIONS

Battery: 40V

Max Air Velocity: 0 - 215 m/s

Max Air Volume: 0 - 1.1 m³/min

Blowing Force: 4.32 N/ 3.26 N/2.19 N/1.1N

Max Sealed suction: 29.7 kPa

Net Weight: 0.6 kg

FEATURE

1. Delivers up to 215 m/s and 1.1 m³/min
2. Provides up to 50 mins runtime with 4.0 Ah battery
3. 4 digitally controlled speeds



40V WORKING LIGHT

Model : TKDY4021

SPECIFICATIONS

Battery: 40V

Rated power input: 21 W

Color temperature: 6500 K

Brightness:(lm): Low 1000 lm High: 2000 lm

Net Weight: 0.4 kg

FEATURE

Adjustment irradiation angle: 0°-180°



40V FAN

Model : TKDY40405

SPECIFICATIONS

Battery: 40V

Max Air Velocity: 7.4 m/s

Max Air Volume: 56 m³/min

Blade Dia.: 405 mm

Net Weight: 5.0 kg

FEATURE

1. For long workingtime
2. Φ405 mm fan blades, rubber base support

