



深圳市宇盛昌科技有限公司

Filsion Technology Company Limited



办公室地址：深圳市龙岗区平新北路162号广隆大厦7楼7C

工厂地址：东莞市塘厦镇桥陇河东路7号鸿鑫宝产业园A栋三楼

Office Address: 7C, Guanglong Plaza, No. 162 Pingxin North Road, Longgang, Shenzhen, China

Factory Address: Floor 3, Block A, HongXinBao Industrial Park, Qiao Long River East Road No. 7
Tangxia Town, Dongguan, China

www.filsion.com

Email: intersales@filsion.com

FILSION

目录 CONTENTS

01	5V 2A常规充电宝 / 5V 2A Power Bank	01
02	65W 100W充电宝 / 65W 100W Power Bank	06
03	QC PD20W / QC&PD Fast Charge Power Bank	07
04	磁吸充电宝 / Magsafe Wireless Power Bank	14
05	户外电源 / Power Station	16
06	太阳能 / Solar Power Bank	16
07	透明款 / Transparent Power Bank	18
08	无线充 / Wireless Charger	19



S-100F

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



S-200F

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



D-100G

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



D-200G

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



ACP-100D

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A or QC18W (Dual USB
- 3.Input : 5V/2A or QC18W (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity,
- 8.Built-in wall plug
- 9.Built-in 2 cables

COLOR LED USB Port High-capacity



ACP-500A

- 1.Capacity: 50000mAh(Max)
- 2.Output : 5V/2A (Type C)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Optional to built-in cable

COLOR LED USB Port High-capacity



C-100J

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



C-200J

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



C-300J

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity



C-100F

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR LED USB Port High-capacity

**C-200F**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type A)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR

**C-300F**

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR

**C-100K**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR

**C-200K**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity

COLOR

**O-500A**

- 1.Capacity: 5000mAh
- 2.Output : 5V/2A (USB A & Type C)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Indicator to show battery capacity

COLOR

**DC-500FS**

- 1.Capacity: 5000mAh(max)
- 2.Output Type C: 5V/2A
- 3.Input Micro USB : 5V/2A
- 4.Circulation : > 500 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.Direct charge, Foldable Type C port
- 8.With Type C cable for output 2A

COLOR

**D-500A**

- 1.Capacity: 5000mAh
- 2.Output : 5V/1A
- 3.Input : 5V/1A (Micro USB)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**B-100G**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**B-200G**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**Q-200G**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**Q-100G**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**Q-300G**

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**Mi-100T3**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2A, 12V/1.5A(Dual USB A)
- Type C: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Input : 5V/3A, 9V/2A, 12V/1.5A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.TFT Display to show battery capacity

COLOR

**Mi-100T2**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2A, 12V/1.5A(USB A)
- Type C: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Input : 5V/3A, 9V/2A, 12V/1.5A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.TFT Display to show battery capacity
- 8.Built-in Type C fast charge cable

COLOR

**Mi-100T1**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2A, 12V/1.5A(USB A)
- Type C: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Input : 5V/3A, 9V/2A, 12V/1.5A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.TFT Display to show battery capacity

COLOR

**J-100A**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**J-200A**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR

**C-100E**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



**C-200E**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**C-300E**

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-500C**

- 1.Capacity: 5000mAh
- 2.Output : 5V/2A (USB)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-100C**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-500E**

- 1.Capacity: 5000mAh
- 2.Output : 5V/2A (USB)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-100E**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-200E**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**L-S500A**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2.22A PD20W (Type C)
- 3.Input : 5V/3A, 9V/2A 18W (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.Smart size, with Type C/Lightning cables

COLOR



Digital display



USB Port



High-capacity

**B-500A**

- 1.Capacity: 5000mAh
- 2.Output : 5V/2A (USB)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-100A**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-200A**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**L-100C1**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2.22A PD20W (Type C)
- 3.Input : 5V/3A, 9V/2A 18W (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.Smart size, with Type C/Lightning cables

COLOR



Digital display



USB Port



High-capacity

**B-200D**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery c

COLOR



Digital display



USB Port



High-capacity

**Q-35H**

- 1.Capacity: 10000mAh
- 2.Output : 5V/3A, 9V/2.22A (USB A & Type C)
- 3.Input : 5V/3A, 9V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-500M**

- 1.Capacity: 5000mAh
- 2.Output : 5V/2A (USB)
- 3.Input : 5V/2A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-100M**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



Digital display



USB Port



High-capacity

**B-200M**

- 1.Capacity: 20000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



LED

**B-300M**

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



LED

**K-100D**

- 1.Capacity: 10000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



LED

**K-300D**

- 1.Capacity: 30000mAh
- 2.Output : 5V/2A (Dual USB A)
- 3.Input : 5V/2A (Micro & Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity

COLOR



LED

**Mi-200A**

- 65W
- 1.Capacity: 20000mAh
 - Type-C Output protocol: QC2.0/QC3.0 /AFC/FCP/PD2.0/PD3.0 /PPS
 - USB A Output protocol: QC2.0/QC3.0 /AFC/FCP/SCP/PPS
 - Type-C1 Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A
 - USB 1 Output: 4.5V/5A 5V/3A 9V/2A 12V/1.5A 22.5W Max
 - USB 2 Output: 5V/3A 9V/2A 12V/1.5A 18W Max

COLOR



LED

**S-400P**

- 65W
- 1.Capacity: 40000mAh
 - Type-C Output protocol: QC2.0/QC3.0 /AFC/FCP/PD2.0/PD3.0 /PPS
 - USB A Output protocol: QC2.0/QC3.0 /AFC/FCP/SCP/PPS
 - Type-C1 Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A
 - Type-C2 Output: 5V/3A 9V/2A 12V/1.5A 18W Max
 - USB 1 Output: 4.5V/5A 5V/3A 9V/2A 12V/1.5A 22.5W Max
 - USB 2 Output: 5V/3A 9V/2A 12V/1.5A 18W Max
- *Optional: Wireless charging: 15W
C1, USB1, all the way, C2, USB 2, all the way.

COLOR



LED


**S-500P**

- 65W
- 1.Capacity: 50000mAh
 - Type-C Output protocol: QC2.0/QC3.0 /AFC/FCP/PD2.0/PD3.0 /PPS
 - USB A Output protocol: QC2.0/QC3.0 /AFC/FCP/SCP/PPS
 - Type-C1 Output: 5V/3A 9V/3A 12V/3A 15V/3A 20V/3A
 - Type-C2 Output: 5V/3A 9V/2A 12V/1.5A 18W Max
 - USB 1 Output: 4.5V/5A 5V/3A 9V/2A 12V/1.5A 22.5W Max
 - USB 2 Output: 5V/3A 9V/2A 12V/1.5A 18W Max
- *Optional: Wireless charging: 15W
C1, USB1, all the way, C2, USB 2, all the way.

COLOR



LED

**MO-100A**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Camera design
- 9.Back light to show the image

COLOR



LED

**CM-100A**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Camera design
- 9.Built-in charging cable

COLOR



LED

**F-Smart100A**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Super Smart in size

COLOR



LED

**Mi-100CA**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Built-in charging cable

COLOR



LED

**Mi-100A**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mini design using 21700 battery

COLOR



LED

**FP-100A**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mechanical design
- 9.Fidget Spinner

COLOR



LED

**RC-100C**

- 1.Capacity: 10000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
Type C Cable Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Built-in retractable Type C cable, max length 50cm
- 9.Optional to make 30W output

COLOR



LED

**F-Smart200A**

- 1.Capacity: 20000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Super Smart in size

COLOR



LED

**Mi-100J**

- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Built-in charging cable

COLOR



LED

**Mi-200A**

- 1.Capacity: 20000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mini design using 21700 battery

COLOR




LED




**Mi-100R**


- 1.Capacity: 10000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicator to show battery capacity
- 8.Mini design using Li-polymer battery
- 9.Built-in Type C fast charge cable

**Mi-100S**


- 1.Capacity: 10000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mini design using Li-polymer battery
- 9.Built-in Type C fast charge cable

**Mi-100CC**


- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mini design using 21700 battery
- 9.With Type C cable built-in

**Mi-100DC**


- 1.Capacity: 10000mAh
- 2.USB Output : 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Type C Input : 5V/2A, 9V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Mini design using 21700 battery
- 9.With Type C cable & Lightning cable built-in

**H-100P**

- 1.Capacity: 10000mAh/20000mAh/30000mAh/40000mAh/50000mAh
- 2.Output :
USB A output: 4.5V/5A(22.5W), 9V/2.22A(20W), 12V/1.67A(20W)
Type C output: 5V/3A, 9V/2.22A(20W), 12V/1.67A(20W)
Type C output while using together with USB A, it will share from 5V/2A power(final V/A depends on how many ports using)
- 3.Input :
Micro USB: 5V/2A
Type C: 5V/3A, 9V/2A(18W)
4.USB support output QC3.0/QC2.0/FCP/PE2.0/PE1.1/5FCP
5.Type-C support output PD3.0/PD2.0/QC3.0/QC2.0/FCP/PE2.0/PE1.1/5FCP support input PD3.0/PD2.0
6.Support quick charge input and output at the same time
7.With LED display to show battery capacity and output/input status
8.Dynamic display to show real charging Voltage and V/A

**S-200F**

- 1.Capacity: 10000mAh/20000mAh/30000mAh/40000mAh/50000mAh
- 2.Output :
USB A output: 4.5V/5A(22.5W), 9V/2.22A(20W), 12V/1.67A(20W)
Type C output: 5V/3A, 9V/2.22A(20W), 12V/1.67A(20W)
Type C output while using together with USB A, it will share from 5V/2A power(final V/A depends on how many ports using)
- 3.Input :
Micro USB: 5V/2A
Type C: 5V/3A, 9V/2A(18W)
4.USB support output QC3.0/QC2.0/FCP/PE2.0/PE1.1/5FCP
5.Type-C support output PD3.0/PD2.0/QC3.0/QC2.0/FCP/PE2.0/PE1.1/5FCP support input PD3.0/PD2.0
6.Support quick charge input and output at the same time
7.With LED display to show battery capacity and output/input status
8.Dynamic display to show real charging Voltage and V/A

**S-100A**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-200H**

- 1.Capacity: 20000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-100D**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-300D**

- 1.Capacity: 30000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-500D**

- 1.Capacity: 50000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-800D**

- 1.Capacity: 80000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-300H**

- 1.Capacity: 30000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-200D**

- 1.Capacity: 20000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-400D**


- 1.Capacity: 40000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-600D**


- 1.Capacity: 60000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**D-100C**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
USB A : 4.5V/5V(22.5W) 5V/3A, 9V/2A, 12V/1.5A
Type C output: 5V/3A, 9V/2.22A(20W), 12V/1.67A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status
- 8.Optional to built-in fast charge Type C cable and Lightning cable


**S-200A**

- 1.Capacity: 20000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status

**C-100H**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
USB A : 5V/3A, 9V/2.22A(20W)
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Micro USB: 5V/3A, 9V/2.22A(20W)
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With LED Display to show battery capacity and output/input status



**LA-BU100**

- 1.Capacity: 10,000mAh (Li-polymer)
- 2.Output:
USB A : 4.5V/(22.5W) 5V/3A, 9V/2A
12V/1.5A
Type C output: 5V/3A, 9V/2.22A(20W)
12V/1.67A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Magsafe wireless charging 15W
- 7.With LED Display to show battery capacity and output/input status
- 8.Built-in fast charge Type C cable and Lightning cable
- 9.Cables cover with labubu looks

COLOR

**MS-500WA**

- 1.Capacity: 5000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W),
12V/1.67A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Magsafe wireless charging 15W
- 7.With LED indicators to show battery capacity and output/input status
- 8.Built-in fast charge Type C cable
- 9.With Mirror built-in
10. Foldable design

COLOR

**MGC-500PB Qi2**

- 1.Capacity: 5,000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A(20W)
- 3.Type C Input : 5V/2A, 9V/2A(18W)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Original is 20W wired charge and 15W wireless charge.
- 10.With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**MGM-100ES Qi2**

- 1.Capacity:10,000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity
- 8.With Magnetic Stand
- 9.Original is 10W wired charge and 5W wireless charge.
10. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
- 11.With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**MG-500A**


- 1.Capacity: 5000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicators to show battery capacity
- 8.Original is 10W wired charge and 5W wireless charge.
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
- 10.With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**B-400Q Qi2**

- 1.Capacity: 5,000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W),
12V/1.67A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2.22A(20W)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.With Dynamic TFT display to show battery capacity and output/input status
- 8.Magsafe 15W wireless charging
- 9.Optional to make with charging iWatch
- 10.Optional to make 10,000mAh

COLOR

**MG-S500C**

- 1.Capacity:5,000mAh
- 2.Type C Output: 5V/2A
Wireless Output: 5W
- 3.Type C Input : 5V/2A
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Super Slim: 8.8mm
- 7.LED indicator to show battery capacity
- 8.Optional to make with 15W and 20W PD
- 10.With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**MGC-100PB Qi2**

- 1.Capacity: 10,000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A(20W)
- 3.Type C Input : 5V/2A, 9V/2A(18W)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
- 8.Original is 20W wired charge and 15W wireless charge.
- 10.With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**MG-100FC**

- 1.Capacity:10,000mAh
- 2.Type C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Input : 5V/3A, 9V/2A, 12V/1.5A (1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.With Phone Stand
9. Wireless 15W fast charge.
10. Colorful rotate fan while working
11. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series phones

COLOR

**MG-500AR**

1. Capacity: 5000mAh
2. USB Output: 5V/2A
3. Input : 5V/2A (1*Type C)
4. Circulation : > 300 times
5. Working Tem. : -10°C-40°C
6. Storage Tem. : -20°C-50°C
7. LED indicators to show battery capacity
8. Original is 10W wired charge and 5W wireless charge.
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
10. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series
11. With Ring Phone Stand design

COLOR

**MGB-500CS Qi2**

- 1.Capacity:5,000mAh
- 2.USB Output: 5V/3A, 9V/2A, 12V/1.5A
Type C Output: 5V/3A, 9V/2.22A, 12V/1.67
- 3.Input : 5V/3A, 9V/2A (1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.Original is 10W wired charge and 5W wireless charge.
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
10. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series

COLOR

**MG-100SS Qi2**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2A(18W)
4. With Phone Stand.
5. Magsafe wireless output: 15W
6. Available to charge iPhone/iWatch/Earbuds
7. Circulation: > 500 times
8. Working Tem.: -10°C-40°C
9. Storage Tem.: -20°C-50°C
10. With LED Display to show battery capacity and output/input status

COLOR

**TS-100YC**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2A(18W)
4. Transparent cases to see components used.
5. Magsafe wireless output: 15W
6. Magnet built-in
7. Circulation: > 500 times
8. Working Tem.: -10°C-40°C
9. Storage Tem.: -20°C-50°C
10. With LED Display to show battery capacity and output/input status

COLOR

**MGM-100NC**

- 1.Capacity: 10000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Micro, 1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED display to show battery capacity
8. Wireless Charging 5W
9. Optional to make PD18W + 10W Fast Wireless Charger

COLOR

**MG-100BS**

- 1.Capacity: 10000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Micro, 1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.Original is 10W wired charge and 5W wireless charge.
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
9. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series

COLOR

**MGB-500CL**

- 1.Capacity: 5,000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2A(18W)
4. Electronics Painting cases to see glossy colorful
5. Magsafe wireless output: 15W
6. Magnet built-in
7. Circulation: > 500 times
8. Working Tem.: -10°C-40°C
9. Storage Tem.: -20°C-50°C
10. With LED indicators to show battery capacity and output/input status

COLOR

**TS-100YA**

- 1.Capacity: 10000mAh (Li-polymer)
- 2.Output:
Type C output: 5V/3A, 9V/2.22A(20W)
- 3.Input:
Type C : 5V/3A, 9V/2A(18W)
4. Transparent cases to see components used.
5. Magsafe wireless output: 15W
6. Magnet built-in
7. Circulation: > 500 times
8. Working Tem.: -10°C-40°C
9. Storage Tem.: -20°C-50°C
10. With LED Display to show battery capacity and output/input status

COLOR

**MG-100H**

- 1.Capacity: 5000mAh
- 2.USB C Output: 5V/3A, 9V/2.22A, 12V/1.67A
- 3.Input : 5V/3A, 9V/2A, 12V/1.5A (Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Indicators to show battery capacity
8. Wireless 15W output
9. Super slim design with colorful lights
9. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series

COLOR

**W-100Y**

- 1.Capacity: 10000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Micro, 1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED indicator to show battery capacity
8. Wireless Charging 5W
9. With phone stand, Magnet
10. Optional to make PD18W + 10W Fast Wireless Charger

COLOR

**MG-100H**

- 1.Capacity: 10000mAh
- 2.USB Output: 5V/2A
- 3.Input : 5V/2A (1*Micro, 1*Type C)
- 4.Circulation : > 300 times
- 5.Working Tem. : -10°C-40°C
- 6.Storage Tem. : -20°C-50°C
- 7.LED Display to show battery capacity
- 8.Original is 10W wired charge and 5W wireless charge.
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 15W fast charge
9. With Magnet built-in, compatible with iPhone 16/15/14/13/12 series

COLOR





- 1.Capacity: 10000mAh
- 2.USB Output: 5V/2A
- 3.Input: 5V/2A (1*Micro, 1*Type C)
- 4.Circulation: > 300 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.LED indicators to show battery capacity
- 8.Original is 10W wired charge and 5W wireless charge
9. Optional to make Fast Charge wired 18W + Wireless 10W fast charge
9. Optional to make Fast Charge wired 22.5W + Wireless 10W fast charge
- 10.With Magnet built-in, compatible with iPhone 12 mini/12/12 pro/12 pro max

COLOR

LED



SL-C200



- 1.Capacity: 20000mAh
- 2.Input:5V/3A
- 3.Outputs(Type C):5V/3A
- 4.USB A output: 5V/3A
- 5.Built-in big LED Camping light
- 6.LED numbers to show battery capacity
- 7.Solar Panel help charging power bank with sun light
- 8.Wireless output 5W or 15W
- 8.Optional to make wireless charging 15W and PD/QC 22.5W fast charge

COLOR

LED



SC-G100



- 1.Capacity: 10000mAh
- 2.Input:5V/2A
- 3.Outputs(Micro USB & Type C & Lightning):5V/2A
- 4.USB output: 5V/2A
- 5.Built-in Lightning 3 charging cable(3 cables of Micro/Type C/Lightning to charge smartphones)
- 6.LED numbers to show battery capacity
- 7.Solar Panel help charging power bank with sun light
- 8.LED Torch light built-in
- 9.Optional to make wireless charging

COLOR

LED



SC-E200



- 1.Capacity: 20000mAh
- 2.Input:5V/3A
- 3.Outputs(Type C):5V/3A
- 4.USB A output: 5V/3A
- 5.Built-in Lightning 3 charging cable(3 cables of Micro/Type C/Lightning to charge smartphones)
- 6.Built-in LED torch light
- 7.LED numbers to show battery capacity
- 8.Solar Panel help charging power bank with sun light
- 9.Wireless output 5W or 15W
- 10.Optional to make wireless charging 15W and PD/QC 22.5W fast charge

COLOR

LED



S-100F



- 1.Lable Capacity:10000MAH
- 2.Output:5V/2A x 2
- 3.Input:Micro USB 5V/2A , Type C 5V/2.4A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Compass built-in

COLOR

LED



S-300A



- 1.Lable Capacity: 16,000MAH/30,000MAH(Max)
- 2.Output: 4 USB Outputs, max output 5V/3A, 9V/2A(18W QC3.0)
- 3.Wireless Output: 10W
- 4.Input: Micro USB 5V/2A, Type C 5V/2A, 9V/2.4A
- 5.Circulation: > 500 times
- 6.Working Tem.: -10°C-40°C
- 7.Storage Tem.: -20°C-50°C
- 8.Solar charger, 2W solar Panel
- 9.LED Torch lights
- 10.With Compass
- 11.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-200C



- 1.Lable Capacity: 20000MAH(Max)
- 2.Output: 2*USB: 5V/2A(Max)
- 3.Input: Micro USB 5V/2A, Type C: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Wireless output 5W or 15W
- 10.Optional to make wireless charging 5W/15W

COLOR

LED



SC-E100



- 1.Capacity: 10000mAh
- 2.Input:5V/2A
- 3.Outputs(Micro USB & Type C & Lightning):5V/2A
- 4.USB output: 5V/2A
- 5.Built-in Lightning 3 charging cable(3 cables of Micro/Type C/Lightning to charge smartphones)
- 6.LED numbers to show battery capacity
- 7.Solar Panel help charging power bank with sun light
- 8.Optional to make wireless charging

COLOR

LED



S-100W



- 1.Lable Capacity:10000MAH
- 2.Output:5V/2A x 2
- 3.Input:Micro USB 5V/2A , Type C 5V/2.4A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Compass built-in
- 11.Wireless charging 5W
- 12.Optional to make 15W wireless fast charge

COLOR

LED



S-100H



- 1.Lable Capacity:10000MAH
- 2.Output:5V/2A x 2
- 3.Input:Micro USB 5V/2A , Type C 5V/2.4A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Compass built-in
- 11.Optional to make wireless charging function

COLOR

LED



S-500MSA

- 1.Lable Capacity:5000MAH
- 2.Output:5V/2A
- 3.Input:Micro USB 5V/2A , Type C 5V/2.4A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Magnet built-in with Magsafe function
- 11.wireless charging function 5W

COLOR

LED



S-400A



- 1.Lable Capacity: 8000MAH(Max)
- 2.Output: 5V/1A
- 3.Input: 5V/1A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-400E



- 1.Lable Capacity: 4000MAH(Max)
- 2.Output: 5V/1A
- 3.Input: 5V/1A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-100P



- 1.Lable Capacity: 8000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-F100T



- 1.Lable Capacity: 10000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.Foldable solar panels triple panels after-open
- 9.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-CC300-1200



- 1.Lable Capacity: 30,000MAH-120,000MAH
- 2.Output: 5V/2A x 4
- 3.Input: 5V/2A (Micro USB & Type C)
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Built-in Lightning 4 charging cable(3 cables of Micro/Type C/Lighting to charge smartphones, 1 cable USB to charge power bank)

COLOR

LED



S-800M



- 1.Lable Capacity: 8000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Aluminum casing

COLOR

LED



S-100D



- 1.Lable Capacity: 8000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Phone holder
- 10.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-800A



- 1.Lable Capacity: 8000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop

COLOR

LED



S-200SY



- 1.Lable Capacity: 20000MAH(Max)
- 2.Output: 5V/2A x 2
- 3.Input: 5V/2A
- 4.Circulation: > 500 times
- 5.Working Tem.: -10°C-40°C
- 6.Storage Tem.: -20°C-50°C
- 7.Solar charger
- 8.LED Torch lights
- 9.Waterproof, Dustproof, Anti-drop
- 10.Hand rotate to make electronicity

COLOR

LED



**WS3IN1J**

- 1) Input: 9V/2A, 5V/2A
- 2) Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
- Wireless output for iWatch 3W
- Wireless output for Airpod 5W
- 3) Charge distance: 4~8mm
- 4) Magnet built-in
- 5) Size: 75*75*30mm

COLOR



LED

**WS3IN1K**

- 1) Input: 9V/2A, 5V/2A
- 2) Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
- Wireless output for iWatch 3W
- Wireless output for Airpod 5W
- 3) Charge distance: 4~8mm
- 4) Magnet built-in
- 5) Size: 75*75*30mm

COLOR



LED

**WS3IN1T**

- 1) Input: 9V/2A, 5V/2A
- 2) Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
- Wireless output for iWatch 3W
- Wireless output for Airpod 5W
- 3) Charge distance: 4~8mm
- 4) Magnet built-in
- 5) Size: 75*75*30mm

COLOR



LED

**WG24**

- Fast Wireless Charger Car Mount Gravity
- 1) Input: 5V/9V
 - 2) Output: 5W/7.5W/10W/15W
 - 3) Size: mm
 - 4) Air Vent Mount
 - 5) Weight: g

COLOR



LED

**MC-01**

- 1) Wireless Charging Car Mount
 - 2) Input: DC5V/3A, 9V/2.0A
 - 3) Wireless Output: 5W/7.5W/10W
 - 4) Charge current: 5V/1.5A, 9V/1.10A
 - 5) Qi FAST wireless charger
 - 6) With Magnet built-in
- Compatible with iPhone 12/iPhone 11 /iPhone Xs/iPhone XR/iPhone X/iPhone 8 /iPhone SE/iPhone SE2

COLOR



LED

**MC-02**

- 1) Wireless Charging Car Mount
 - 2) Input: DC5V/3A, 9V/2.0A
 - 3) Wireless Output: 5W/7.5W/10W
 - 4) Charge current: 5V/1.5A, 9V/1.10A
 - 5) Qi FAST wireless charger
 - 6) With Magnet built-in
- Compatible with iPhone 12/iPhone 11 /iPhone Xs/iPhone XR/iPhone X/iPhone 8 /iPhone SE/iPhone SE2

COLOR



LED

**WL13**

- Desk Lamp + Fast Wireless Charger
- 1) Input: 5V/2A, 9V/2A
 - 2) Output: 5W/7.5W/10W
 - 3) Size: 121*250*375mm
 - 4) Desk Lamp Wireless Charger
 - 5) Weight: 265 g

COLOR



LED

**WL14**

- Desk Lamp + Fast Wireless Charger
- 1) Input: 5V/2A, 9V/2A
 - 2) Output: 5W/7.5W/10W
 - 3) Size: 121*250*375mm
 - 4) Desk Lamp Wireless Charger
 - 5) Weight: 265 g

COLOR



LED

**WL-01**

- Fast Wireless Charger + LED Light
- *1) Input: DC 5V/2.1A, 9V/1.67A
 - *2) Output: 15W (Compatible with 5W/7.5W/10W) for Smartphone
 - 3W for TWS earbuds
 - 2W for Smart Watch
 - Wireless charge distance: < 6mm
 - 4) Size: 215mm*120mm*90mm
 - 5) Charge two Smartphones together
 - 6) LED lights as night light on desk
 - 7) Charge TWS earbuds
 - 8) Charge Smart Watch

COLOR



LED

**AW-01**

1. Alarm Clock + Wireless charger
2. Input: DC5V/3A, 9V/2.0A
3. Wireless Output: 5W/7.5W/10W/15W
4. Charge current: 5V/1.5A, 9V/1.10A
5. Distance: 5mm
6. Alarm clock function
7. Temperature
8. Detachable

COLOR



LED

**AW-03**

1. Alarm Clock + Wireless charger
2. Input: DC5V/3A, 9V/2.0A
3. Wireless Output: 5W/7.5W/10W/15W
4. Charge current: 5V/1.5A, 9V/1.10A
5. Distance: 5mm
6. Alarm clock function
7. Temperature
8. Detachable

COLOR



LED

**AW-05**

1. Alarm Clock + Wireless charger
2. Input: DC5V/3A, 9V/2.0A
3. Wireless Output: 5W/7.5W/10W/15W
4. Charge current: 5V/1.5A, 9V/1.10A
5. Distance: 5mm
6. Alarm clock function
7. Temperature
8. Detachable

COLOR



LED

**AW-06**

1. Alarm Clock + Wireless charger
2. Input: DC5V/3A, 9V/2.0A
3. Wireless Output: 5W/7.5W/10W/15W
4. Charge current: 5V/1.5A, 9V/1.10A
5. Distance: 5mm
6. Alarm clock function
7. Temperature
8. Detachable

COLOR



LED

**WS3IN1J**

1. Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
2. Wireless output for iWatch 3W
- Wireless output for Airpod 5W
3. Charge current: 5V/1.5A, 9V/1.10A
4. Distance: 5mm
5. Foldable design

COLOR



LED

**WG23**

- Fast Wireless Charger Car Mount Gravity
- 1) Input: 5V/9V
 - 2) Output: 5W/7.5W/10W/15W
 - 3) Size: 115*95.5*50mm
 - 4) Air Vent Mount
 - 5) Weight: 121 g

COLOR



LED

**WL12**

- Desk Lamp + Fast Wireless Charger
- 1) Input: 5V/2A, 9V/2A
 - 2) Output: 5W/7.5W/10W
 - 3) Size: 121*250*375mm
 - 4) Desk Lamp Wireless Charger
 - 5) Weight: 265 g

COLOR



LED

**WS3IN1R**

1. Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
2. Wireless output for iWatch 3W
- Wireless output for Airpod 5W
3. Charge current: 5V/1.5A, 9V/1.10A
4. Distance: 5mm
5. Foldable design
6. Bottom light for atmosphere

COLOR



LED

**WS3IN1Q**

1. Magnetic Wireless Output for smartphone: 15W(9V/1.66A), 10W(9V/1.11A), 7.5W(9V/0.83A), 5W(5V/1A)
2. Wireless output for iWatch 3W
- Wireless output for Airpod 5W
3. Charge current: 5V/1.5A, 9V/1.10A
4. Distance: 5mm
5. Foldable design

COLOR



LED

