



Oulan Top selling products

Shandong Oulan steel Co.,Ltd

Address: Room 511, Zhongke Innovation
Park, ,Liaocheng ,Shandong Province,China

Web: www.oulansteel.com



COMPANY PROFILE

We are a professional metal raw material manufacturer located in Shandong China. Over more than 10 years experiences in the steel field, we have developed into a well-known brand in China. Our products includes galvanized steel coil, galvalume steel coil, PPGI, PPGL, cold rolled steel coil, stainless steel coil, aluminum coil, roofing sheets, spring steel strip and various special steel sheets. Our products have been exported to dozens of countries around the world.

Shandong Oulan Steel Co., Ltd. is a professional steel supplier. It has been established for more than ten years. We have our own processing center, warehouse, experienced workers and warehouse. All our employees work together as a team to meet our customers.

Our customers are all over the world. Our products are widely used in Hong Kong, Taiwan, Korea, Singapore, Malaysia, Philippines, Vietnam, Turkey, Russia, Bulgaria, Malta, Canada, Australia, Iran, Brazil, Lebanon, Vietnam and other countries.

We provide high-quality products with reasonable prices and perfect services, and exchange service and sincerity for your trust and support, creating mutual benefits and creating a win-win situation! Our company is willing to cooperate wholeheartedly with colleagues from all walks of life at home and abroad to create a better future!



Customer service

Customers are the source of enterprise development. Fully understand the needs of customers, attach importance to contracts, ensure quality, deliver on time, and strictly abide by promises. Good after sales service is the beginning of sales. We will use our sincere service to look forward to long term cooperation with customers.



Material certificate

All of our raw materials are from well-known Chinese factories, and all products are certified by the authority and comply with international standards JIS, AISI, ASTM, GB, DIN, EN, etc. Certification includes CE ISO SGS UL and so on. All our production lines are built according to the global advanced factory standards.



Retail and wholesale

We are a trusted partner to the customer around the world. We provide favourable price and good quality products in the area of retail and wholesale businesses. We can provide you with personalized and efficient solutions to meet your various requirements. Hope to achieve mutual benefit with your company and maintain a good cooperative relationship.



Package delivery

We provide customers with professional logistics services through one-stop integrated logistics solutions including air transportation, sea transportation, international express delivery, land transportation, and customs clearance. Fast and professional logistics services are an important part of our overall sales.

ABOUT US

We are also showing our good will to our clients to make cooperations, mutual benefits and promotion. Welcome to visit our factory and join us.

Sincerely hope that we can build up our good business cooperation with each other in the future through our joint efforts.

GALVANIZED COIL



PRODUCT INFO

Galvanized coil refers to a steel plate coated with a layer of zinc on the surface.Galvanizing is an economical and effective anti-corrosion method that is often used to prevent corrosion on the surface of the steel plate and extend its service life.About half of the world's zinc production is used in this process.

PRODUCT FEATURES

Strong corrosion resistance, good surface quality, good for deep processing,economical and practical, etc.

APPLICATIONS

Galvanized coils are mainly used in fields such as construction, home appliances,automobiles, containers, transportation and household industry.Especially in steel structure construction, automobile manufacturing, steel silo manufacturing and other industries.

PRODUCT PARAMETERS

Product name	Galvanized coil
Thickness	0.3-100mm
Width	600mm, 1000mm, 1219mm, 1500mm, 1800mm, 2000mm, 2500mm, 3000mm, 3500mm,
Length	2000mm, 2440mm, 3000mm, 5800mm, 6000mm, etc.
Quality test	we can offer MTC(mill test certificate)
Payment terms	T/T, L/C at sight
Stock or not	enough stock
Hardness	Annealed, 1/16 Hard, 1/8 Hard, 1/4 Hard, 1/2 Hard, Hard
Container size	20ft GP: 5898mm(Length)x2352mm(Width)x2393mm(High) 40ft GP: 12032mm(Length)x2352mm(Width)x2393mm(High) 40ft HC: 12032mm(Lengh)x2352mm(Width)x2698mm(High)
Delivery time	Within 7-10 Working Days

PRODUCT PACKAGING



GALVALUME COIL



PRODUCT INFO

Galvalume steel coil is an important alloy material often used in daily life. The galvanized steel coil is composed of aluminum-zinc alloy structure, which is composed of 55% aluminum,43% zinc and 2% silicon solidified at a high temperature of 600°C.The entire structure is composed of aluminum-iron-silicon-zinc,forming a dense four-element An alloy of crystals.

PRODUCT FEATURES

Corrosion resistance: The corrosion resistance of "aluminized zinc steel coil" is mainly due to the protective function of aluminum and aluminum. When zinc is worn, aluminum forms a dense layer of aluminum oxide, which prevents corrosion-resistant substances from further corroding the interior.

Heat resistance: aluminum-zinc alloy steel coil has good heat resistance and can withstand high temperatures of more than 300 degrees Celsius. It is similar to the high temperature oxidation resistance of aluminum-plated steel sheets. It is often used in chimney pipes, ovens, luminaires and fluorescent lampshades.

Heat reflectivity: The heat reflectivity of galvanized steel coil is very high, which is twice that of galvanized steel. People often use it as a material for heat insulation.

Economical: Because the density of 55%AL-Zn is lower than that of Zn, the area of galvanized steel coil is more than 3% larger than that of plated steel coil with the same weight and the same thickness of gold plating.

APPLICATIONS

Construction: roofs, walls, garages, soundproof walls, pipes and modular houses, etc. Automobiles: mufflers, exhaust pipes, wiper accessories, fuel tanks, truck boxes and other home appliances: refrigerator back panels, gas stoves, air conditioners, electronic microwave ovens, LCDs Frames, CRT explosion-proof belts, LED backlights, electrical cabinets and other agricultural applications: pig houses, chicken houses, granaries, greenhouse pipes, etc. Others: thermal insulation covers, heat exchangers, dryers, water heaters, etc.

PRODUCT PARAMETERS

Product Name	Aluminum zinc coil
Standard	AISI, ASTM, BS, DIN, GB, JIS
Material	Q195, Q235, Q345 SGCC, SGCH,SGC340 SGC400 SGC440 SGC490 SGC570 SGHC SGH340 SGH400 SGH440 SGH490 SGH540 DX51D DX52D DX53D DX54D
Thickness	0.12-2.0mm
Zinc Layer	20-275g/m2
Width	600-1250mm
Zinc Spangle	Zero Spangle,Regular Spangle,Minimum Spangle
Grade	Full hard/CS-A, B, C/FS-A/B/DQ/ SS-33, 37, 40, 50 and 80
Shape	Grades as per ASTM/EN/JIS/SASO Coil, strip, flat,sheet, plate, etc.
Application	Building materials, steel structure, home construction, roofing sheets, etc.
Product Features	Good performance, high precise, high straightness, high evenness and surface finishing, uniform thickness, easy for coating process, high tensile strength, high pressing property and low yield point

PRODUCT PACKAGING



PPGI/PPGL



PRODUCT INFO

Color-coated coil is a product made of hot-dip galvanized sheet, hot-dip galvanized sheet,electro-galvanized sheet,etc.as the substrate.After surface pretreatment, one or several layers of organic paint are applied on the surface, and then baked and cured. It is also named because of the color steel coils coated with organic coatings of various colors,referred to as color coated coils.

PRODUCT FEATURES

- (1) It has good durability, and its corrosion resistance is longer than that of galvanized steel;
- (2) It has good heat resistance and is less prone to discoloration at high temperatures than galvanized steel sheets;
- (3) It has good heat reflectivity;
- (4) It has processing performance and spraying performance similar to that of galvanized steel sheet.
- (5) It has good welding performance.
- (6)It has a good performance-to-price ratio, durable performance and a very competitive price.

APPLICATIONS

Mainly used in the advertising industry, construction industry, home appliance industry, electrical appliance industry, furniture industry and transportation industry.

PRODUCT PARAMETERS

Product	PPGI/PPGL Steel Coil
Width	0.6m-3m or as your requirement
Thickness	0.1mm-300mm or as your requirement
Standard	AISI,ASTM,DIN,JIS,GB,JIS,SUS,EN,etc.
Technique	Hot rolled
Surface Treatment	Clean, blasting and painting according to customer requirement
Thickness	±0.15mm
Material	Q345,Q345A,,Q345B,Q345C,Q345D,Q345E,Q235 HC340LA,HC380LA,HC420LAB340LA,B410L A15CRMO,12Cr1MoV,20CR,40CR,65MN
Coatings	Top Coats :5 micron primer + 20 micron colour Back
MOQ	25tons.We also can accept sample order.
Shipment time	Within 15-20 working days after receiving the deposit
Export packing	Waterproof paper, and steel strip packed. Standard Export Seaworthy Package.Suit for all kinds of transport,or as required

PRODUCT PACKAGING



ROOFING SHEET



PRODUCT INFO

Color steel tile, also known as: color profiled tile, is a profiled plate that uses color coated steel plate and is rolled and cold-formed into various wave shapes. It is suitable for industrial and civil buildings, warehouses, special buildings, roofs, walls and interior and exterior wall decorations of large-span steel structure houses, etc. It has light weight, high strength, rich color, convenient and fast construction, earthquake resistance, fire prevention, rain protection, and longevity. Long, maintenance-free and other characteristics have been widely promoted and applied.

PRODUCT FEATURES

- 1. Light weight: 10-14 kg/m², equivalent to 1/30 of a brick wall.
- 2. Thermal conductivity: $\lambda \leq 0.041 \text{ W/mK}$.
- 3. High strength: It can be used as a load-bearing board for ceiling enclosure structure, resisting bending and compression; beams and columns are not used in general houses.
- 4. Bright color: no surface decoration is required, and the anticorrosive layer of the color galvanized steel plate can be kept for 10-15 years.
- 5. Flexible and quick installation: the construction period can be shortened by more than 40%.
- 6. Oxygen Index: (OI) 32.0 (provincial fire product quality inspection station).

APPLICATIONS

It is widely used in the walls and roofs of large public buildings, public factories, prefabricated houses, and integrated houses.

PRODUCT PARAMETERS

Standard	ISO, JIS, AS EN, ASTM
Thickness (mm)	0.12-5.0mm as your requirement
Width (mm)	600mm-1250mm as your requirement
Length(mm)	1000-20000mm as required
Range Of Application	Purification workshop, industrial workshop, screen, ceiling, shutter door, etc
Grade	Q195, Q235, Q345
	SGCC, SGCH, SGC340 SGC400 SGC440 SGC490 SGC570
	SGHC SGH340 SGH400 SGH440 SGH490 SGH540
	DX51D DX52D DX53D DX54D
	S220GD S250GD S280GD S320GD S350GD S400GD S500GD S550GD
Surface Treatment	Deoiling, drying, chromate passivation, non-chromate passivation
Surface Type	Wooden, Stone, High Glossy, Film, Wrinkled, Embossed, Camouflage, Printing, White Board
Paint Kind	PE, SMP, HDP, PVDF
Technical Parameters	Color coating : Maximum 30um/25um (top side/back side)
	T bend: 0T 1T 2T 3T
	Glossy : High, Medium, Low
	Impact : 9J 12J
	Pencil hardness: 3H
	MEK: 100 times
	Salt spray test: 5000 hours
	UV test: 3500 Hours

PRODUCT PACKAGING

