SAMPOS 声宝仕

广东声宝仕电子有限公司
GUANGDONG SAMPOS ELECTRONICS CO.,LTD
东莞市东城丰盛泰电子厂
DONGGUAN FONSTA ELECTRONICS FACTORY
工厂地址:东莞市东城区下桥工业园D栋
Fty Add:Xiaqiao Industrial Park, Dongcheng District, Dongguan,523112, China
电话(Tel):+86-769-22676911/22676915
传真(Fax):+86-769-22676995
网站(Web):www.sampos.cn
邮箱(E-mail):sales@sampos.cn

WT-8258



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WT-815



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WT-8810



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WA-8819



Bluetooth version:V5.0
Battery:400 mAh rechargeable lithium battery
Charge time:3H
Work time:6-8h(Bluetooth+ANC) 24h(ANC only)20h(Bluetooth only)
Working distance:≥10M
Frequency Response: 20Hz-20KHz
Charging Port: micro usb
Charger adapter output: DC 5V& 1A
Sensitivity: 119±3dB

WT-8820



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WT-8780



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WA-8356



Battery capacity: 400mAh
Driver diameter: 40mm
Sensitivity: 110B±3dB
Power Supply: 5V DC
Receiver Distance: 10m
Bluetooth verison:V5.0
Charging time: 2H
Playing time: 8H

WA-8809



Bluetooth version:V5.0
Battery:400 mAh rechargeable lithium battery
Charge time:3H
Work time:6-8h(Bluetooth+ANC) 24h(ANC only)20h(Bluetooth only)
Working distance:≥10M
Frequency Response: 20Hz-20KHz
Charging Port: micro usb
Charger adapter output: DC 5V& 1A
Sensitivity: 119±3dB



SP-X50



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X9



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X18



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X45



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X40



Speaker size:Φ50mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:118dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

HT-775



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X39



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X21



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X26



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X53



Speaker size:Φ50mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:118dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

SP-X41



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m

HT-788



Speaker size:Φ40mm
Frequency range:20-20,000Hz
Speaker impedance:32 Ohm
Speaker sensitivity:115dB±3dB
Mic Frequency:16Hz-20,000Hz
Mic Impedance:2,200 Ohms
Plug: 3.5mm*1/USB
Length of cable:approx. 2.0m