



Shenzhen Qianfeng Communication Equipment Co., Limited

ADD.:Room 412 Building #1 Youchuang Space Qunhui Rd. No.1 Baoan District Shenzhen 518101
WEB.: www.qianfengtek.com TEL.:+86 755 2330 0250

CATALOG

Items	Style	Model Number #	Pictures	Specification	Functions	Packing Details
GPS Tracker	Standard Series	QS109		1. Working Voltage: 9-90V DC 2. Internal Battery Capacity: 150mAh 3.7V 3. Working Temperature: -20°C to +60°C 4. Storage Temperature: -20°C to +70°C 5. GSM Module: MT2503 6. Network: 2G 7. Tracking Sensitivity: -162dbm 8. Navigation Sensitivity: -160dbm 9. Location Accuracy: <5m 10. Cold Start: Average 32 seconds 11. Transmission Protocol: TCP 12. Weight: 30.5g (including Internal Battery Capacity) 13. Dimension: 74*25*14 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. ACC Detection 3. Vibration Alert 4. Device Disconnection Alert 5. Overspeed Alert 6. Low Battery Alert 7. GEO Fence 8. Historical Route 9. Cut off/Resume oil(optional, relay required)	1. Accessories: Device, User manual, Power cord 2. Weight: 85g/set 3. Box dimension: 11.7*8.8*3.5cm 4. Carton dimension: 47*31*34.5cm 5. Packing: 100sets/CTN 6. Weight: 8.9kg/CTN
GPS Tracker	Standard Series	QS111		1. Working Voltage: 9-90V DC 2. Internal Battery Capacity: 150mAh (3.7V) 3. Working Temperature: -20°C to +60°C 4. Storage Temperature: -20°C to +70°C 5. GSM Module: SIMCom A7670SA 6. GPS Chip: UC6228CI 7. Network: 2G/4G 8. Tracking Sensitivity: -162 dbm 9. Navigation Sensitivity: -160dbm 10. Location Accuracy: <5m 11. Cold Start: Average 32 seconds 12. Transmission Protocol: TCP 13. Weight: 48.5g (including Internal Battery Capacity) 14. Dimension: 80*34*17 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. ACC Detection 3. Vibration Alert 4. Device Disconnection Alert 5. Overspeed Alert 6. Low Battery Alert 7. GEO Fence 8. Historical Route 9. Cut off/Resume oil(optional, relay required)	1. Accessories: Device, User manual, Power cord 2. Weight: 115 g/set 3. Box dimension: 12*8*4cm 4. Carton dimension: 42*25.8*25.2 cm 5. Packing: 100 sets/CTN 6. Weight: 12 kg/CTN
GPS Tracker	Standard Series	QS111R		1. Working Voltage: 9-95V DC 2. Internal Battery Capacity: 60mAh 3.7V 3. Working Temperature: 20°C-75°C 4. GSM Module: Simcom7670SA 5. GPS Chip: Quectel L76K 6. Network: 2G/4G 7. Tracking Sensitivity: -162dbm 8. Navigation Sensitivity: -160dbm 9. Location Accuracy: <10m 10. Average Cold Start: <32 sec; Average Hot Start: ≤ 3sec(open sky) 11. Transmission Protocol: TCP 12. Weight: 42g (including Internal Battery Capacity) 13. Dimension: 79*32*18 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. ACC Detection 3. Vibration Alert 4. Device Disconnection Alert 5. Overspeed Alert 6. Low Battery Alert 7. GEO Fence 8. Historical Route 9. Cut off/Resume oil(optional, relay required)	1. Accessories: Device, User manual, Power cord 2. Weight: 100g/set 3. Box dimension: 12*8*4cm 4. Carton dimension: 39.5*23.5*26.5cm 5. Packing: 50sets/CTN 6. Weight: 5kg/CTN



Shenzhen Qianfeng Communication Equipment Co., Limited

ADD.:Room 412 Building #1 Youchuang Space Qunhui Rd. No.1 Baoan District Shenzhen 518101
WEB.: www.qianfengtek.com TEL.:+86 755 2330 0250

CATALOG

Items	Style	Model Number #	Pictures	Specification	Functions	Packing Details
GPS Tracker	Multi-functional Series	QM105		1. Working Voltage: DC 9V - 95V 2. Internal Battery Capacity: 180mAh 3.7V 3. Working Temperature: -20℃ - 75℃ 4. Storage Temperature: -30℃ - 80℃ 5. Working Humidity: 10%-85% RH 6. GPS Module: AT6558R 7. Communication Module brand/Chip Module: EC200SCN 8. Network: 2G/4G 9. Tracking Sensitivity: -162dbm 10. Capture Sensitivity: -148dbm 11. Location Accuracy: <10m 12. Cold Start: Average 32 seconds, Hot Start: Average 1 seconds 13. Weight: 82g 14. Dimension: 99* 52* 18 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. ACC Detection 3. Vibration Alert 4. Device Disconnection Alert 5. Overspeed Alert 6. Low Battery Alert 7. SOS Alert 8. GEO Fence 9. Historical Route 10. External MIC 11. SOS Button 12. Cut off/Resume oil(optional, relay required)	1. Accessories: Device, User manual, Power cord 2. Weight: 196 g/set 3. Box dimension: 14.2*8.5*5.5 cm 4. Carton dimension: 47*30.5*33.5 cm 5. Packing: 100 sets/CTN 6. Weight: 23.5 kg/CTN
OBD (Built-in GPS Tracker)	Hidden Series	QH302		1. Working Voltage: 12V DC 2. Internal Battery Capacity: 180mAh 3.7V 3. Working Temperature: -20℃ to +60℃ 4. Storage Temperature: -20℃ to +70℃ 5. Main Chip: MT6261DA 6. GPS Chip: AT6558 7. Network: 2G 8. Tracking Sensitivity: -162dbm 9. Navigation Sensitivity: -160dbm 10. Location Accuracy: <5m 11. Cold Start: Average 32 seconds 12. Transmission Protocol: TCP 13. Weight: 32g (including Internal Battery Capacity) 14. Dimension: 46*25*32 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. Vibration Alert 3. Device Disconnection Alert 4. Overspeed Alert 5. Low Battery Alert 6. GEO Fence 7. Historical Route	1. Accessories: Device, User manual 2. Weight: 76 g/set 3. Box dimension: 12*8*2.8 cm 4. Carton dimension: 47*30.5*33.5 cm 5. Packing: 100 sets/CTN 6. Weight: 8.3 kg/CTN
OBD (Built-in GPS Tracker)	Hidden Series	QH302R		1. Working Voltage: 12-24V DC 2. Internal Battery Capacity: 100mAh 3.7V 3. Working Temperature: -20℃ to +60℃ 4. Storage Temperature: -20℃ to +70℃ 5. GSM Module: SIMCOM-A7670C 6. GPS Chip: AT6558R 7. Network: 4G 8. Tracking Sensitivity: -162dbm 9. Navigation Sensitivity: -160dbm 10. Location Accuracy: <5m 11. Cold Start: Average 32 seconds 12. Transmission Protocol: TCP 13. Weight: 42g (including Internal Battery Capacity) 14. Dimension: 49*38.6*33.4mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. Vibration Alert 3. Device Disconnection Alert 4. Overspeed Alert 5. Low Battery Alert 6. GEO Fence 7. Historical Route	1. Accessories: Device, User manual 2. Weight: 100 g/set 3. Box dimension: 12*8*2.8 cm 4. Carton dimension: 47*30.5*33.5 cm 5. Packing: 100 sets/CTN 6. Weight: 11 kg/CTN



Shenzhen Qianfeng Communication Equipment Co., Limited

ADD.:Room 412 Building #1 Youchuang Space Qunhui Rd. No.1 Baoan District Shenzhen 518101
WEB.: www.qianfengtek.com TEL.:+86 755 2330 0250

CATALOG

Items	Style	Model Number #	Pictures	Specification	Functions	Packing Details
Magnetic GPS Tracker	Hidden Series	QH411		1. Internal Battery Capacity: 6000 mAh/10000 mAh /20000 mAh(3.7V) optional 2. charging voltage: DC 3.54-4.5V 3. Working Temperature: 20℃-75℃ 4. GSM Module: SIMCOM-A7670SA 5. Network: 4G/2G 6. Location Accuracy: <10m 7.Transmission Protocol: TCP 8. Weight & Dimension: 6000 mAh: 206g, 121*65*27 mm 10000 mAh: 296.5g, 121*65*32 mm 20000 mAh: 460g, 121*69*34 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. Vibration Alert 3. Overspeed Alert 4. Low Battery Alert 5. GEO Fence 6. Historical Route 7. Waterproof IP65	1. Accessories: Device, User manual, Charging cord 2. Weight & Box dimension: 6000 mAh: 362.5g/set, 15.1*15.1*4 cm 10000 mAh: 469.5g/set, 15.1*15.1*5.9 cm 20000 mAh: 647g/set, 15.1*15.1*5.9 cm 3. Carton dimension: 47*29.5*32.5 cm 4. Packing & Weight: 6000 mAh: 40 sets/CTN, 14.9 kg/CTN 10000 mAh: 30 sets/CTN, 14.65 kg/CTN 20000 mAh: 30 sets/CTN, 19.5 kg/CTN
Magnetic GPS Tracker	Hidden Series	QH415		1. Internal Battery Capacity: 1500 mAh/2500 mAh/5000 mAh optional 2. charging voltage: DC 3.54-4.5V 3. Working Temperature: 20℃-75℃ 4. GSM Module: SIMCOM-A7670SA 5. Network: 4G/2G 6. Location Accuracy: <10m 7.Transmission Protocol: TCP 8. Weight & Dimension: 1500 mAh: 42g, 53*31*21 mm (No magnet) 2500 mAh: 96g, 78*54*14 mm 5000 mAh: 132g, 78*54*21 mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. Vibration Alert 3. Overspeed Alert 4. Low Battery Alert 5. GEO Fence 6. Historical Route 7. Waterproof IP65	1. Accessories: Device, User manual, Charging cord 2. Weight & Box dimension: 1500 mAh: 118g/set, 12*7.2*4.5 cm 2500 mAh: 159g/set, 12*7.2*4.5 cm 5000 mAh: 205g/set, 12*7.2*4.5 cm 3. Carton dimension: 47*29.5*32.5 cm 4. Packing & Weight: 1500 mAh: 100 sets/CTN, 12.5 kg/CTN 2500 mAh: 100 sets/CTN, 16.5 kg/CTN 5000 mAh:100 sets/CTN, 21.2 kg/CTN
Magnetic GPS Tracker	Hidden Series	QH416		1. Internal Battery Capacity: 4200 mAh (3.0V lithium manganese battery CR123A*2) 2. Working voltage: DC 2.5 - 3.6V 3. Working Temperature: -20℃-75℃ 4. GSM Module: SIMCOM-A7670SA 5. Network: 4G/2G 6. Location Accuracy:<10m 7. Transmission Protocol: TCP 8. Weight: 120g 9. Dimension: 73.5*42.8*31.2mm	1. GPS+Beidou+LBS Multi-Mode Positioning 2. Vibration Alert 3. Overspeed Alert 4. Low Battery Alert 5. GEO Fence 6. Historical Route 7. 3 years of ultra-long standby	1. Accessories: Device, User manual, Charging cord 2. Weight: 174 g/set 3. Box dimension: 10.5*7.1*4.5 cm 4. Carton dimension: 47*30*33 cm 5. Packing: 100 sets/CTN 6. Weight: 18.2 kg/CTN



Shenzhen Qianfeng Communication Equipment Co., Limited

ADD.:Room 412 Building #1 Youchuang Space Qunhui Rd. No.1 Baoan District Shenzhen 518101
WEB.: www.qianfengtek.com TEL.:+86 755 2330 0250

CATALOG

Items	Style	Model Number #	Pictures	Specification	Functions	Packing Details
Pets GPS Tracker	Pets Series	QP103		1. Internal Battery Capacity: 700 mAh(3.7V) 2. Working Voltage: DC 3.4V - 4.5V 3. Working Current: 4V/60mA 4. Standby Current: 4V/5mA 5. Working Temperature: -20℃ - 75℃ 6. Storage Temperature: -30℃ - 80℃ 7. Working Humidity: 10%-85% RH 8. GSM Module: MC25, A7670C, A7670E, A7670SA optional 9. GPS Chip: AT6558R 10. Network: 4G, 2G optional 11. GPS Location Accuracy: <10m 12. Weight: 42.2g 13. Dimension: 75.8*37.6*19 mm	1. GPS+Beidou+LBS+Multi -Mode Positioning 2. Waterproof IP67 3. Monitoring by Web platform/ Phone App/ SMS 4. Historical Route 5. GEO Fence 6. Low Battery Alert 7. Sound Seeks Pets 8. Light Seeks Pets 9. Charge: Magnetic Charging	1. Accessories: Device, Charging cord, User manual 2. Weight: 130 g/set 3. Box demensions: 10*10*4cm 4. Carton demensions: 47*29.5*32.5 cm 5. Packing: 96sets/CTN 6. Weight: 13.5kg/CTN
Pets GPS Tracker	Pets Series	QP106		1. Internal Battery Capacity: 700 mAh(3.7V) 2. Working Voltage: DC 3.4V - 4.5V 3. Working Current: 4V/60mA 4. Standby Current: 4V/5mA 5. Working Temperature: -20℃ - 75℃ 6. Storage Temperature: -30℃ - 80℃ 7. GSM Module: EG915ULA 8. Positioning method: BDS/GPS/GLONASS 9. GPS Chip: AT6558R 10. Network: 4G 11. GPS Location Accuracy: <10m 12. Weight: 36g 13. Dimension: 51*40*17 mm	1. GPS+Beidou+LBS+Multi -Mode Positioning 2. Waterproof IP67 3. Monitoring by Web platform/ Phone App/ SMS 4. Historical Route 5. GEO Fence 6. Low Battery Alert 7. Sound Seeks Pets 8. Light Seeks Pets 9. Charge: Magnetic Charging	1. Accessories: Device, Charging cord, User manual 2. Weight: 130 g/set 3. Box demensions: 10*10*4cm 4. Carton demensions: 47*29.5*32.5 cm 5. Packing: 96sets/CTN 6. Weight: 13.5kg/CTN